



Cross Section at Flat



PART NUMBER	PAIRS	COND	A SPAN		B SPAN		Ref Dia
			Inches	(mm)	Inches	(mm)	
159-2832-010	5	10	0.526	(13,36)	0.450	(11,43)	.300
159-2832-014	7	14	0.726	(18,44)	0.650	(16,51)	.330
159-2832-016	8	16	0.826	(20,98)	0.750	(19,05)	.340
159-2832-020	10	20	1.026	(26,06)	0.950	(24,13)	.380
159-2832-026	13	26	1.326	(33,68)	1.250	(31,75)	.410
159-2832-034	17	34	1.726	(43,84)	1.650	(41,91)	.450
159-2832-040	20	40	2.026	(51,46)	1.950	(49,53)	.480
159-2832-050	25	50	2.526	(64,16)	2.450	(62,23)	.520
159-2832-060	30	60	3.026	(76,86)	2.950	(74,93)	.560
159-2832-064	32	64	3.226	(81,94)	3.150	(80,01)	.570
159-2832-068	34	68	3.426	(87,02)	3.350	(85,09)	.580

PHYSICAL

- Conductors: 28 AWG 7/36 Tinned Copper
- Insulation: .010" PVC
- Laminate: (2) .005" Clear PVC
- Color Code: Tan Common: Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White, Black and Repeat.
- Shielding: .001" Aluminum/Polyester with 85% minimum coverage Tinned Copper Braid
- Jacket: .030" Black PVC
- Temperature: 105°C

ELECTRICAL

- Impedance: 70 ohms
- Capacitance: 25 pF/ft at 1MHz
- Prop Delay: 1.65 ns/ft
- Current Rating: 1.3 A at 10°C Rise Above Ambient
- Voltage Rating: 300 V
- Insulation Res: 10¹⁰ ohms - 10 ft minimum
- Approvals: UL Listed Type CL2
CSA AWM FT-1
- Above Values calculated in the ground-signal Configuration
- Shielding Variations: -1XX Foil Only; -2XX No Shield with Polyester Wrap.
- Note: Reference Diameters are .030" to .040" smaller

All Dimensions in Inches Unless Otherwise Noted.

DRAWN	PROD ENG	QA	MKT	P/ECN#	DRAWING NO. 159-2832-0XX	AMPHENOL SPECTRA-STRIP 720 SHERMAN AVE TEL (203) 281-3200 HAMDEN CT 06514 FAX (203) 281-5872	Rev L
TITLE: Round Twist 'N' Flat® Cable					SHEET 1 of 1		

FlTS
2/21/01

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Flat Cables](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[F28-A25G](#) [F28-A34G](#) [F28-A36G](#) [FST-23A-15](#) [AYT1510-US](#) [171-37G](#) [C336514-500](#) [902220736002000](#) [902220736006000](#) [28100-0614](#)
[9L28010-008-H300](#) [9L28014-008-H300](#) [F28-A24G](#) [F28-A60G](#) [25WDY00002](#) [28100-0571](#) [28100-0602](#) [28100-0650](#) [28100-0664](#) [336506-](#)
[100SF](#) [336512-300](#) [336518](#) [336537-CUT-LENGTH](#) [3447/10-100](#) [362514100MSF](#) [40WDY00005](#) [AYT51163](#) [336506-300](#) [C3302/16](#)
[C374910](#) [3749/10-100](#) [375630](#) [3-971111-6](#) [1-1437356-3](#) [812504](#) [20WDY00001](#) [5-1437214-8](#) [3355/15](#) [40WBY00007](#) [3609/12](#) [5111196336](#)
[607.5689.087](#) [607.5689.091](#) [3801/04](#) [8124/04](#) [3801/12](#) [3625/22100MSF](#) [902220736005000](#) [902220736004000](#) [C3811/10-100](#)