



NOTES:

1. MATERIALS AND FINISHES:  
 MMCX STR PLUG - BRASS, GOLD PLATING  
 CABLE - RG 178/U
2. ELECTRICAL:  
 A. IMPEDANCE: 50 OHM
3. PACKAGING:  
 A. QUANTITY: SINGLE PACK  
 B. MARKING: BAG TO BE MARKED  
 "AMPHENOL RF, 265101-08-XX.XX AND DATE CODE"

THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
--	RELEASED TO MFG.	--	--	--
B	FORMAT UPDATED, 48.00", METRIC LENGTHS ADDED & HST LENGTHS UPDATED IN LENGTH TABLE	21-Oct-16	2201	AG
C	60.00", 72.00", 84.00", 96.00" & 102.00" LENGTHS ADDED	11-Oct-18	9342	VR



LENGTH TABLE			
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH 'L' IN INCHES [METERS]	LENGTH 'X' IN INCHES [METERS] MIN
265101-08-06.00	-	6.00 [0.152]	0.75 [0.019]
-	265101-08-M0.25	9.84 [0.250]	
265101-08-12.00	-	12.00 [0.305]	
265101-08-18.00	-	18.00 [0.457]	1.50 [0.038]
-	265101-08-M0.50	19.69 [0.500]	
265101-08-24.00	-	24.00 [0.610]	
-	265101-08-M0.75	29.53 [0.750]	
265101-08-36.00	-	36.00 [0.914]	
-	265101-08-M1.00	39.37 [1.000]	
265101-08-48.00	-	48.00 [1.219]	
-	265101-08-M2.00	78.74 [2.000]	
-	265101-08-M4.00	157.48 [4.000]	
265101-08-60.00	-	60.00 [1.524]	
265101-08-72.00	-	72.00 [1.829]	
265101-08-84.00	-	84.00 [2.134]	
265101-08-96.00	-	96.00 [2.438]	
265101-08-102.00	-	102.00 [2.591]	

TOLERANCE TABLE	
LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

- FREQUENCY: ---- TO ---- GHz     CONTINUITY  
 VSWR: ---- MAX     HI-POT: 300 VRMS  
 INS. LOSS: ---- dB MAX     OTHER

**CUSTOMER OUTLINE DRAWING**

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL    3 PLACE DECIMAL    ANGLES ±.015 (0.381 mm)    ±.005 (0.127 mm)    ± 1°	MATERIAL	DRAWN	DATE	TITLE	Amphenol RF www.amphenolrf.com	
	SEE NOTES	ANANDH G	30-Sep-16	MMCX STR PLUG TO MMCX STR PLUG, USING RG 178/U CABLE VARIOUS LENGTH		
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	REFERENCE EAR #	ENGINEER	DATE	SCALE: 2.8:1.0 SHEET 2 OF 2	DRAWING NO. 265101-08-XX-XX	
	CONFIGURATION LEVEL: In Work	APPROVED	KARTHIK R	11-Oct-18		ITEM NO. 265101-08-XX-XX
	FINISH	K. CAPOZZI	CAD FILE		DWG SIZE B    REV C	PART NO. 265101-08-XX-XX

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Cable Assemblies](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[73-6352-10](#) [73-6353-3](#) [73-6364-6](#) [R285001001](#) [R288940004](#) [R288940005](#) [145111-05-12.00](#) [1661-C-24](#) [1801171170914KE](#) [24P104C24J1-012](#) [24P104C24P1-006](#) [24P104C24P1-018](#) [24P204C24J1-003](#) [172-2150-EX](#) [1800920920914PJ](#) [FCB-3030-ALT](#) [21117-046](#) [21117-050](#) [PCX-24-50](#) [24P103C24P2-003](#) [25P203C25P2-003](#) [PTWY-24-78](#) [R284008001](#) [R285001021](#) [R285426000](#) [R288940003](#) [R288940008](#) [RF179-74BJ3-77RP1-0305](#) [4814-BB-24](#) [5260-72](#) [JT2N1-CL1-1F](#) [DLP-COAX1](#) [4814-K-48](#) [115101-09-06.00](#) [CCNTN2-MM-LL335-26](#) [73-6351-25](#) [73-6352-3](#) [73-6353-25](#) [1800920920610PJ](#) [GD0BQ0BQ024.0](#) [1-3636-600-5210](#) [TL8A-11SMA-11SMA-01500-51](#) [R284C0351060](#) [R288940009](#) [R284C0351028](#) [R288940002](#) [9702-1SL-1](#) [PT82NSMA](#) [73-6353-10](#) [R285020301W](#)