

PL-500SM-N FEATURES

Ideal for front-panel instrumentation and hand-held equipment, the compact and cost effective PL-500 Series is designed to meet the efficient packaging demands of portable electronic devices

Packaging (intuitive, compact, configurable)

- Pulse-Lok® auto-latch / mating confirmation
- Miniature .520" diameter circular shell
- Up to 14 contact positions
- 14 standard color combinations
- Multiple and proprietary keying options
- Available as an overmolded cable assembly
- Custom configurations available

Performance (for harsh environments)

- Water proof (IP-67 rated)
- Steam, EtO, & Gamma sterilizable
- Chemical resistant housing
- Up to 5,000 mating cycles (with std. Contacts)
- Factory terminated, overmolded cable assemblies for enhanced flex and strain relief

SPECIFICATIONS

Electrical (see below)

Mating Life: 5,000 cycles min.
Contact Resistance: < 10 milliohms*

Material

Connector Housing: Nylon 12
Flex Reliefs: Thermoplastic Rubber
Contacts: Brass / BeCu,
Gold Plate per MIL-G-45204

Mechanical

Mating Cycles: 20K cycles max
Retention Force:
• Mated Connectors: 25 lbs. Minimum
• Cable to Connector: to 30 lbs. typical
• Backshell to Connector: 50 lbs. Minimum


Environmental

- Operating Temp: -20C to +85C
- Moisture Resistance: to IP-67 (encapsulated)
- Sterilizable: gamma, EtO & Autoclave
- Chem. Resistance: common OR cleaning solvents
* post conditioning

TABLE A: STANDARD CONTACT CONFIGURATIONS & SPECIFICATIONS

Number of Poles	Contact Size Pin ϕ (mm)	Max Wire Gauge	Operating Voltage max	Operating Current Max	Contact Resistance
14	0.5	28	300 V RMS	.9 A	< 14m ohms
10	0.5	28	300 V RMS	1.2 A	< 14m ohms
8	0.7	22	300 V RMS	1.8 A	< 6m ohms
7	0.7	22	300 V RMS	2.1 A	< 6m ohms
6	0.7	22	300 V RMS	2.1 A	< 6m ohms
5	0.7	22	300 V RMS	2.4 A	< 6m ohms
4	0.7	22	300 V RMS	2.4 A	< 6m ohms
3	0.7	22	300 V RMS	3.0 A	< 6m ohms
2	0.7	22	300 V RMS	3.0 A	< 6m ohms
1	0.7	22	300 V RMS	3.0 A	< 6m ohms
1	1.5	16	300 V RMS	7.0 A	< 2m ohms

**Up to 14
contact positions**



Custom contact inserts are available. Consult factory.

STANDARD HOUSING OPTIONS

In-Line Receptacle Assembly



2.05

Shown with overmolded strain relief
(Refer to PL Series Overmolding Guide)


In-Line Receptacle Kit (for overmolding)



1.43

Select this component from Table B

Panel-Mount Receptacle Assembly



Panel thickness range = .063 to .125


Panel-Mount Receptacle



1.02

Select this component from Table B


In-Line Plug Assembly



2.00

Shown with Overmolded Strain Relief
(Refer to PL Series Overmolding Guide)

In-Line Plug Kit (for overmolding)



1.35

Select this component from Table B

Connector housings are illustrated in blue with gray couplers and backshells. Standard color is black on black. See our online configurator for color options at: www.aldenproducts.com/configurator

* All dimensions shown in inches except where indicated

For additional information about this, or any other Alden product, please contact an Amphenol Alden specialist today.

Phone: 508-427-7000
Fax: 508-583-0164
www.amphenolalden.com

PL-500SM-N SERIES

Plastic Shell Auto-Coupling Connectors

14 Pole Capacity Miniature Circular Connectors

TABLE B:

STANDARD PART NUMBERS

Number of Poles	In-Line Receptacle	Panel-Mount Receptacle		In-Line Plug
	Solder Cup	Solder Cup	PCB	Solder Cup
14	320679	320483	320875	320182
10	320651	320455	320847	320126
8	320637	320441	320833	320098
7	320630	320434	320826	320084
6	320623	320427	320819	320070
5	320616	320420	320812	320056
4	320609	320413	320805	320042
3	320602	320406	320798	320028
2	320595	320399	320791	320014
1 (.7mm Pin)	320588	320392	320784	320000
1 (1.5mm Pin)	321022	321008	N/A	320980

Note: Part numbers cover black housings in Key 1 configuration. For other color and housing options utilize the Alden connector configurator located @ www.aldenproducts.com/configurator

Options Include:


Housing Color Options
Mating Key Options
Panel-Mount Thickness Options

Black, Gray, White, Blue, Red, Green, Yellow
2 Standard Keys, Proprietary Keys Available
Up to .125 Standard

CONTACT TERMINATION OPTIONS

Termination Options Receptacles & In-Line Plug


PCB (Panel-Mount Receptacle only)



stand off height.050"
pin length .125"


Request sales drawing SD-106999 for PCB mounting templates

Solder Cup (available on all)



Tiered & Canted for ease of assembly

Panel-Mount, Cut-Out Template



Receptacle Dust Cover



Alden P/N 107976

Assembly Instructions

AI-PL500-01 Receptacle


AI-PL500-02 Plug

Available at:

www.aldenproducts.com

ACCESSORIES

Receptacles



1 Receptacle Housing
2 Receptacle Core

In-Line Plug



1 Plug Core
2 Plug Housing Assembly

CONNECTOR ASSEMBLY TOOLS

Receptacles

Item	Alden P/N	Description	Application
1	109099-77	Solder Nest	Receptacle Core
2	390052	Insertion Tool	Receptacle Core 224 IGA
3	390253	Insertion Tool	Receptacle Core 224 IGA
4	390032-77	Spanner Wrench	Receptacle Mounting Ring

In-Line Plug

Item	Alden P/N	Description	Application
1	108077-77	Solder Nest/Assembly Base	Plug Core

For additional information about this, or any other Alden product, please contact an Amphenol Alden specialist today.

Phone: 508-427-7000
Fax: 508-583-0164
www.amphenolalden.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular Push Pull Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[6407-249V-11273P](#) [6408-201V-13273](#) [6408-202V-13343](#) [6408-202V-17343](#) [EZG.0B.309.CLN](#) [FFA.2S.310.ZLA](#) [FGA.1B.307.CYCD72Z](#)
[FGJ.1B.304.CLLD76](#) [FGJ.1B.306.CWLD72](#) [FGJ.2B.302.CYMD82Z](#) [FGJ.2B.310.CYMD72Z](#) [FGJ.3B.304.CYMD10Z](#)
[FGJ.3B.304.CYMD82Z](#) [FHJ.2B.310.CLLD72](#) [PCS.01.250.DLLE24](#) [PHG.0K.305.CYMC40Z](#) [PHG.1K.308.CLLK85](#) [PKG.M0.6BL.LZ](#)
[PLC.M1.0SL.LA](#) [GMA.10.290.DN](#) [GMA.3B.090.DA](#) [PRG.M0.6GL.LC52GZ](#) [PSA.1S.275.CTLC66](#) [ABF.1S.250.NTA](#) [133020F](#)
[1331ER193MZ](#) [1332M107MZ](#) [DTS26Z19-32JA-LC](#) [DTS26Z19-32SA](#) [DTS26Z19-32SA-LC](#) [DTS26Z23-55HA](#) [DTS26Z23-55HA-LC](#)
[DTS26Z23-55JA-LC](#) [EAJ.1B.306.CWA](#) [ECG.XB.312.CLL](#) [1589430-2](#) [EEA.0B.305.CLN](#) [EEA.0B.309.CLL](#) [ELF.00.250.NTL](#)
[ERA.01.250.DLL](#) [BRD.0B.200.PCSG](#) [BRR.2S.200.PZVG](#) [HR10A-P](#) [CAH.M34.SLL.C72GZ](#) [CAJ.M34.SLL.C72GZ](#) [300500](#)
[ESB.00.303.NLL](#) [EXG.0B.309.HLN](#) [FFB.1S.250.CLAC27](#) [FFG.1B.306.CLAZ](#)