





**MATERIAL:** 

STAINLESS STEEL PER ASTM A630, ALLOY UNS S17400, CONDITION A. BODY:

PUSH ROD &

STAINLESS STEEL PER AMS-5640, ALLOY UNS S30300, TYPE 1 PLUNGER:

SPRING: MUSIC WIRE

FINISH:

PUSH ROD & PLUNGER: PASSIVATED PER AMS-2700.

ELECTROLESS NICKEL PER SAE 2404, CLASS 1 BODY:

NOTES:

REMOVAL TOOL FOR 3221-40020. USED ON 67.X CONTACTS, RESPECTIVELY 1. 2.

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES:		
FINISH:	SEE NOTES	FRACTIONAL: ±1/64 ANGULAR: X* ±1*0' X*X' ±15' DECIMAL: .X ±.030 .XX +.010		
SURFACE AREA: N/A		.XXX ±.005 INTERPRET DIMENSIONS AND TOLERANCE PER ASME Y14.5M - 1994		
PROPRIETARY				
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE. INC.		THIRD ANGLE PROJECTION		
ANY REPRODUC	CTION IN PART OR AS A WHOLE WRITTEN PERMISSION OF E, INC IS PROHIBITED.	→ ← →		

DIMENSIONS ARE IN INCHES TOLERANCES:		
FRACTIONAL: ±1/64 ANGULAR: X° ±1°( X°X' +15		
DECIMAL: .X ±.030 .XX ±.010 .XXX ±.005	2) 3) 4) 5)	
INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994		

1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 187 & LAST THREADS. 5) SURFACE ROUGHNESS 63.MIL-STD-10. 6) DIA'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS	

APPROVED:

UNLESS OTHERWISE SPECIFIED

CHAM. 1ST & LAST THREADS. SURFACE ROUGHNESS 63-MIL-STD-10. DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN. 005 T.I.R. REMOVE ALL BURRS			
DRAWN:	NHR 01/31/11	]	
CHECKED:	STW 01/31/11	1	

SV Microwave, I	nc
-----------------	----

2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409

VITA 67.3 BACKPLANE CONTACT REMOVAL TOOL

14111 01/01/11	CIZE	CACE CODE	DIA/C NO		
STW 01/31/11	B	95077	DWG. NO.	500-32-015	
STW 01/31/11	S	CALE: 5:1			SHEET 1 OF 1

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connector Tools category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

R282744011 R282744220 R282120010 4-1532129-0 6-1337482-0 R282730040 R282743120 R282744100 23W100-000 23W101-000 227
1497 R282589210 R282967015 R282918210 GK-S600TT GK-S240TT GK-S900TT CS24-1 500-32-015 W1W005-000 W1W001-000

500-32-004 500-38-002 500-32-008 227-T2000 500-12-019 500-32-007 500-32-022 500-38-004 500-38-006 500-38-008 500-80-014

D.FL75-LP-N CAS-BNC-T R282868280 19W002-000 6006330101 1055454-1 GK-S400TT 500-12-000 X.FL-LP-IN.OUT1 500-32-010 W1W002-000 RFMODE1.5 CS10 CS12 CS14 CS16 CS20 CS32