
PIHER



Bushless version

* Others check availability.

** Up to 85°C depending on application.

MECHANICAL SPECIFICATIONS

 Mechanical rotation angle: 	300° ± 5°		
- Electrical rotation angle:	280° ± 20°		
– Torque:	0.5 to 1.5 Ncm. (0.7 to 2.1 in-oz)		
– Stop torque:	> 40 Ncm. (>56 in-oz)		
- Max. torque nut (binding out):	< 80 Ncm. (112 in-oz)		
- Thrust and pull in the shaft:	> 25 N		


PC-16 16 mm Carbon Potentiometer

FEATURES

- Carbon resistive element.
- IP54 protection according to IEC 60529.
- Polyester substrate.
- Modular gang type (up to 4).
- Self extinguishable material UL 94-V0.
- Upon request:
 - Metalic support.
 - · Stereo matching.
 - Switch.
 - Nut & washer.
 - Bushless & shaftless models.
 - Assemblies with wires and connectors.

ELECTRICAL SPECIFICATIONS

- Range of values*
- $100\Omega \le Rn \le 5~M$ (Decad. 1.0 2.0 2.2 2.5 4.7 5.0)
- Standard tolerance*: $100\Omega \le Rn \le 1M \ \Omega \ \dots \ \pm 20\%$ $1M\Omega \ < Rn \le 5M \ \Omega \ \dots \ \pm 30\%$
- Max. Voltage: 250 VDC (lin) 125 VDC (no lin)
- Nominal Power 50°C (122°F) (see power rating curve)
 0.2 W (lin) 0.1 W (no lin)
- Taper* Lin ; Log; Alog (Log. & Alog. only $Rn \ge 1K$).
- Residual resistance*: $\leq 0.5\%$ Rn (5 Ω min.)
- Equivalent Noise Resistance: \leq 3% Rn (3 Ω min.)
- Operating temperature**: -25°C + 70°C (-13°F + 158°F)



HOW TO ORDER CUSTOM DRAWING


PC-16 S V + DRAWING NUMBER (Max. 16 digits)

This way of ordering should be used for options which are not included in the "How to order" standard and optional extras.


MODELS


STANDARD OPTIONS

Shaft length	. 0 Standard Length
Mounting brackets	. Without mounting brackets
Stereo matching	. Only on request (see note 8)
Switch	. No switch
Nut & washer	. Without nut and washer




METALLIC SUPPORT






BUSHINGS



EXAMPLES OF BUSHLESS VERSION



PIHER

TERMINALS

Standard

100

80


60

40

20 Α

0

25



POWER RATING CURVE


50°

W (%)

100 %

40 %

NUTS & WASHERS



NOTE = Please note relative terminal positions when ordering non linear tapers.

A = Linear

B = Log.

C = Alog.

Е

B

50 75 100


TESTS		TYPICAL VARIATIONS
ELECTRICAL LIFE	1.000 h. @ 50°C; 0.2 W	±5 %
MECHANICAL LIFE : POT.* SWITCH	25.000 (10-15 CPM) 10.000 (1 A, 50 VAC)	±3 % (Rn < 1 MΩ)
TEMPERATURE COEFFICIENT	–25°C; +70°C	±300 ppm/°C (Rn <100 KΩ)
THERMAL CYCLING	16 h. @ 85°C; 2h. @ −25°C	±2.5 %
DAMP HEAT	500 h. @ 40°C @ 95% HR	±5 %
VIBRATION (for each plane X,Y,Z)	2 h. @ 10 Hz 55 Hz.	±2 %

►

70°

(*) only applicable to values ≥1K. For lower values please consult.

SWITCH




SWITCH SPECIFICATIONS		
NOMINAL CURRENT	1A, 250 VAC	
CONTACT RESISTANCE (initial)	10 m Ω	
OPERATING TORQUE	1 to 3 Ncm (1.4 to 4.2 in oz)	
OPERATING ANGLE	30° ± 5°	
TEST VOLTAGE	500 V	


PACKAGING

Boxes of 100 pieces (single body model): Inner dimensions 250 x 160 x 95 mm

METALIC SHAFTS









Α	L	CODE
4	45	M04
6	45	M06
6.35	45	M07

Α	в	С	L	CODE
2	5	7	15	M11
2	10	11	20	M12
4	12	14	25	M13
4	12	14	30	M14
4	12	14	35	M15
4	12	14	40	M16
4	12	14	45	M17


SPECIAL









PLASTIC SHAFTS Ø3.1




PLASTIC SHAFTS Ø4







PLASTIC SHAFTS Ø6

Shaft position shown full CCW. Any other position for plastic shafts has to be shifted n times 24°. Other positions upon request.













CW on-off (E)

A = Initial S = Wiper E = Final.

PCI, PCF and other configurations available upon request. Check the ordering code with Piher.

RECOMMENDED CONNECTIONS





Disclaimer

The product information in this catalogue is for reference purposes. Please consult for the most up to date and accurate design information.

Piher Sensors & Controls S.A., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Piher"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product described herein.

Piher disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Piher's terms and conditions of sale, including but not limited to the warranty expressed therein, which apply to these products.

No licence, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Piher.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Piher products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Piher for any damages arising or resulting from such use or sale. Please contact authorised Piher personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Information contained in and/or attached to this catalogue may be subject to export control regulations of the European Community, USA, or other countries. Each recipient of this document is responsible to ensure that usage and/or transfer of any information contained in this document complies with all relevant export control regulations. If you are in any doubt about the export control restrictions that apply to this information, please contact the sender immediately. For any Piher International Corp. Exports, Note: All products / technologies are EAR99 Classified commodities. Exports from the United States are in accordance with the Export Administration Regulations. Diversion contrary to US law is prohibited.

Piher is an AmphenolTM company.



Note: Piher products can be adapted to meet customer's requirements. Due to continuous process improvement, specifications are subject to change without notice.

v180220



Piher Sensors & Controls SA Polígono Industrial Municipal Vial T2, 22, 31500 Tudela - Spain. t. +34-948-820450 f. +34-948-824050

sales@piher.net

www.piher.net

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Potentiometer Tools & Fixings category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

 7071
 7071E
 7072E
 FKS-1/4
 H-38-3
 1220A
 ACCPOTDBB173190100
 H-858
 H-137-000
 H-38-1
 7090E
 7074E
 RK14K1240A4S

 HARDWARE
 H-37-4
 H-862
 100P8
 H-80-1
 RKZ00020NA
 34-1032-1A
 006-1-0
 1-150
 H-38-2
 H-37-1
 DA-01
 P0700-21
 P0700-7
 DA-02

 008T000
 T4845
 13
 T4845
 18
 T4857
 GSD-675
 H-114P
 H-83P
 H-90
 H-91
 DA-83
 DA-88
 6533E
 6591E
 7070E
 7091E
 5465

 RKZ00023UA
 ZB4BD912
 T4844
 T4847
 T4856
 ACCPOTECB303651550