





PRODUCT NO SEE TABLE		REVISIONS <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>REV</th> <th>DESCRIPTION</th> <th>BY</th> <th>DATE</th> </tr> <tr> <td style="text-align: center;">X</td> <td></td> <td></td> <td></td> </tr> </table>	REV	DESCRIPTION	BY	DATE	X																															
REV	DESCRIPTION	BY	DATE																																			
X																																						
<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>2 x 5 STYLE A</p> </div> <div style="text-align: center;">  <p>2 x 7 STYLE C</p> </div> </div> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>2 x 5 STYLE B</p> </div> <div style="text-align: center;">  <p>2 x 6 thru 2 x 30 STYLE D</p> </div> </div>		<p>NOTES:</p> <ol style="list-style-type: none"> 1 WELDING MATERIAL, GLASS-FILLED POLYESTER, FLAME RETARDANT PER UL 94V-0, COLOR: BLUE. 2 TERMINAL MATERIAL, PHOSPHOR BRONZE. 3 1° MAX DRAFT PERMITTED ON ALL SURFACES. 4 SAME TOLERANCE APPLIES TO BOTH ENDS OF EACH TERMINAL. 5 1.8 KG/4 LBS MIN TENSILE PULL-OUT FORCE. 6 .13/.050 STEP AROUND MOUNTING HOLE. 7 RECOMMENDED MOUNTING SCREW SIZE #2-36 FILLISTER HEAD 4.75/.180 LONG FOR 1.54/.06 BOARD 5.47/.20 LONG FOR 2.47/.09, 3.18/.120 BOARD 8 ADD "LF" SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION. 9 IF "LF" P/N THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN 00-00-000. 10 THE HOUSING WILL WITHSTAND EXPOSURE TO 260° PEAK TEMPERATURE FOR 15 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.5mm MINIMUM THICK CIRCUIT BOARD. SEE APPLICATION NOTES/PROCEDURES IF THEY ARE AVAILABLE. <p>11. plating option. maybe either Gold or GXT plating at manufacturer's option.</p>																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">DATE</td> <td style="width: 10%;">REV</td> <td style="width: 10%;">BY</td> <td style="width: 10%;">CHKD</td> <td style="width: 10%;">APP'D</td> <td style="width: 10%;">MATERIAL</td> <td style="width: 10%;">PROCESS</td> <td style="width: 10%;">FINISH</td> <td style="width: 10%;">TOLERANCE</td> <td style="width: 10%;">DIMENSIONS</td> <td style="width: 10%;">WEIGHT</td> <td style="width: 10%;">VOLUME</td> <td style="width: 10%;">COST</td> <td style="width: 10%;">STATUS</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>		DATE	REV	BY	CHKD	APP'D	MATERIAL	PROCESS	FINISH	TOLERANCE	DIMENSIONS	WEIGHT	VOLUME	COST	STATUS															<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">FCJ</td> <td style="text-align: center;">www.fcjconnect.com</td> </tr> <tr> <td colspan="2" style="text-align: center;"> HEADER, SLITCHES, SLIP LINES, VERTICAL </td> </tr> <tr> <td style="text-align: center;">4/1</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">06992</td> <td style="text-align: center;">0002</td> </tr> </table>	FCJ	www.fcjconnect.com	HEADER, SLITCHES, SLIP LINES, VERTICAL		4/1	0	06992	0002
DATE	REV	BY	CHKD	APP'D	MATERIAL	PROCESS	FINISH	TOLERANCE	DIMENSIONS	WEIGHT	VOLUME	COST	STATUS																									
FCJ	www.fcjconnect.com																																					
HEADER, SLITCHES, SLIP LINES, VERTICAL																																						
4/1	0																																					
06992	0002																																					

PRODUCT NO	SIZE	DIM A	DIM B	DIM C	DIM D	DIM E	DIM J	TERM TYPE	TERM PLATING	STYLE	REVISIONS		
											REV	DESCRIPTION	BY
65692-066	2X5	24.17/.95	18.37/.72	10.16/.400	19.81/.780	17.78/.700	2.67/.105	RD	.76u/30u* GXT/GOLD FLASH	A			
-067	2X5	24.17/.95	18.37/.72	10.16/.400	19.81/.780	17.78/.700	17.15/.675	SO		A			
-068	2X7	29.2/1.15	23.47/.92	15.24/.600	24.89/.980	22.86/.900	2.67/.105	RD		C			
-069	2X7	29.2/1.15	23.47/.92	15.24/.600	24.89/.980	22.86/.900	17.15/.675	SO		C			
-070	2X8	31.8/1.25	25.9/1.02	17.78/.700	27.43/1.080	25.40/1.000	2.67/.105	RD		D			
-071	2X8	31.8/1.25	25.9/1.02	17.78/.700	27.43/1.080	25.40/1.000	17.15/.675	SO					
-072	2X10	36.8/1.45	30.9/1.22	22.86/.900	32.51/1.280	30.48/1.200	2.67/.105	RD					
-073	2X10	36.8/1.45	30.9/1.22	22.86/.900	32.51/1.280	30.48/1.200	17.15/.675	SO					
-074	2X13	44.5/1.75	38.6/1.52	30.48/1.200	40.12/1.580	38.10/1.500	2.67/.105	RD					
-075	2X13	44.5/1.75	38.6/1.52	30.48/1.200	40.12/1.580	38.10/1.500	17.15/.675	SO					
-076	2X17	54.6/2.15	48.8/1.92	40.64/1.600	50.29/1.980	48.26/1.900	2.67/.105	RD					
-077	2X17	54.6/2.15	48.8/1.92	40.64/1.600	50.29/1.980	48.26/1.900	17.15/.675	SO					
-078	2X20	62.2/2.45	56.4/2.22	48.26/1.900	57.91/2.280	55.88/2.200	2.67/.105	RD					
-079	2X20	62.2/2.45	56.4/2.22	48.26/1.900	57.91/2.280	55.88/2.200	17.15/.675	SO					
-080	2X25	74.9/2.95	69.1/2.72	60.96/2.400	70.61/2.780	68.58/2.700	2.67/.105	RD					
-081	2X25	74.9/2.95	69.1/2.72	60.96/2.400	70.61/2.780	68.58/2.700	17.15/.675	SO					
-082	2X5	24.17/.95	18.37/.72	10.16/.400	19.81/.780	17.78/.700	2.67/.105	RD	.35u/15u*Au OVER 1.27u/50u*Ni	A			
-083	2X5	24.17/.95	18.37/.72	10.16/.400	19.81/.780	17.78/.700	3.8/.15	RD		A			
-084	2X5	24.17/.95	18.37/.72	10.16/.400	19.81/.780	17.78/.700	17.15/.675	SO		A			
-085	2X7	29.2/1.15	23.47/.92	15.24/.600	24.89/.980	22.86/.900	2.67/.105	RD		C			
-086	2X7	29.2/1.15	23.47/.92	15.24/.600	24.89/.980	22.86/.900	3.8/.15	RD		C			
-087	2X7	29.2/1.15	23.47/.92	15.24/.600	24.89/.980	22.86/.900	17.15/.675	SO		C			
-088	2X8	31.8/1.25	25.9/1.02	17.78/.700	27.43/1.080	25.40/1.000	2.67/.105	RD		D			
-089	2X8	31.8/1.25	25.9/1.02	17.78/.700	27.43/1.080	25.40/1.000	3.8/.15	RD					
-090	2X8	31.8/1.25	25.9/1.02	17.78/.700	27.43/1.080	25.40/1.000	17.15/.675	SO					
-091	2X10	36.8/1.45	30.9/1.22	22.86/.900	32.51/1.280	30.48/1.200	2.67/.105	RD					
-092	2X10	36.8/1.45	30.9/1.22	22.86/.900	32.51/1.280	30.48/1.200	3.8/.15	RD					
-093	2X10	36.8/1.45	30.9/1.22	22.86/.900	32.51/1.280	30.48/1.200	17.15/.675	SO					
-094	2X13	44.5/1.75	38.6/1.52	30.48/1.200	40.12/1.580	38.10/1.500	2.67/.105	RD					
-095	2X13	44.5/1.75	38.6/1.52	30.48/1.200	40.12/1.580	38.10/1.500	3.8/.15	RD					
-096	2X13	44.5/1.75	38.6/1.52	30.48/1.200	40.12/1.580	38.10/1.500	17.15/.675	SO					
-097	2X17	54.6/2.15	48.8/1.92	40.64/1.600	50.29/1.980	48.26/1.900	2.67/.105	RD					
-098	2X17	54.6/2.15	48.8/1.92	40.64/1.600	50.29/1.980	48.26/1.900	3.8/.15	RD					
-099	2X17	54.6/2.15	48.8/1.92	40.64/1.600	50.29/1.980	48.26/1.900	17.15/.675	SO					
65692-100	2X20	62.2/2.45	56.4/2.22	48.26/1.900	57.91/2.280	55.88/2.200	2.67/.105	RD					

CUSTOMER COPY
 CODE 10000
 DATE 1/8/08
 FCJ www.fcjconnect.com
 TITLE: HEADER, QUICKIE BLIN LINE, VERTICAL
 SHEET SIZE: 100 X 100
 65692 SHEET 5

DO NOT SCALE DIMENSIONS
 DIMENSIONS IN MILLIMETERS
 ANGLES IN DEGREES
 TOLERANCES UNLESS OTHERWISE SPECIFIED
 FRACTIONS: 1/16, 1/8, 3/16, 1/4, 3/8, 1/2, 5/8, 3/4, 7/8, 1
 DECIMALS: .0005, .001, .002, .005, .01, .02, .05, .1, .2, .5, 1, 2, 5, 10, 20, 50, 100, 200, 500, 1000
 HIDDEN DIMENSIONS: HIDDEN DIMENSIONS
 DIMENSIONS: DIMENSIONS
 ANGLES: ANGLES

PRODUCT NO	SIZE	DIM A	DIM B	DIM C	DIM D	DIM E	DIM J	TERM TYPE	TERM PLATING	STYLE	REVISIONS			
											REV	DESCRIPTION	BY	DATE
65692-101	2X20	62.2/2.45	56.4/2.22	48.26/1.900	57.91/2.280	56.88/2.200	3.8/.15	RD	.38 μ /15 μ *Au OVER 1.27 μ /50 μ *Ni	D				
-102	2X20	62.2/2.45	56.4/2.22	48.26/1.900	57.91/2.280	56.88/2.200	17.15/.675	SO						
-103	2X25	74.9/2.95	69.1/2.72	60.96/2.400	70.61/2.780	68.58/2.700	2.67/.105	RD						
-104	2X25	74.9/2.95	69.1/2.72	60.96/2.400	70.61/2.780	68.58/2.700	3.8/.15	RD						
-105	2X25	74.9/2.95	69.1/2.72	60.96/2.400	70.61/2.780	68.58/2.700	17.15/.675	SO						
-106	2X30	87.6/3.45	81.8/3.22	73.66/2.900	83.31/3.280	81.28/3.200	2.67/.105	RD						
-107	2X30	87.6/3.45	81.8/3.22	73.66/2.900	83.31/3.280	81.28/3.200	3.8/.15	RD						
-108	2X30	87.6/3.45	81.8/3.22	73.66/2.900	83.31/3.280	81.28/3.200	17.15/.675	SO						
-109	2X5	24.1/.95	18.3/.72	10.16/.400	19.81/.780	17.78/.700	2.67/.105	RD		.76 μ /30 μ *Au OVER 1.27 μ /50 μ *Ni	B			
-110							3.8/.15	RD						
-111							17.15/.675	SO						
-112							2.67/.105	SO	3.81 μ /150 μ * TIN					
-113							3.8/.15	SO						
-114							17.15/.675	SO						
-115							2.67/.105	RD	.38 μ /15 μ *Au OVER 1.27 μ /50 μ *Ni					
-116							3.8/.15	RD						
-117							17.15/.675	SO						
-118							2.67/.105	RD	.76 μ /30 μ * GXT/GOLD FLASH					
-119							3.8/.15	RD						
65692-120	2X5	24.1/.95	18.3/.72	10.16/.400	19.81/.780	17.78/.700	17.15/.675	SO		B				
65692-121	OBSOLETE													
65692-216	OBSOLETE													
65692-217	2X12	41.9/1.65	36.1/1.42	27.94/1.100	37.59/1.480	35.56/1.400	2.67/.105	RD	.38 μ /15 μ *Au OVER 1.27 μ /50 μ *Ni	D				
-218							3.81/.150	RD						
-219							17.15/.675	SO						
-220							2.67/.105	RD		.76 μ /30 μ *Au OVER 1.27 μ /50 μ *Ni				
-221							3.81/.150	RD						
-222							17.15/.675	SO						
-223							2.67/.105	RD		.76 μ /30 μ * GXT/Au FLASH				
-224							3.81/.150	RD						
-225							17.15/.675	SO						
-226							2.67/.105	SO		3.81 μ /150 μ * TIN				
-227							3.81/.150	SO						
65692-228	2X12	41.9/1.65	36.1/1.42	27.94/1.100	37.59/1.480	35.56/1.400	17.15/.675	SO		D				

CUSTOMER COPY		FCJ www.fcjconnect.com
CODE IDENT	22886	
DATE	1/8/08	TITLE HEADER, QUICKIE SLID L.D.E. VERTICAL
BY	J. FRONT	
DATE	1/8/08	
BY	J. FRONT	
DATE	1/8/08	FORM SIZE
BY	J. FRONT	1/1
DATE	1/8/08	65692
BY	J. FRONT	SHEET 6

DATE	1/8/08	TIME	11:11
BY	J. FRONT	DATE	1/8/08
DATE	1/8/08	TIME	11:11
BY	J. FRONT	DATE	1/8/08
DATE	1/8/08	TIME	11:11
BY	J. FRONT	DATE	1/8/08
DATE	1/8/08	TIME	11:11
BY	J. FRONT	DATE	1/8/08

NOTE: This print is the property of and contains confidential information of FCJ CONNECT. If you find this document on this print you are not to use it. Return the original document to FCJ CONNECT, New Bedford, MA.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [009176003701906](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#)