




PRODUCT NO.
SEE TABLE



FCI
FCIconnect.com

Copyright FCI

.005/.13 X
TYP


mat'l. code SEE NOTE 1 & 2		surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection INCH/MM	product family CARD CONN
ltr	ecn no	dr	date	title	
W	ELX-N-1389	DCS	2013-01-28	VERT. CARD CONNECTOR	
X	ELX-N-1441	DCS	2013-03-05	.100/2.54 CTR., DBL ROW	
S	v03-1072	LP	9/25/03	dr	M.CLOUSER 3/25/94
T	M05-0216	ERE	10/11/05	enr	H. SUNDY 3/25/94
U	M06-0210	MHT	6/03/06	chr	H. SUNDY 3/25/94
V	M07-0143	ERE	03/03/07	app	H. SUNDY 3/25/94
sheet	revision	X	X	X	X
index	sheet	1	2	3	4



dwg no 65781 sheet 1 of 6 size A3
type Product Customer Drawing

PRODUCT NO.

SEE TABLE



RECOMMENDED HOLE PATTERN
SCALE 4:1

NOTES:

- ① HOUSING MAT'L: FILLED POLYESTER.
FLAME RETARDANT PER UL 94V-0.
COLOR: BLACK.
- ② TERMINAL MATERIAL AND PLATING: SEE TABULATION.
- 3. RECOMMENDED PIN SIZE: $.025 \pm .001 / .64 \pm .03$ SQUARE.
RECOMMENDED PIN LENGTH: $.210 \pm .020 / 5.33 \pm .51$.
- 4. MARK FCI PART NUMBER AND DATE CODE LEGIBLE
ON TUBE LABEL.
- ⑤ ADD "LF" SUFFIX AT THE END OF PART NUMBER
FOR LEAD FREE OPTION.
- ⑥ THESE PRODUCTS MEET EUROPEAN UNION DIRECTIVES
AND OTHER COUNTRY REGULATIONS AS DESCRIBED
IN GS-22-008.
- 7. THIS PART WILL WITHSTAND EXPOSURE TO 260°C PEAK
TEMPERATURE FOR 20 SECONDS IN WAVE SOLDER,
INFRA-RED OR VAPOR PHASE SOLDER PROCESS.
- ⑧ "THIS PRODUCT HAS 100% TIN PLATING IN THE
INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER
GROWTH IN ALL INTERCONNECT ENVIRONMENTS."



FCIconnect.com

Copyright FCI

mat'l. code		surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection 	product family CARD CONN
ltr	ecn no	dr	date	title	
X				INCH/MM	VERT. CARD CONNECTOR .100/2.54 CTR., DBL ROW
				scale 4:1	
		dr	M.CLOUSER	3/25/94	dwg no
		enr	H. SUNDY	3/25/94	sheet 2 of 6
		chr	H. SUNDY	3/25/94	size
		app	H. SUNDY	3/25/94	A3
sheet index	revision sheet				type Product Customer Drawing

PRODUCT NUMBER	SIZE	DIM A	DIM B	MATERIAL AND PLATING	DIM C	LEAD FREE OPTION
65781-001				UNASSIGNED		
-002	2X2	.100 / 2.54	.200 / 5.08	BODY MAT'L: BRASS BODY PLATING: 40u"/1.02u MIN THICK C.I. GOLD INSIDE CONTACT AREA, 2u"/.051u GOLD FLASH MIN ON REST OF TERMINAL BODY, OVER 50u"/ 1.27u MIN NICKEL SPRING MAT'L: BeCu HEAT TREATED SPRING PLATING: GOLD FLASH	.140/3.56	
-003	2X3	.200 / 5.08	.300 / 7.62			
-004	2X4	.300 / 7.62	.400 / 10.16			
-005	2X5	.400 / 10.16	.500 / 12.70			
-006	2X6	.500 / 12.70	.600 / 15.24			
-007	2X7	.600 / 15.24	.700 / 17.78			
-008	2X8	.700 / 17.78	.800 / 20.32			
-009	2X9	.800 / 20.32	.900 / 22.86			
-010	2X10	.900 / 22.86	1.000 / 25.40			
-011	2X11	1.000 / 25.40	1.100 / 27.94			
-012	2X12	1.100 / 27.94	1.200 / 30.48			
-013	2X13	1.200 / 30.48	1.300 / 33.02			
-014	2X14	1.300 / 33.02	1.400 / 35.56			
-015	2X15	1.400 / 35.56	1.500 / 38.10			
-016	2X16	1.500 / 38.10	1.600 / 40.64			
-017	2X17	1.600 / 40.64	1.700 / 43.18			
-018	2X18	1.700 / 43.18	1.800 / 45.72			
-019	2X19	1.800 / 45.72	1.900 / 48.26			
-020	2X20	1.900 / 48.26	2.000 / 50.80			
-021	2X21	2.000 / 50.80	2.100 / 53.34			
-022	2X22	2.100 / 53.34	2.200 / 55.88			
-023	2X23	2.200 / 55.88	2.300 / 58.42			
-024	2X24	2.300 / 58.42	2.400 / 60.96			
-025	2X25	2.400 / 60.96	2.500 / 63.50			
-026	2X26	2.500 / 63.50	2.600 / 66.04			
-027	2X27	2.600 / 66.04	2.700 / 68.58			
-028	2X28	2.700 / 68.58	2.800 / 71.12			
-029	2X29	2.800 / 71.12	2.900 / 73.66			
-030	2X30	2.900 / 73.66	3.000 / 76.20			
-031	2X31	3.000 / 76.20	3.100 / 78.74			
-032	2X32	3.100 / 78.74	3.200 / 81.28			
-033	2X33	3.200 / 81.28	3.300 / 83.82			
-034	2X34	3.300 / 83.82	3.400 / 86.36			
-035	2X35	3.400 / 86.36	3.500 / 88.90			
65781-036	2X36	3.500 / 88.90	3.600 / 91.44			.140/3.56

OBS

NOTE 5,6

NOTE 5,6



FCIconnect.com

Copyright FCI

mat'l. code		surface	tolerance	projection	product family
ISO 1302		ISO 406	ISO 1101		CARD CONN
tolerances unless otherwise specified				INCH/MM	title
linear				scale 4:1	VERT. CARD CONNECTOR .100/2.54 CTR., DBL ROW
angles					dwg no
0'±2'					sheet 3 of 6 size
dr		M.CLOUSER	3/25/94		65781
enr		H. SUNDY	3/25/94		A3
chr		H. SUNDY	3/25/94		
app		H. SUNDY	3/25/94		
sheet index	revision sheet	type Product Customer Drawing			

PRODUCT NUMBER	SIZE	DIM A	DIM B	MATERIAL AND PLATING	DIM C	LEAD FREE OPTION
65781-037				UNASSIGNED		
-038	2X2	.100 / 2.54	.200 / 5.08	BRASS 100u"/2.54u THICK SN PLATE SPRING MAT'L: BeCu HEAT TREATED SPRING PLATING: 30u"/76u MIN ELECTROLESS TIN	.140/3.56	OBS NOTES 5,6,8
-039	2X3	.200 / 5.08	.300 / 7.62			
-040	2X4	.300 / 7.62	.400 / 10.16			
-041	2X5	.400 / 10.16	.500 / 12.70			
-042	2X6	.500 / 12.70	.600 / 15.24			
-043	2X7	.600 / 15.24	.700 / 17.78			
-044	2X8	.700 / 17.78	.800 / 20.32			
-045	2X9	.800 / 20.32	.900 / 22.86			
-046	2X10	.900 / 22.86	1.000 / 25.40			
-047	2X11	1.000 / 25.40	1.100 / 27.94			
-048	2X12	1.100 / 27.94	1.200 / 30.48			
-049	2X13	1.200 / 30.48	1.300 / 33.02			
-050	2X14	1.300 / 33.02	1.400 / 35.56			
-051	2X15	1.400 / 35.56	1.500 / 38.10			
-052	2X16	1.500 / 38.10	1.600 / 40.64			
-053	2X17	1.600 / 40.64	1.700 / 43.18			
-054	2X18	1.700 / 43.18	1.800 / 45.72			
-055	2X19	1.800 / 45.72	1.900 / 48.26			
-056	2X20	1.900 / 48.26	2.000 / 50.80			
-057	2X21	2.000 / 50.80	2.100 / 53.34			
-058	2X22	2.100 / 53.34	2.200 / 55.88			
-059	2X23	2.200 / 55.88	2.300 / 58.42			
-060	2X24	2.300 / 58.42	2.400 / 60.96			
-061	2X25	2.400 / 60.96	2.500 / 63.50			
-062	2X26	2.500 / 63.50	2.600 / 66.04			
-063	2X27	2.600 / 66.04	2.700 / 68.58			
-064	2X28	2.700 / 68.58	2.800 / 71.12			
-065	2X29	2.800 / 71.12	2.900 / 73.66			
-066	2X30	2.900 / 73.66	3.000 / 76.20			
-067	2X31	3.000 / 76.20	3.100 / 78.74			
-068	2X32	3.100 / 78.74	3.200 / 81.28			
-069	2X33	3.200 / 81.28	3.300 / 83.82			
-070	2X34	3.300 / 83.82	3.400 / 86.36			
-071	2X35	3.400 / 86.36	3.500 / 88.90			
65781-072	2X36	3.500 / 88.90	3.600 / 91.44	BRASS 100u"/2.54u THICK SN PLATE SPRING MAT'L: BeCu HEAT TREATED SPRING PLATING: 30u"/76u MIN ELECTROLESS TIN	.140/3.56	NOTES 5,6,8

mat'l. code		surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection 	product family CARD CONN
ltr	ecn no	dr	date	title	
X				VERT. CARD CONNECTOR .100/2.54 CTR., DBL ROW	
				INCH/MM	
				scale 4:1	
		dr	M.CLOUSER 3/25/94	dwg no sheet 4 of 6 size	
		enr	H. SUNDY 3/25/94	65781 A3	
		chr	H. SUNDY 3/25/94	type Product Customer Drawing	
		app	H. SUNDY 3/25/94		
sheet index	revision sheet				

PRODUCT NUMBER	SIZE	DIM A	DIM B	MATERIAL AND PLATING	DIM C	LEAD FREE OPTION	
65781-073				UNASSIGNED			
-074	2X2	.100 / 2.54	.200 / 5.08	BODY MAT'L: Cu Ni 10u"/.25u Au FLASH INSIDE BODY CONTACT AREA ONLY WITH .001/.03 MIN HIGH GOLD DOT. SPRING PLATING: GOLD FLASH SPRING MAT'L: BeCu HEAT TREAT	.140/3.56	NOTE 5,6	
-075	2X3	.200 / 5.08	.300 / 7.62				
-076	2X4	.300 / 7.62	.400 / 10.16				
-077	2X5	.400 / 10.16	.500 / 12.70				
-078	2X6	.500 / 12.70	.600 / 15.24				
-079	2X7	.600 / 15.24	.700 / 17.78				
-080	2X8	.700 / 17.78	.800 / 20.32				
-081	2X9	.800 / 20.32	.900 / 22.86				
-082	2X10	.900 / 22.86	1.000 / 25.40				
-083	2X11	1.000 / 25.40	1.100 / 27.94				
-084	2X12	1.100 / 27.94	1.200 / 30.48				
-085	2X13	1.200 / 30.48	1.300 / 33.02				
-086	2X14	1.300 / 33.02	1.400 / 35.56				
-087	2X15	1.400 / 35.56	1.500 / 38.10				
-088	2X16	1.500 / 38.10	1.600 / 40.64				
-089	2X17	1.600 / 40.64	1.700 / 43.18				
-090	2X18	1.700 / 43.18	1.800 / 45.72				
-091	2X19	1.800 / 45.72	1.900 / 48.26				
-092	2X20	1.900 / 48.26	2.000 / 50.80				
-093	2X21	2.000 / 50.80	2.100 / 53.34				
-094	2X22	2.100 / 53.34	2.200 / 55.88				
-095	2X23	2.200 / 55.88	2.300 / 58.42				
-096	2X24	2.300 / 58.42	2.400 / 60.96				
-097	2X25	2.400 / 60.96	2.500 / 63.50				
-098	2X26	2.500 / 63.50	2.600 / 66.04				
-099	2X27	2.600 / 66.04	2.700 / 68.58				
-100	2X28	2.700 / 68.58	2.800 / 71.12				
-101	2X29	2.800 / 71.12	2.900 / 73.66				
-102	2X30	2.900 / 73.66	3.000 / 76.20				
-103	2X31	3.000 / 76.20	3.100 / 78.74				
-104	2X32	3.100 / 78.74	3.200 / 81.28		BODY MAT'L: Cu Ni 10u"/.25u Au FLASH INSIDE BODY CONTACT AREA ONLY WITH .001/.03 MIN HIGH GOLD DOT. SPRING PLATING: GOLD FLASH SPRING MAT'L: BeCu HEAT TREAT		
-105	2X33	3.200 / 81.28	3.300 / 83.82				
-106	2X34	3.300 / 83.82	3.400 / 86.36				
-107	2X35	3.400 / 86.36	3.500 / 88.90				
65781-108	2X36	3.500 / 88.90	3.600 / 91.44		.140/3.56	NOTE 5,6	



FCconnect.com

Copyright FCJ

mat'l. code		surface	tolerance	projection	product family
ISO 1302		ISO 406	ISO 1101		CARD CONN
tolerances unless otherwise specified					title
angles		linear		scale 4:1	VERT. CARD CONNECTOR .100/2.54 CTR., DBL ROW
0'±2'					dwg no
dr M.CLOUSER 3/25/94					sheet 5 of 6 size
enr H. SUNDY 3/25/94					65781 A3
chr H. SUNDY 3/25/94					type Product Customer Drawing
appd H. SUNDY 3/25/94					
sheet index	revision sheet				

PRODUCT NUMBER	SIZE	DIM A	DIM B	MATERIAL AND PLATING	DIM C	LEAD FREE OPTION
65781-149	2X5	.400/10.16	.500/12.70	BRASS 100u"/2.54u THICK SN PLATE SPRING MAT'L: BeCu HEAT TREATED SPRING PLATING: 30u"/76u MIN ELECTROLESS TIN	.115/2.92	NOTES 5,6,8
65781-151	2X7	.600/15.24	.700/17.78		.115/2.92	
65781-152	2X8	.700/17.78	.800/20.32		.115/2.92	
65781-153	2X13	1.200 / 30.48	1.300 / 33.02	CONTACT BODY MATERIAL: BRASS CONTACT BODY PLATING: 30u"/0.76u MIN GOLD INSIDE CONTACT AREA AND GOLD FLASH ON TAILS OVER 50u"/1.27u MIN NICKEL SPRING MATERIAL: BeCu HEAT TREATED SPRING PLATING: GOLD FLASH ON CONTACT AREA	.140/3.56	NOTE 5,6
65781-154	2X15	1.400 / 35.56	1.500 / 38.10		.140/3.56	
65781-155	2X17	1.600 / 40.64	1.700 / 43.18		.140/3.56	
65781-156	2X18	1.700 / 43.18	1.800 / 45.72		.140/3.56	
65781-157	2X20	1.900 / 48.26	2.000 / 50.80		.140/3.56	
65781-158	2X30	2.900 / 73.66	3.000 / 76.20		.140/3.56	
65781-159	2X10	.900 / 22.86	1.000 / 25.40		.140/3.56	
65781-160	2X5	.400 / 10.16	.500 / 12.70		.140/3.56	



FCIconnect.com

Copyright FCI

mat'l. code		surface	tolerance	projection	product family
		ISO 1302 ✓	ISO 406 ISO 1101		CARD CONN
ltr	ecn no	dr	date	title	
X				VERT. CARD CONNECTOR .100/2.54 CTR., DBL ROW	
				INCH/MM	
				scale 4:1	
		dr	M.CLOUSER 3/25/94		dwg no
		enr	H. SUNDY 3/25/94		sheet 6 of 6
		chr	H. SUNDY 3/25/94		65781
		app	H. SUNDY 3/25/94		A3
sheet index	revision sheet				type Product Customer Drawing

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#)
[65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-](#)
[5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-360C032-B](#) [FCN-](#)
[367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)