

# SOFIX<sup>®</sup> POWER CABLE ASSEMBLIES

Part of the Metral<sup>®</sup> Backplane Connector Family

## OVERVIEW

Higher input/output density and signal speeds demand management of EMC. The Sofix<sup>®</sup> front I/O interconnect system is comprised of right-angle headers and cable plugs that are suitable for the distribution of power and signals.

Sofix<sup>®</sup> connectors are fully shielded down to the PCB level to provide EMC shielding at the sub-rack/front panel level. When used with appropriate cables, the emission level from these links is well below IEC/CISPR 22 and FCC part 15 class B requirements.

Sofix<sup>®</sup> power connectors feature a robust design and are suitable for applications in systems with slot pitch as low as 15mm. The design rules for the Sofix<sup>®</sup> family of I/O connectors are derived from the Metral system (IEC 61076-4-104). As such, the Sofix<sup>®</sup> system can be used as complement to the Metral backplane connector family or applied as dedicated I/O solution.



## FEATURES & BENEFITS

- Unique EMC properties
- 10 Amps per power contact
- According to IEC 60950 and UL 1950
- Hot pluggable
- Robust design
- 15mm slot pitch
- RoHS-compliant design

## TARGET MARKETS/APPLICATIONS

- Communication
- Instrumentation
- Medical
- Hazardous environments





## TECHNICAL INFORMATION

### MATERIALS

- Plug
  - Housing: Polybutylene terephthalate (PBT UL94V-0)
  - Terminals: Copper alloy
  - Covers: Zinc alloy
- Header
  - Housing: Liquid crystal polymer (UL94V-0)
  - Terminals: Copper alloy
  - Covers: Zinc alloy
  - Ground spring: Stainless steel

### ELECTRICAL PERFORMANCE

- Current rating: 10 A per contact
- Withstanding voltage: 1000V RMS
- Initial insulation resistance: 5000MΩ min.

### MECHANICAL PERFORMANCE

- Insertion force: 20 N max.
- Durability: 200 cycles (Telcordia)
- Temperature range: -40°C to +70°C

## PART NUMBERS

Description	Part Numbers
Header Right Angle with 15 Amp Filter	72846-204LF
Cable Connector Kit	72824-201LF

### SPECIFICATIONS

- Header: GS-12-307
- Cable connector: GS-12-308
- Recommended cable specification:
  - Copper 2.5mm<sup>2</sup>
  - Overall Ø 1.95mm
  - Total diameter Ø 8.0mm max.
- Packaging specification: GS-14-1093
- Per Telecordia GR1217-CORE, central office requirements

### CERTIFICATIONS & APPROVAL

- Underwriters Laboratories Inc. (UL file no. E66906)
- Canadian Standards Association (CSA file no. LR46923)

### PACKAGING

- Headers: Tubes
- Header accessories: Bags
- Cable connector components: Bags

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [I/O Connectors](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[571763P](#) [58098-0628](#) [72.250.1628.2](#) [72.250.2428.2](#) [74720-0505](#) [76.350.0729.0](#) [76871-1403](#) [FCN-244F080-G/1](#) [FCN-260A9920](#) [MP-5T180MUNNA-005](#) [PCR-E36PM](#) [PCS-XE26MA+](#) [G38A71314B](#) [1571250010](#) [157-22500-3](#) [MS3471L14-19P L/C](#) [192991-0703](#) [172501-4002](#) [172501-6002](#) [FCN-260C008-A/L0](#) [FCN-260C024-AL0](#) [FCN-261Z008](#) [2000314-1](#) [200331-1](#) [PCR-E36FC+](#) [PCS-E28FS+](#) [PCS-XE26SLFD+](#) [PCS-XE26SLFDT+](#) [G730VID08BDC24](#) [HDR-E14MSG1+](#) [U90B2054081210](#) [UE86K842720321](#) [38113800006](#)  
[DP3AR020WQ1R200](#) [Z4.102.0680.0](#) [500-1040](#) [500-1052](#) [500-1054](#) [ZP-4008-66L](#) [0709821002](#) [DX40-20P\(55\)](#) [5554841-1](#) [MS3474W18-8P-LC\\*](#) [SM3106F14S-7S-LC](#) [U90B3054061110](#) [U65-E04-4020](#) [ZPF000000000097891](#) [557-262M2-06C](#) [747360449](#) [10099439-003C-TRLF](#)