

MEG-Array®

PROVEN BGA CONNECTOR FOR RELIABILITY AND HIGH DATA RATES

Patented BGA design, offering industry leading self-leveling and self-centering. 1.27mm x 1.27mm array of discrete circuit contacts allows flexible ground distribution to optimize high speed signal integrity at speeds up to 32 Gbps.

- High density, high speed, dual-point contacts
- 32 Gbps performance documented for 4mm and 6mm stack heights
- 1.27mm x 1.27mm grid, 71 contacts per cm²
- Wide range of sizes and PCB stack heights
- Self-alignment and leveling for multiple connector use



TARGET MARKETS



FEATURES

- 22+ year old solder joint reliability per IPC-SM-785
- Telcordia GR-1217-CORE and NPS-25298-2
- Stack heights available from 4mm to 14mm
- Pin counts 40 to 528 positions
- Multiple in-process vision systems

BENEFITS

- Long term quality and reliability
- Verified performance through environmental stress and uncontrolled environments
- Fits a large range of customer applications
- Fits a large range of customer applications
- BGA and contact integrity

TECHNICAL INFORMATION

MATERIAL

- Housing: Liquid crystal polymer
- Contact: Copper alloy
- Solder sphere: Lead Free

ELECTRICAL PERFORMANCE

- Insulation resistance: 1000mΩ min.
- Dielectric withstanding voltage: 200 VAC max
- 2.0A < 30°C Δ T (single contact energized)

MECHANICAL PERFORMANCE

- Durability: 50, 100, or 200 cycles
- Contact Wipe: 0.80mm Nominal
- IPC-SM-785 Solder Joint Reliability: 22.1 year product end-of-life

ENVIRONMENTAL

- Telcordia GR-1217-CORE

APPROVALS AND CERTIFICATIONS

- UL File Numer: E66906

PART NUMBERS

		MATED HEIGHT							
SIZE	TYPE	4.0mm	5.5mm	6.0mm	8.0mm	10.0mm	11.5mm	12.0mm	14.0mm
81 POSITION (9X9)	Plug	55714 / 0mm							
	Receptacle	55715 / 4mm							
100 POSITION (10X10)	Plug	84512 / 0mm							
	Receptacle	84513 / 4mm							
200 POSITION (10X20)	Plug	84516 / 0mm		84516 / 0mm	84516 / 0mm	84530 / 6mm		84530 / 6mm	84530 / 6mm
	Receptacle	84517 / 4mm		55724 / 6mm	84535 / 8mm	84517 / 4mm		55724 / 6mm	84535 / 8mm
240 POSITION (8X30)	Plug	74213 / 0mm		74213 / 0mm					
	Receptacle	74217 / 4mm		55755 / 6mm					
300 POSITION (10X30)	Plug	84500 / 0mm	84500 / 0mm		84500 / 0mm	84578 / 6mm	84578 / 6mm		84578 / 6mm
	Receptacle	84501 / 4mm	84502 / 5.5mm		84553 / 8mm	84501 / 4mm	84502 / 5.5mm		84553 / 8mm
320 POSITION (10X32)	Plug	10123981 / 0mm							
	Receptacle	10123982 / 4mm							
400 POSITION (10X40)	Plug	84740 / 0mm		84740 / 0mm	84740 / 0mm	84520 / 6mm		84520 / 6mm	84520 / 6mm
	Receptacle	74221 / 4mm		74388 / 6mm	74390 / 8mm	74221 / 4mm		74388 / 6mm	74390 / 8mm
528 POSITION (12X44)	Plug			10022671 / 0mm					
	Receptacle			10026846 / 6mm					

SPECIFICATIONS

- Product specification: GS-12-100
- Application specification: GS-20-033

PACKAGING

- Tape and Reel

TARGET MARKETS/APPLICATIONS



Automotive



Data



Telecommunication



Industrial & Instrumentation



Consumer



Medical

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [FCN-214Q030-G/0](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [AXG720047](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [DF33-2P-3.3DSA\(24\)](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [10123981-102LF](#) [101A10019X](#) [55650-0588-C](#) [68682-310LF](#) [68684-306](#) [75140-7012](#) [87471-650](#) [YTW-30-07-H-Q-410-140](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [FCN-268M024-G/3D](#) [FCN-268M036-G/BD](#) [20021832-06016C1LF](#) [KX15-20KLDL-E1000E](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#) [AXE816124](#) [AXE720127](#) [354184](#)