



DIMENSION	LOCKING LEVER	
	SHORT	LONG
X Max.	25.30	28.0
Y Max.	11.30	15.0
Z	9.0	10.5

POS.	DIMENSION				
	A ^{+0.25} _{-0.16}	B ^{+0.10} _{-0.18}	C±0.1	D ^{+0.13} ₋₀	E ^{+0.05} _{-0.27}
10	32.00	27.94	21.84	17.91	10.16
14	37.08	33.02	26.92	22.99	15.24
16	39.62	35.56	29.46	25.53	17.78
20	44.70	40.64	34.54	30.61	22.86
24	49.78	45.72	39.62	35.69	27.94
26	52.32	48.26	42.16	38.23	30.48
30	57.40	53.34	47.24	43.31	35.56
34	62.48	58.42	52.32	48.39	40.64
40	70.10	66.04	59.94	56.01	48.26
50	82.80	78.74	72.64	68.71	60.96
60	95.50	91.44	85.34	81.41	73.66
64	100.58	96.52	90.42	86.49	78.74

TECHNICAL SPECIFICATION

HOUSING MATERIAL : THERMOPLASTIC POLYESTER UL94V0; GREY / BLACK ON REQUEST

HOUSING CAN WITHSTAND EXPOSURE TO LEAD FREE WAVE SOLDERING TEMPERATURE OF 260-265°C FOR STRAIGHT CONNECTORS AS IT IS USED IN CLASSICAL LEAD WAVE SOLDERING AT 235-250°C FOR ANGLE CONNECTORS, PROTECTIVE ADHESIVE OR PROTECTIVE METALLIC DEVICE IS TO BE USED AS IN CLASSICAL LEAD WAVE SOLDERING AT 235-250°C

CONTACT MATERIAL : COPPER ALLOY

CONTACT PLATING

ACTIVE ZONE : Au OR EQUIVALENT (Au OVER PALLADIUM NICKEL) OVER Ni.

TERMINATION ZONE : Sn (PURE MATTE) OVER Ni

CURRENT RATING : 1.5A AT 20°C

INSULATION RESISTANCE : 5000MΩ AT 100V

CONTACT RESISTANCE : 20mΩ

DIELECTRIC WITHSTANDING VOLTAGE : 1000Vrms

WORKING VOLTAGE : 250Vrms

OPERATING TEMPERATURE : -55°C TO +125°C

REFERENCE SPECIFICATION : IEC 603-13 / DIN 41651

NOTES

- LEFT POLARISATION IS NOT PROVIDED FOR 10 & 14 POSITIONS.
- RIGHT POLARISATION IS NOT PROVIDED FOR 10 POSITION, INSTEAD PROJECTION AS SHOWN IN DETAIL-A WILL BE PROVIDED.
- INTERMEDIATE LEGS ARE PROVIDED ONLY ABOVE 20 POSITION.
- THE "LF" PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 3.5 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6 MM MINIMUM THICK CIRCUIT BOARD.
- LEAD FREE OR RoHS DIRECTIVE LABELING TO BE PROVIDED AS PER GS-14-920

SERIES 8613 010 2 1 14 3 4 5 E1LF

No. OF CONTACTS 010,014,016,020,024,026,030,034,040,050,060,064

TYPE OF INSULATOR
 HEADER WITH CENTRAL POLARISATION FOR ALL POSITIONS ----- 2
 HEADER 10 POSITION WITH CENTRAL POLARISATION & INSIDE PROJECTION ----- 8

METHOD OF MOUNTING
 WITHOUT LEVERS ----- 0
 WITH LONG BLACK LEVERS ----- 1
 WITH SHORT BLACK LEVERS ----- 2
 WITH LONG GREY LEVERS ----- 3
 WITH SHORT GREY LEVERS ----- 4

TERMINATION STYLE
 STRAIGHT SPILL LONG (L = 4.35±0.35mm) ----- 14
 STRAIGHT SPILL SHORT (L = 2.9±0.2mm) ----- 24
 ANGLED SPILL LONG (L = 4.2±0.35mm) ----- 13
 ANGLED SPILL SHORT (L = 2.8±0.2mm) ----- 23

HOUSING MATERIAL
 PBT GREY ----- 3
 PBT BLACK ----- 2

PERFORMANCE CLASS
 DIN 41651 CLASS 3 ----- 4
 DIN 41651 CLASS 2 ----- 5
 DIN 41651 CLASS 1 ----- 6
 AS PER JSS 50810 ----- 8

LONGITUDINAL PITCH
 2.54 mm ----- 5
 5.08 mm ----- 8

SPECIAL CODE
 LEAD FREE VERSION ----- E1LF

mat'l. code SEE TECH. SPEC.		surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection mm		product family 8613	
ltr	ecn no	dr	date	tolerances unless otherwise specified		mm		title HEADERS STRAIGHT & ANGLED SPILL, TMT VERSION	
B	106-0066	MINI	2006-06-01	angles	linear	.0±.1		dwg no C-8613-0041	
C	107-0132	KR	2007-10-05	0°±1°		scale 3:2		sheet 1 of 1 size A3	
D	108-0094	KR	2008-7-28	2001-12-18		FCJ		type Product Customer Drawing	
E	108-0145	JS	2008-10-18	dr	MINI K V	2001-12-18			
F	111-0193	GT	2011-12-20	engr	RAKHEE GEORGE	2001-12-18			
G	BLX-14380	MJM	2013-03-08	chr	GREGAR MATHEW	2016-03-31			
H	BLX-123881	GM	2016-03-31	app	BIJU K PAUL	2016-03-31			
sheet index	revision	G1.1							
	sheet	1							

Copyright FCJ FCconnect.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#)
[65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-](#)
[5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-360C032-B](#) [FCN-](#)
[367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)