



MATERIAL and Plating  
 Body:white PTFE  
 Center contact:brass gold plated  
 Clip:beryllium,nickel pated  
 ELECTRICAL DATA  
 Contact resistance:<3ma  
 Contact current:1.5A  
 Test voltage:3800V rms  
 Working voltage:2800V rms  
 MECHANICAL DATA:> 100  
 TEMPERATURE RANGE:-55°C to +125°C  
 PACKAGING:per 100 pieces

IND	DESIGNATION
C	ADD CHARACTERISTICS AND SHOW CENTER CONTACT

PART NUMBER 86382001LF

rev	ecn no	dr	date
A	LS06-0022	MPE	2006/03/11
B	LS06-0095	LGO	2006/07/19
C	LS07-0287	MPE	2007/11/09
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface ISO 1302	tolerance std ISO 406 ISO 1101	projection A3	mm
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	M. PESSON	2006/03/11	ANGULAR	0.X	±0.1
Eng	M. PESSON	2006/03/11	LINEAR	0.XX	±0.1
Chr	LEGARRE	2006/03/11	0.XX' ±2'	0.XXX	±0.1
Appr	LEGARRE	2006/03/11	Product family	D-SUB	Spec ref -
title HIGH VOLTAGE CONTACT FEMALE FOR FLAT CABLE .		dwg no C01-8638-0360		Rev. C	
catalog no		-		CUSTOMER sheet 1 of 1	

Copyright FCJ.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub Contacts](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[D02-22-26S-10000](#) [8656352067LF](#) [131A15029X](#) [132J22039X](#) [132A11029X](#) [132A11049X](#) [132A12059X](#) [1757912-1](#) [188582-000](#)  
[162A11889X](#) [1757913-1](#) [212558-1](#) [030-1955-000](#) [053744-0098](#) [053744-0099](#) [053745-0105](#) [053745-0111](#) [601098N003](#) [D-610-10CS2962](#)  
[86303057NLF](#) [131A11019X](#) [162A11819X](#) [40-9854MP](#) [1-208778-5](#) [FC120N2](#) [MC7526D/AA](#) [MC8122D/AA](#) [FC4010D-15](#) [FC4006D](#)  
[121A05329A](#) [164C16669X](#) [86566620064LF](#) [131A13019X](#) [DLS3XS5AK40X](#) [09692825723](#) [030-1954-000](#) [L17DM53744207](#)  
[L17RRD1M11400](#) [030-1952-000](#) [030-1953-000](#) [030-1953-030](#) [132C11039X](#) [132J15019X](#) [132C15019X](#) [131A10029X](#) [8638PSC2006LF](#)  
[8656453067LF](#) [86566520064LF](#) [L17DM537441](#) [L17DM537425001](#)