



Overview

Amphenol RF offers a number of 50 ohm SMA and RP-SMA connectors designed to accommodate ultraminiature micro-coax cable types. These jacks and plugs are available in the straight and right-angle crimp configuration and feature a threaded coupling mechanism for secure mating.

The SMA connector is a lightweight and compact connector that offers reliable RF performance up to 7 GHz. Their high-strength design provides vibration resistance while the micro-coax cables adds considerable flexibility making them ideal for a broad range of design possibilities.

These connectors are part of a robust portfolio of ultraminiature products suitable for applications such as drones, test and measurement equipment, industrial automation and inspection, and Bluetooth and cellular technology.

Features and Benefits

- Reliable electrical performance up to 6 GHz
- Threaded coupling mechanism for secure mating
- Vibration resistant design
- Ideal for applications with space constraints

Applications

- Antennas
- Base Stations
- Drones
- Test and Measurement Equipment
- Industrial Automation and Inspection
- Bluetooth and Cellular technology
- WLAN

Ordering Information

SMA Straight Crimp Jacks for Micro-Coax Cable

Part Number	Description
901-10761	SMA Straight Crimp Jack, 0.81 mm
901-10762	SMA Straight Crimp Jack, 1.13 mm
901-10763	SMA Straight Crimp Jack, 1.32 mm
901-10764	SMA Straight Crimp Jack, 1.37 mm

RP-SMA Straight Crimp Jacks for Micro-Coax Cable

Part Number	Description
901-10774	RP-SMA Straight Crimp Jack, 0.81 mm
901-10775	RP-SMA Straight Crimp Jack, 1.13 mm
901-10776	RP-SMA Straight Crimp Jack, 1.32 mm
901-10777	RP-SMA Straight Crimp Jack, 1.37 mm
901-10778	RP-SMA Straight Crimp Jack, RG-178

SMA Straight Crimp Plugs for Micro-Coax Cable

Part Number	Description
901-10107	SMA Straight Crimp Plug, 1.13 mm
132387	SMA Straight Crimp Plug, 1.32 mm
132390	SMA Straight Crimp Plug, 1.37 mm

RP-SMA Straight Crimp Plugs for Micro-Coax Cable

Part Number	Description
901-10779	RP-SMA Straight Crimp Plug, 0.81 mm
901-10780	RP-SMA Straight Crimp Plug, 1.13 mm
901-10781	RP-SMA Straight Crimp Plug, 1.32 mm
901-10782	RP-SMA Straight Crimp Plug, 1.37 mm

RP-SMA Right-Angle Crimp Plugs for Micro-Coax Cable

Part Number	Description
901-10783	RP-SMA Right-Angle Crimp Plug, 0.81 mm
901-10784	RP-SMA Right-Angle Crimp Plug, 1.13 mm
901-10785	RP-SMA Right-Angle Crimp Plug, 1.32 mm
901-10786	RP-SMA Right-Angle Crimp Plug, 1.37 mm

Amphenol RF

Four Old Newtown Road
Danbury, CT 06810

For more information visit www.amphenolrf.com
or call 800.627.7100

Amphenol® RF

Technical Specifications

Electrical

Impedance		50Ω
Frequency Range		DC - 7 GHz
Voltage Rating		166 RMS Max Continuous
Dielectric Withstanding Voltage		500 VRMS Min
VSWR (Return Loss)	DC – 3 GHz	1.3 Max
	3 – 6 GHz	1.4 Max
Insulation Resistance		5000 MΩ Min
Center Contact Resistance		3.0 mΩ Min
Outer Contact Resistance		2.0 mΩ Min

Environmental

Temperature Range		-65°C to +165°C
RoHS Compliance		Compliant with Exemption 6C

Mechanical

Mating Cycles		500 Min
Coupling Mechanism		Threaded

Materials

Body		Brass, Gold Plating
Contact		Beryllium Copper, Gold Plating
Insulator		PTFE, Natural

Note: Technical specifications are typical and may vary by specific part number. Please see component drawing.

Amphenol RF

Four Old Newtown Road
Danbury, CT 06810

For more information visit www.amphenolrf.com
or call 800.627.7100

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[89674-0827](#) [6059674-1](#) [630059-000](#) [6501-1071-002](#) [6769](#) [7002-1541-010](#) [7002-1572-002](#) [7004-1512-000](#) [7009-1511-004](#) [7101-1541-010](#)
[7101-1571-002](#) [7105-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-040](#) [7242-1511-000](#) [7405-1521-005](#) [7405-1521-802](#)
[804S01D04M040](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [PL11C-026](#) [PL40-36](#) [9408-1113-000](#) [980-](#)
[8666-005](#) [11 SMA-50-2-6 / 111 NE](#) [11 SMA-50-3-6 / 111 NE](#) [1-201144-1](#) [120919](#) [R107003010W](#) [R112186000](#) [R113053000W](#) [R113082097](#)
[R113236000](#) [R114083000](#) [R114670000W](#) [R123415000W](#) [R124076320](#) [R124076450](#) [R124175123](#) [R125075000W](#) [R125075001](#)
[R125172000W](#) [R125415030](#) [R141007161](#)