Plug Attenuators

Amphenol's plug-style attenuator is compact in size, offers attenuation values from 0-20dB, and is available in LC, SC, and FC industry standard connector styles, with either flat or angle polish.

Amphenol's attenuators use light absorption technology. This eliminates the scattering of light into the fiber cladding that could be reflected back from the connector interface.

With the short distance between connector end faces, the reflected light creates interferences that in turn create the desired insertion loss variation as the wavelength changes.



Features and Benefits

Available in LC, FC, and SC configurations

Wavelength independent for multiple wavelength system compatibility

Compact plug style design easily fits into existing patch panels

Available in 1dB through 20dB attenuation values

Polarization insensitive

Compact plug style design easily fits into existing patch panels

Specifications

Attenuation values:

≤5dB ±0.5dB

>6dB ± 10% of nominal value

Return Loss:

≤-55dB Ultra Polish (UPC)

≤-65dB S/M Angle Polish (APC)

Operating Temperature: -40 to +80°C

Operating Wavelengths: 1310/1550nm (center wavelength)

Operating Band Pass: 1260nm to 1360nm and 1430nm to 1580nm

PDL: ≤0.2dB

≤5dB ±0.5dB

Industry Compliance

RoHS compliant

Meets GR-910 specifications

Connectors comply to applicable TIA/EIA and IEC intermateability standards

Applications

Data Centers

IT/Datacom

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fibre Optic Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

0004700001 6100-R 6313 F709722200 F709730000 F718183204 F727403500 F727752800 8119 9440F20-27S-190 944-120-6001 9441F10SL-3S 9444W28-21S 9444W36-10S 9446W20-16S 953-101-5310-P 954-101-57202B A0270169 12-9122 12-5702 AX101713 AX102420 AX103923 AX104024 AX104193 AX104230 AX104562 AX105203-B25 AX105205-S1 EHSC2M 17-300800 181-011-126 181-011-S 181-057-126 NKSOPBUY 20500002116 2064996-1 20800001065 2170 9132 2612 2620 9291 9440F16-10S 9440F20-18S 9444W32-738 9446F16-108-190 953-106-50231 953-120-5003 955-120-5110