Amphenol[®] Gray is the New Green



Gray Zinc / Nickel (ZnNi) Plating

In a world of Black and White, the answer is typically Gray. Amphenol Gray ZnNi is your RoHS connector plating answer.

Amphenol Industrial Operations (AIO) is proud to offer a RoHS compliant harsh environment plating. Gray Zinc over an Electroless Nickel (Gray ZnNi) base, with a Light Gun Metal Gray appearance. This Plating was initially developed for Harsh Marine environments given it's high corrosion resistance. There is no significant galvanic reaction when mated with leading standard market plating options, and it is Cadmium Free, making this the ideal solution for high corrosive environments and is available in all your favorite Amphenol Industrial Connectors.

Features:

- Cadmium Free
- RoHS Compliant
- -65°C 125°C Temperature Range
- <2.5mΩ Conductivity
- Rated at 500 Hours Salt Spray
- Compatible with Market Standard Plating Options
- Non-Magnetic

www.amphenol-industrial.com

Gray ZnNi plating is available on Amphenol Industrial's standard core products, with no significant galvanic reaction between existing OD Cad, Black Zinc and Electroless Nickel plating. AIO's connectors plated in Gray ZnNi makes for the best harsh environment solutions on the market.




ACA-B and GT Series

Gray ZnNi plating meets the acceptance criteria of the following salt spray/salt fog tests:

- ISO 21207:2004 Method B
- ASTM B117 (500 hours)
- ANSI/EIA-364-26B

97 Series



AC Threaded

Use the Amphenol Plating Suffix (Excluding 97 Series) (072) at the end of a part number (724) = (116) RoHS Contacts & (072) Gray Zinc Nickel

How to Specify Gray ZnNi

Example:

GTC06F18-10P(072)

97 Series (959) (no pre filled solder cups) (958) (solder filled solder cups non-RoHS assembly) Example: 97-3106A18-10P(959)

Amphenol Industrial Plating Comparison:

	Gray ZnNi	OD Cad	Electroless Nickel	Zinc Cobalt
Color	Gray	Olive Drab (Mil Green)	Nickel-Metallic	Black or Green
Compatible with CAD	\checkmark	\checkmark	×	\checkmark
Salt Spray Resistance	500 hrs	96 hrs	48 hrs	48 hrs
Temp Rating	125 °C	175 °C	200 °C	125 °C
Non-Reflective	\checkmark	\checkmark	×	\checkmark
RoHS Compliant	\checkmark	×	\checkmark	\checkmark

Applications: (But not limited to)

Marine Craft

- Electric Vehicle
- Industrial Machinery / Equipment
- Power Generation



Notice: Specifications are subject to change without notice. Contact your nearest Amphenol Corporation Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suggestions concerning possible use of our products are made without representation or warranty that any such use i free of patent infringement and are not recommendations to infringe any patent. The user should assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all connectors

orth America: mphenol Industrial Operations 30 N. Freeport Drive, Plant 4 ogales, AZ 85621 al: (888) 364-9011 ax: (520) 285-5134

Europe: Amphenol Industrial Operations Europe Via Barbaiana 5 1-20020 Lainate (MI) Italy Tel: +39 02 93254.204 Fax: +39 02 93254.444

Asia: Amphenol Technology (Zhuhai) Co., Ltd. No. 63 Xin Han Road, San Zao Town Jin Wan District, Zhuhai City, China 519040 Fel: +86 756-3989760 Fax: +86 756-3989768

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular MIL Spec Tools, Hardware & Accessories category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

0113-201-2025 600-079-06 600-146-06 M10-101983-183 M10-454396-008 602GB18808 CS3102A-22-14PW M2887615-CD 627-009 M38999/9-19B 630A007NF083A 630B007M051A 630BJ003NF032H 637-149NF04B M39029/29-215 6408-203V-09273 6426-201-11343 650FS002NF16 660-008NF14S7-01 660-009M22H8-03 660-013NF19U6-210 660-015M10S6-17 660-015NF10S5-01 660-015NF14R3.5-01 660-023NF19H6-19 660-024NF11S12-01 660-024NF11S3-01 660-024NF17S4-109 660-050XM17F4-01 660-068NF25R6-30G 660-070M23S8-04 660-073MTCH9-20 M83723/61-18W M83723/61-218R M83723/61-224W 667-084-23C 667-084-35C 667-224NF16 687-697NF-1 M85049/94-10-A M85049/96-7-A M855282-10A01A M85528/2-10B M855282-18A01A M85528/2-22A01A M85528/2-22AA 710HS460NF2508 780-001-22G12-SK 780-002-19G12-SK 780-002-20G12SK