

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:


HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-4S* PLUG (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

| 6 | 6 CONTACT SIZE AND REAR SEAL WIRE RANGE: | | | | | | |
|---|--|----------------------|----------------------|-----------------------------|--|--|--|
| | | | MAX. INSUL | _ | | | |
| | SIZE | O.D. | | WIRE RANGE | | | |
| | 16 | 1.35 mm (.053 in) | 3.05 mm (.120 in) | 14 - 20 AWG (2.0-0.5mm²) | | | |



| PART NUMBER CHART | | | | |
|-------------------|--|--|--|--|
| PART NUMBER | | | | |
| AT04-4P-RD01 | | | | |
| AT04-4P-RD01BLK | | | | |
| AT04-4P-RD01BLU | | | | |
| AT04-4P-RD01BRN | | | | |
| AT04-4P-RD01GRN | | | | |
| AT04-4P-RD01RED | | | | |
| AT04-4P-RD01WHT | | | | |
| AT04-4P-RD01YEL | | | | |
| AT04-4P-RD01ORG | | | | |
| | | | | |

| REVISIONS | | | | | | | |
|-----------|--------|------------------------|---------|-------|-------|--|--|
| REV | ECO | DESCRIPTION | DATE | BY | APPR | | |
| A3 | - | RELEASE NEW DWG FORMAT | 25DEC13 | DRP | | | |
| A4 | C0540S | UPDATE DIMENSIONS | 23JUN16 | JONY | TOMMY | | |
| A5 | - | ADD COLOR OPTION | 23NOV20 | LOUIE | TOMMY | | |

REQUIRES CONTACT RETENTION WEDGE AW4P



STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

| | SEE PART NUMBER CHART | | | REF:DT04-4P-C015, DT04-4P-CE02 | | | | | |
|---|---------------------------|---|--|--|---|------------|-------------|----|--|
| | PART NUMBER | | | DESCRIPTION | | | ITEM | | |
| QUANTITY MA | | | MAT | ERI | ALS LI | ST | | | |
| UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64 | | SIGN | ATURES | S DATE | | Amphonol | | | |
| | | DRAWN: | LOUIE | 23NOV20 | Amphenol | | | | |
| 2 PL DEC ±0.15 3 PL DEC ±0.08 | 2 PL DEC ±0.15 Angles ±1° | | ORION | 25NOV20 | Sine Systems - www.amphenol-sine.com | | | | |
| 3) Note reference = X | | ENGINEER: | | | 44724 Morley Drive Clinton Township, MI 48036 | | | | |
| MATERIAL SPECIFICA | MATERIAL SPECIFICATIONS: | | TOMMY | 27NOV20 | | | | | |
| | | CUSTOMER: RECEPTACLE, 4 PIN, AT SERIES, | | | | | ί, | | |
| PROCESS SPECIFICATIONS: | | THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, | | | REDUCED DIAMETER WIRE SEAL | | | L | |
| | | THE AMPHENO OF REPRODUC | NS AND PERFORM ON ARE THE PR OL CORPORATIO CTION ARE IMPL ARE SUBJECT TO | OPERTY OF ON. NO RIGHTS JED. ALL | B C- | AT04-4P-RD | 01XXX | A5 | |
| NEXT ASS'Y: | | MANUFACTURING VARIATIONS. | | SCALE: NONE | | знеет 1 | or 1 | | |

AT04-4P-RD01XXX

RECEPTACLE, 4 PIN, AT SERIES, REDUCED DIA. WIRE SEAL

3

ΞΞ

AT Series™ - Contact Size 16 Options

| Machined Contacts, Sockets & Pins | | | | | | |
|-----------------------------------|--|----|----------|----------|--|--|
| Part Number | Description | | AWG | Туре | | |
| AT60-215-1631 | Male Contact - Pin, Gold-plated 16 | | 14 | Machined | | |
| AT62-209-1631 | Female Contact - Socket, Gold-plated | 16 | 14 | Machined | | |
| AT60-215-16141 | Male Contact - Pin, Nickel-plated | 16 | 14 | Machined | | |
| AT62-209-16141 | Female Contact - Socket, Nickel-plated 16 | | 14 | Machined | | |
| AT60-202-1631 | Male Contact - Pin, Gold-plated | 16 | 16-20 | Machined | | |
| AT62-201-1631 | Female Contact - Socket, Gold-plated 16 1 | | 16-20 | Machined | | |
| AT60-202-16141 | Male Contact - Pin, Nickel-plated 16 16-20 I | | Machined | | | |
| AT62-201-16141 | Female Contact - Socket, Nickel-plated | 16 | 16-20 | Machined | | |
| AT60-202-1631-22 | Male Contact - Pin, Gold-plated | 16 | 22-24 | Machined | | |
| AT62-201-1631-22 | AT62-201-1631-22 Female Contact - Socket, Gold-plated 16 22-24 | | Machined | | | |
| AT60-202-16141-22 | Male Contact - Pin, Nickel-plated | 16 | 22-24 | Machined | | |
| AT62-201-16141-22 | Female Contact - Socket, Nickel-plated | 16 | 22-24 | Machined | | |

| Tooling - Machined Contacts | | | | |
|-----------------------------|-------------|--|--|--|
| Part | Part Number | Description | | |
| | CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only) | | |
| | CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only) | | |

| Contact Removal Tools | | | | |
|-----------------------|---------------|---|--|--|
| Part | Part Number | Description | | |
| | ATRT-100 | Used for removal of contacts for A Series™ products | | |
| | AT11-310-1605 | Contact Removal Tool, Plastic, Size 16 | | |
| | A114017 | Sealing Plug, Size 16, White | | |

| Stamped & Formed Contacts, Sockets & Pins | | | | | | |
|---|--|------|-------|------------------|--|--|
| Part Number Description | | Size | AWG | Туре | | |
| AT60-14-0144 | Male Contact - Pin, Gold-plated | 16 | 14-16 | Stamped & Formed | | |
| AT62-14-0144 | Female Contact - Socket, Gold-plated | 16 | 14-16 | Stamped & Formed | | |
| AT60-14-0122 | Male Contact - Pin, Nickel-plated | 16 | 14-16 | Stamped & Formed | | |
| AT62-14-0122 | Female Contact - Socket, Nickel-plated | 16 | 14-16 | Stamped & Formed | | |
| AT60-16-0144 | Male Contact - Pin, Gold-plated | 16 | 16-18 | Stamped & Formed | | |
| AT62-16-0144 | Female Contact - Socket, Gold-plated | 16 | 16-18 | Stamped & Formed | | |
| AT60-16-0122 | Male Contact - Pin, Nickel-plated | 16 | 16-18 | Stamped & Formed | | |
| AT62-16-0122 | Female Contact - Socket, Nickel-plated | 16 | 16-18 | Stamped & Formed | | |
| AT60-16-0644 | Male Contact - Pin, Gold-plated | 16 | 18-20 | Stamped & Formed | | |
| AT62-16-0644 | Female Contact - Socket, Gold-plated | 16 | 18-20 | Stamped & Formed | | |
| AT60-16-0622 | Male Contact - Pin, Nickel-plated | 16 | 18-20 | Stamped & Formed | | |
| AT62-16-0622 | Female Contact - Socket, Nickel-plated | 16 | 18-20 | Stamped & Formed | | |
| AT60-16-0844 | Male Contact - Pin, Gold-plated | 16 | 20-22 | Stamped & Formed | | |
| AT62-16-0844 | Female Contact - Socket, Gold-plated | 16 | 20-22 | Stamped & Formed | | |
| AT60-16-0822 | Male Contact - Pin, Nickel-plated | 16 | 20-22 | Stamped & Formed | | |
| AT62-16-0822 | Female Contact - Socket, Nickel-plated | 16 | 20-22 | Stamped & Formed | | |

| Tooling - Stamped & Formed Contacts | | | | |
|-------------------------------------|-------------------------|---|--|--|
| Part | Part Number Description | | | |
| | MFX-3950 | Crimp Die - Size 16, 18-20AWG (S&F contacts only) | | |
| | MFX-3953 | Crimp Die - Size 16, 16-18AWG (S&F contacts only) | | |
| | MFX-3975 | Crimp Die - Size 16, 14-16AWG (S&F contacts only) | | |
| | MFX-3990 | Crimp Die - Size 16, 20-22AWG (S&F contacts only) | | |
| | ATT-16-00 | Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only) | | |
| | ATT-16-01 | Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only) | | |
| | ATT-1612-03 | Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only) | | |

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052225-L 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546