

## NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:


HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)


- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-6S\* PLUG (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

| 6 | 6 CONTACT SIZE AND REAR SEAL WIRE RANGE: |           |            |                           |  |  |
|---|--|-----------|------------|---------------------------|--|--|
|   |  |           | MAX. INSUL | TYPICAL                   |  |  |
|   | SIZE                                     | O.D.      | O.D.       | WIRE RANGE                |  |  |
|   | 16                                       | 1.35 mm   | 3.05 mm    | 14 - 20 AWG               |  |  |
|   | 10                                       | (.053 in) | (.120 in)  | (2.0-0.5mm <sup>2</sup> ) |  |  |



| PART NUMBER CHART |                 |  |  |
|-------------------|-----------------|--|--|
| COLOR             | PART NUMBER     |  |  |
| GREY              | AT04-6P-RD01    |  |  |
| BLACK             | AT04-6P-RD01BLK |  |  |
| BLUE              | AT04-6P-RD01BLU |  |  |
| BROWN             | AT04-6P-RD01BRN |  |  |
| GREEN             | AT04-6P-RD01GRN |  |  |
| RED               | AT04-6P-RD01RED |  |  |
| WHITE             | AT04-6P-RD01WHT |  |  |
| YELLOW            | AT04-6P-RD01YEL |  |  |
| ORANGE            | AT04-6P-RD01ORG |  |  |

| REVISIONS |        |                        |         |       |       |
|-----------|--------|------------------------|---------|-------|-------|
| REV       | ECO    | DESCRIPTION            | DATE    | BY    | APPR  |
| A3        | -      | RELEASE NEW DWG FORMAT | 26DEC13 | JARRY | -     |
| A4        | C0540S | UPDATE DIMENSIONS      | 28JUN16 | JONY  | TOMMY |
| A5        | -      | ADD COLOR OPTION       | 23NOV20 | LOUIE | TOMMY |





STANDARD MOLDED COLOR IS GREY.

ADDITIONAL COLORS SHOWN IN PART NUMBER

CHART ARE AVAILABLE VIA SPECIAL ORDER.

AT04-6P-RD01XXX

RECEPTACLE, 6 PIN,AT SERIES, REDUCED DIAMETER SEAL

35

ITEM

## **AT Series™** - Contact Size 16 Options

| Machined Contacts, Sockets & Pins  |  |          |          |          |
|--|--|----------|----------|----------|
| Part Number Description  |  | Size     | AWG      | Туре     |
| AT60-215-1631  | Male Contact - Pin, Gold-plated 16 14 N                    |          | Machined |          |
| AT62-209-1631  | Female Contact - Socket, Gold-plated                       | 16       | 14       | Machined |
| AT60-215-16141   | Male Contact - Pin, Nickel-plated                          | 16       | 14       | Machined |
| AT62-209-16141   | Female Contact - Socket, Nickel-plated 16 14 Mac           |          | Machined |          |
| AT60-202-1631  | Male Contact - Pin, Gold-plated 16 16-20 1                 |          | Machined |          |
| AT62-201-1631  | Female Contact - Socket, Gold-plated 16 16-20              |          | Machined |          |
| AT60-202-16141   | Male Contact - Pin, Nickel-plated 16 16-20 Mc              |          | Machined |          |
| AT62-201-16141   | Female Contact - Socket, Nickel-plated                     | 16       | 16-20    | Machined |
| AT60-202-1631-22   | 02-1631-22 Male Contact - Pin, Gold-plated 16 22-24 Mac    |          | Machined |          |
| AT62-201-1631-22   | -1631-22 Female Contact - Socket, Gold-plated 16 22-24 Mac |          | Machined |          |
| AT60-202-16141-22  | Male Contact - Pin, Nickel-plated                          | 16       | 22-24    | Machined |
| AT62-201-16141-22 Female Contact - Socket, Nickel-plated 16 22-24 Machin |  | Machined |          |          |

| Tooling - Machined Contacts |             |  |  |
|-----------------------------|-------------|--|--|
| Part                        | Part Number | Description  |  |
|                             | CA-5D12     | Universal Hand Crimp Tool, Size 12/16/20<br>(Machined contacts only) |  |
|                             | CA-5E12     | Pneumatic Crimp Tool, Size 12/16/20<br>(Machined contacts only)      |  |

| Contact Removal Tools |               |   |  |  |
|-----------------------|---------------|---|--|--|
| Part                  | Part Number   | Description   |  |  |
|                       | ATRT-100      | Used for removal of contacts for A Series™ products |  |  |
|                       | AT11-310-1605 | Contact Removal Tool, Plastic, Size 16              |  |  |
|                       | A114017       | Sealing Plug, Size 16, White                        |  |  |

| Stamped & Formed Contacts, Sockets & Pins |  |    |       |                  |
|---|--|----|-------|------------------|
| Part Number                               | lumber Description                     |    | AWG   | Туре             |
| AT60-14-0144                              | Male Contact - Pin, Gold-plated        | 16 | 14-16 | Stamped & Formed |
| AT62-14-0144                              | Female Contact - Socket, Gold-plated   | 16 | 14-16 | Stamped & Formed |
| AT60-14-0122                              | Male Contact - Pin, Nickel-plated      | 16 | 14-16 | Stamped & Formed |
| AT62-14-0122                              | Female Contact - Socket, Nickel-plated | 16 | 14-16 | Stamped & Formed |
| AT60-16-0144                              | Male Contact - Pin, Gold-plated        | 16 | 16-18 | Stamped & Formed |
| AT62-16-0144                              | Female Contact - Socket, Gold-plated   | 16 | 16-18 | Stamped & Formed |
| AT60-16-0122                              | Male Contact - Pin, Nickel-plated      | 16 | 16-18 | Stamped & Formed |
| AT62-16-0122                              | Female Contact - Socket, Nickel-plated | 16 | 16-18 | Stamped & Formed |
| AT60-16-0644                              | Male Contact - Pin, Gold-plated        | 16 | 18-20 | Stamped & Formed |
| AT62-16-0644                              | Female Contact - Socket, Gold-plated   | 16 | 18-20 | Stamped & Formed |
| AT60-16-0622                              | Male Contact - Pin, Nickel-plated      | 16 | 18-20 | Stamped & Formed |
| AT62-16-0622                              | Female Contact - Socket, Nickel-plated | 16 | 18-20 | Stamped & Formed |
| AT60-16-0844                              | Male Contact - Pin, Gold-plated        | 16 | 20-22 | Stamped & Formed |
| AT62-16-0844                              | Female Contact - Socket, Gold-plated   | 16 | 20-22 | Stamped & Formed |
| AT60-16-0822                              | Male Contact - Pin, Nickel-plated      | 16 | 20-22 | Stamped & Formed |
| AT62-16-0822                              | Female Contact - Socket, Nickel-plated | 16 | 20-22 | Stamped & Formed |

| Tooling - Stamped & Formed Contacts |                         |   |  |
|-------------------------------------|-------------------------|---|--|
| Part                                | Part Number Description |   |  |
|                                     | MFX-3950                | Crimp Die - Size 16, 18-20AWG (S&F contacts only)       |  |
|                                     | MFX-3953                | Crimp Die - Size 16, 16-18AWG (S&F contacts only)       |  |
|                                     | MFX-3975                | Crimp Die - Size 16, 14-16AWG (S&F contacts only)       |  |
|                                     | MFX-3990                | Crimp Die - Size 16, 20-22AWG (S&F contacts only)       |  |
|                                     | ATT-16-00               | Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only) |  |
|                                     | ATT-16-01               | Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only) |  |
|                                     | ATT-1612-03             | Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only) |  |

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052225-L 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546