

C504F Scalable Clip 1.0 mm

Part No. C504 10M006 118 3

- All-purpose (e.g. antenna or grounding contact)
- For flat contact area
- Same Pad-Layout for all scalable Clips
- SMT solderable
- Tape & Reel packaging
- Pick & Place capable



View represents all available contact positions.

For more information, please contact us [here](#).

Series Mobile Connectors
Subseries Mobile Connectors C504F

COMMON CHARACTERISTICS		
No. of contacts		1
Termination		solder
Total height (undeflected)		1.0 mm
Stroke		0.4 mm
CLIMATICAL CHARACTERISTICS		
Operating temperature		-40 °C...+85 °C
MECHANICAL CHARACTERISTICS		
Mechanical lifetime		100 mating cycles
Contact force		Min. 0.2 N
MATERIALS		
Contacts		Stainless steel
Plating contacts		min. 0.5 µm Au
Plating solder area		min. 0.025 µm Au
Underlayer		min. 1,27 µm Ni.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Memory Card Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[M21-033321-005](#) [6407-249V-25273P](#) [6407-249V-25343P](#) [6426-201-21343](#) [69.920.0553.0](#) [FCN-568P068-G/07-4V](#) [809180410000000](#)
[N7E50-7516PG-20-WF](#) [21920-5](#) [2041353-2](#) [33CFAE-DN](#) [502431-1011](#) [EN2997S61212BN](#) [EN2997SE61212BN](#) [617230001](#) [95622-003LF](#)
[95079-00CALF](#) [84648-056HLF](#) [68-580163-21S](#) [33DVIR-29S12R](#) [125A-78C00](#) [MI20A-50PD-SF-EJL\(71\)](#) [KP10S-SF-PEJ\(812\)](#) [504536-](#)
[0691](#) [504580-0691](#) [CCM03-3109 B LFT](#) [2309923-1](#) [61126-050CAHLF](#) [G85DT17001P1EU](#) [G85B21611142HHR](#) [GSD090144HR](#)
[G85D1140022P1HR](#) [GMCB05801124EU](#) [112K-TAA0-RA1](#) [115S-ACA2](#) [115S-ACA3](#) [115S-BS00](#) [115S-BT00](#) [115V-AD00](#) [MCSP-Q1-08-](#)
[A-SG-T/R](#) [503960-0695](#) [101B-TAA0-R](#) [101D-TAAA-R01](#) [101D-TAAB-R01](#) [104D-TCA0-R06](#) [104B-TAA0-R](#) [112C-TBAR-R02](#) [114B-](#)
[40B00-R02](#) [112G-TA00-R](#) [112J-TDAR-R01](#)