




Length



AISG 8-pin female interface with 6 loaded contacts



AISG 8-pin male interface with 6 loaded contacts



**Characteristics**

|                       |   |  |
|-----------------------|---|--|
| Connectors            | according IEC 61076-2-106 and AISG C485           |  |
| Contact plating       | Ag  |  |
| Cable construction    | Jacket  | FR-PE, OD 8,0mm  |
|                       | 6 conductors                                      | 4x0,75mm <sup>2</sup> (power)<br>2x0,25mm <sup>2</sup> twisted pair (data) |
|                       | Screen  | Coverage 85%   |
|                       | Color   | black  |
| Temperature range     | -40°C to +80°C (fixed position)                   |  |
| Protection class      | IP 68 (mated)                                     |  |
| Salt spray resistance | Functional safety in plugged condition up to 720h |  |

**Configuration of Terminals**

| Female AISG connector | color of wire | Signal          | Male AISG connector |
|-----------------------|---------------|-----------------|---------------------|
| 1                     | blue          | +12V DC nominal | 1                   |
| 3                     | white         | RS485 B         | 3                   |
| 4                     | green         | RS485 GND       | 4                   |
| 5                     | brown         | RS 485 A        | 5                   |
| 6                     | red           | +24V DC nominal | 6                   |
| 7                     | black         | DC return       | 7                   |

pins 2 and 8 not connected

**\* order other length**

| Cable Style and length | Definition of length   | Example                                   |
|------------------------|------------------------|---|
| CA 091 60 4000 XXX     | XXX = Length in meters | CA 091 60 4000 005<br>(length = 5 meters) |

**Preferred Cable Length (other length on request)\***

| Part number        | length m / ft |
|--------------------|---------------|
| CA 091 60 4000 950 | 0,5 / 1,6     |
| CA 091 60 4000 001 | 1 / 3,2       |
| CA 091 60 4000 002 | 2 / 6,6       |
| CA 091 60 4000 003 | 3 / 9,8       |
| CA 091 60 4000 004 | 4 / 13,1      |
| CA 091 60 4000 005 | 5 / 16,4      |
| CA 091 60 4000 007 | 7 / 23,0      |
| CA 091 60 4000 010 | 10 / 32,8     |
| CA 091 60 4000 015 | 15 / 49,2     |
| CA 091 60 4000 020 | 20 / 65,6     |
| CA 091 60 4000 050 | 50 / 164      |
| CA 091 60 4000 100 | 100 / 328     |

|                                |  |   |  |                            |  |
|--------------------------------|--|---|--|----------------------------|--|
| Gewicht (errechnet) / Calc WT: |  | Zul. Abw./Tolerances:                       |  | Maßstab / Scale: A3        |  |
| Prüfmaß / Testdimension        |  | DIN / ISO 13715                             |  | CUSTOMER DRAWING           |  |
| Teileindex Partindexnumber     |  | Datum/Date Name                             |  |                            |  |
|                                |  | Gez. Drawn 30.06.2016 MCARL                 |  | Cable assembly             |  |
|                                |  | Status: in work Inspector: 30.06.2016 MCARL |  | FR-PE cable, 6 pins loaded |  |
|                                |  | <b>Amphenol-Tuchel Electronics GmbH</b>     |  | Blatt/Sheet 1              |  |
| 01 201600004 30.06.2016 MCARL  |  | Index Änderung/Description Datum/Date Name  |  | M CA 091 60 4000 XXX 1 Bl. |  |
|                                |  | Ers. f. / Replacement for:                  |  |                            |  |

Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of the utility model or design.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Sensor Cables / Actuator Cables](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[60963](#) [60964](#) [M83513/19-F01CP](#) [703000D02F2002](#) [703001D02F0602](#) [703001D02F300](#) [704000D02F120](#) [773032K02F030](#) [802027107404-1](#)  
[802027213811-1](#) [804001A09M150](#) [805001A09M0502](#) [84914-0235](#) [84914-0237](#) [885030A09M020](#) [8R4J30E03C3003](#) [1200651332](#)  
[1200651713](#) [1200660844](#) [1200660845](#) [1200661173](#) [1200680071](#) [1200720053](#) [1200720081](#) [1200720099](#) [1200720217](#) [1200800231](#)  
[1200860125](#) [1200870123](#) [1200980102](#) [1200650267](#) [1200650298](#) [1200660183](#) [1200660782](#) [1200660849](#) [1200661295](#) [1200661297](#)  
[1200661342](#) [1200661343](#) [1200670080](#) [1200670220](#) [1200680331](#) [1200720252](#) [1200730184](#) [1200860344](#) [1200870359](#) [1200870643](#)  
[1200980008](#) [1200980031](#) [1210502211](#)