

Cool Edge 1.00mm PCIe® Connectors

HIGH SPEED SPACE–SAVING CONNECTOR FOR BOARD–TO–BOARD APPLICATIONS

Cool Edge PCIe® connectors bring high speed PCIe® support into a one-piece card edge package with 16GT/s Gen 4 and 32GT/s Gen 5 capabilities. Slim connector design saves space on the motherboard while facilitating other higher density applications. These connectors come with a simple housing design with an overall reduced footprint, providing additional benefits over standard PCIe® CEM solutions. The conductive plastic design of these connectors provide enhanced signal integrity. The contact pads extend outwards from housing, making inspection easier.

- Provides standard and short solder tail versions
- Supports speeds up to 32GT/s
- Saves more space than standard PCIe® solution
- Enhanced signal integrity using conductive plastic design
- Simple housing design allows vertical AOI inspection

FEATURES

- 1.00mm signal pin pitch based on PCIe® interface
- 1.1A per pin for power application
- 0.7A per pin for signal application
- Supports speeds from 16GT/s, up to 25GT/s and 32GT/s
- PCIe® slots of x8, x16 and x24
- Supports 1.60mm thick mating board
- Slim connector design: height 9.60mm; width 5.80mm; length 95mm
- Simple housing design in vertical configuration
- Connector design with conductive plastic at the base
- Contact pads extend outwards from housing
- Short solder tail version available



TARGET MARKETS



BENEFITS

- Supports board-to-board applications
- Backward compatibility with PCIe® Gen 3 and forward compatibility with PCIe® Gen 5
- Supports most add-in card and next generation GPU applications
- Multiple applications served, from ICT to Consumer
- Saves more space than standard PCIe® with slimmer form factor, smaller width and footprint
- Allows for easy Automated Optical Inspection (AOI) of the connector
- Provides good signal integrity performance at high speeds up to 32GT/s
- Makes inspection easier compared to standard PCIe®
- Good for short riser card fanout and routing at PCB edge

TECHNICAL INFORMATION

MATERIAL

- Contact Base Metal: Copper alloy
- Contact Area Finish: Gold over nickel
- Solder Area Finish: Tin over nickel
- Housing: High temperature thermoplastic (UL 94V-0)

ELECTRICAL PERFORMANCE

- Contact Resistance:
 - 30mΩ max.
 - 10mΩ max. change after test
- Current Rating: 1.1A per pin for power application/0.7A per pin for signal application with temperature rise not exceeding 30°C
- Dielectric Withstanding Voltage: 500V

MECHANICAL PERFORMANCE

- Durability: 200 mating cycles
- Mating Force: 0.6N/pin max. for signal pin
- Unmating Force: 0.06N/pin min. for signal pin

SPECIFICATIONS

- Amphenol Product Specification: SCE009

ENVIRONMENTAL

- Temperature Life: 105±2°C for 240 hours. Per EIA 364-17
- Thermal Shock: 10 cycles between -55°C to +85°C. Per EIA 364-32
- Humidity: 24 cycles between 25±3°C at 80±3% RH and 65±3°C at 50±3% RH. Per EIA 364-31
- Mixed Flow Gas

PACKAGING

- Tray

TARGET MARKETS/APPLICATIONS



Baseband
Commercial Systems
Networking
Radio Units



High-end Computing System
Server and Storage Systems

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Standard Card Edge Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[CR7E-30DB-3.96E\(72\)](#) [6565204-6](#) [PKC-156](#) [1437274-4](#) [147889-1](#) [1489165-4](#) [EBT15622B2X](#) [1-582587-1](#) [284-0102-12100](#)
[306022901000000](#) [307-012-502-202](#) [307-056-520-300](#) [245-062-520-350](#) [287-0032-12101](#) [306-028-525-102](#) [307-072-526-202](#) [345-060-559-](#)
[303](#) [392-008-559-201](#) [534671-1](#) [341-240-317](#) [345-044-500-300](#) [346-240-318](#) [395-100-524-300](#) [09-07-2032](#) [10035388-802LF](#) [10122859-](#)
[009LF](#) [10127905-B04B24BLF](#) [530555-1](#) [5-678046-1](#) [73726-0005](#) [66308-1](#) [1-1437275-6](#) [PEC-07-02-T-S-A](#) [346-014-520-801](#) [307-048-502-](#)
[202](#) [CE100F22-9-C](#) [CE100F26-7-C](#) [CE100F28-3-D](#) [CE156F18-9-C](#) [CE156F22-5-D](#) [CE156F22-9-C](#) [CT100F22-2-D](#) [CT100F22-3-D](#)
[CT100F24-2-D](#) [CT100F24-3-D](#) [CT100F24-6-C](#) [CT156F22-4-D](#) [MLSS100-12-C](#) [MLSS100-16-C](#) [SCC100F-11-C](#)