

Amphenol

TVP Series

Multiway Circular Fibre Optic Connector



A high performance, harsh environment fibre optic connector. The MIL-C-38999 Series III connector can be specified as a dedicated fibre optic connector or a hybrid of fibre optics, power, signal, coax or data bus contacts.

- Ceramic, stainless steel or bronze alignment sleeve.
- Size 16 contacts (MIL-C-38999).
- Shell material - aluminium bronze, aluminium, stainless steel.
- Anti-vibration screw coupling mechanism.
- Environmentally sealed.
- Contacts per connector - minimum 2/maximum 37.
- Plug and receptacle can facilitate the use of pin or socket termini in either way.
- Application applies to any area which requires a totally sealed multiway fibre optic interconnection.

Performance

Optical				
Attenuation	<1.5dB for 50/125 fibre			
Fibre types	50/125	100/140	200/300	200/280
Cable types	To customer specification			
Termination method	Epoxy/polish			
Environmental	Temperature -55°C to +200°C cable dependant			
Durability	500 cycles			

Fibre Optic Contacts Part Number Information

Fibre Size Core/Cladding Dia. (Microns)	Size 16 Socket	Size 16 Pin	A Dia. Ref**	
			Inches	Microns
50/125	CF-198035-10	CF-198036-10	.0050	127
62.5/125	CF-198035-10	CF-198036-10	.0050	127
100/140	CF-198035-17	CF-198036-17	.0057	145
200/230	CF-198035-53	CF-198036-53	.0093	236
200/240	CF-198035-57	CF-198036-57	.0097	245
200/280	CF-198035-74	CF-198036-74	.0114	290
200/300	CF-198035-80	CF-198036-80	.0120	305

Now available in size 20 contacts

Fibre Size Core/Cladding Dia. (Microns)	Size 20 Socket	Size 20 Pin	A Dia. Ref**	
			Inches	Microns
50/125	CF-198080-010	CF-198081-010	0.0050	127
62.5/125	CF-198080-010	CF-198081-010	0.0050	127
100/140	CF-198080-017	CF-198081-017	0.0057	145

For specific ordering information, please consult factory.

For full part numbering information, please see the full range Mil-C-38999 catalogue.

For further information on cables, connectors and assemblies please consult your local office.
Product specifications and performance characteristics are typical only, and subject to change.

Notice: Products are sold subject to Amphenol's conditions of sale ("the standard conditions"). All specifications and statements contained herein are believed to be correct at the time of printing, but no representation or warranty, express or implied, is given as to any specification or statement contained herein. Product specifications including performance characteristics are typical only and subject to deviation. Specifications are also subject to change without notice. Users should not assume that all safety measures are indicated or that other measures may not be required. No representation or warranty, express or implied, is given that any use of products (including any stated or suggested use) does not infringe any patent, registered design or other third party rights and no stated or suggested use of products can be taken to recommend any such infringement.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[0004700001](#) [6100-R](#) [6313](#) [F709722200](#) [F709730000](#) [F718183204](#) [F727403500](#) [F727752800](#) [8119](#) [9440F20-27S-190](#) [944-120-6001](#)
[9441F10SL-3S](#) [9444W28-21S](#) [9444W36-10S](#) [9446W20-16S](#) [953-101-5310-P](#) [954-101-57202B](#) [A0270169](#) [12-9122](#) [12-5702](#) [AX101713](#)
[AX102420](#) [AX103923](#) [AX104024](#) [AX104193](#) [AX104230](#) [AX104562](#) [AX105203-B25](#) [AX105205-S1](#) [EHSC2M](#) [17-300800](#) [181-011-126](#)
[181-011-S](#) [181-057-126](#) [NKSOPBUY](#) [20500002116](#) [2064996-1](#) [20800001065](#) [2170](#) [9132](#) [2612](#) [2620](#) [9291](#) [9440F16-10S](#) [9440F20-18S](#)
[9444W32-73S](#) [9446F16-10S-190](#) [953-106-50231](#) [953-120-5003](#) [955-120-5110](#)