1		2			3	4	
Р 15.30±0.4			ø3.86 -0.03		<u>Active</u> zone	-	А
B	22. 70 Maxi	\$ \$ 9.10 ^{±0.30}	0.95 max	<u>i</u>	ELECTRICAL CHARACT - Impedance: 500HM	- TERISTICS IS	В
C DM537415004 DM537415001	VCLF COAXIAL CONTACT M/	ALE ANGLE 3.15 4 5	5.09 5.95	RG 58 CU KX 15 RG 179 BU RG 316 BU KY224	- Insulation resis - Contact resistan - Insertion lost: - MECHANICAL CHARACT	standing voltage: 600V stance 5000: 14 OHMS ce < 5 m OHMS < 0.2 dB FERISTICS set of contact 0.4 N to 9 N s 500	С
D PART NUMBE NOTE: RoHS INFOR - The "LF" p country reg - The product solder prod - Packaging s	Dispersion Converting						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Contacts category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

173112-0723173112-0393173112-0389173112-0750173112-0912FMP009P104FMP010P104FMP010S104FMP016P104FMP016S104FMP051S110FMX006S128B124C25029X131A11039X132A11019X132J22039X132A11029X132A12059X132C12029XRMPIR01S02E2RLFDM53744-11757912-1188582-000162A11839X162A11889X1757913-1FK20S18-02V_100FMP006S110FMP009S104FMP139S115212558-1D02-22-26P-10000L17DM53744217D-610-10CS2820030-1955-000030-50634053744-0098053744-0099053745-0115053745-0111601064N004601098N0036-745288-2D-610-10CS296286303057NLFDM537425001NCLF131A11019X173112-0045162A11819X1731120397