

Waterproof Micro USB 2.0

SHIELDED WATERPROOF MICRO USB 2.0 TYPE B

Amphenol ICC's Waterproof Micro USB 2.0 comes with full metal shielding that protects against Electromagnetic Interference (EMI), Radio-Frequency Interference (RFI), and Electromagnetic Discharge (ESD). The USB connector supports fast charging with 1.8A power contacts and is capable to support up to 3A for customized needs. The dual layer shell design with plastic tongue ensures high reliability and prevents damage from connector abuse. These halogen-free connectors meet IPX4 industry ratings. Customized designs are also available upon request.

- Equipped with 5 circuits capable of 480Mb/s high-speed transmissions
- Compliant to USB 2.0 specifications
- Fully shielded metal shell with overmolded sealing
- Halogen-free and RoHS compliant

FEATURES

- Equipped with 5 circuits compliant to USB 2.0 specifications
- Robust shell hold-down design
- The smallest USB 2.0 interface
- Optimized shell structure design with full metal shielding
- Rugged Gold-plated leaf contact
- Halogen-free material
- Optimized design structure with epoxy glue-based plastic sealing

NEW


TARGET MARKETS



BENEFITS

- High-speed signal up to 480Mb/s transmission
- Improved peeling force
- Saves space on PCB
- Protects against EMI, RFI and ESD
- Prevents corrosion and improves reliability
- Meets environmental, health and safety requirements
- Meets IPX4 ratings

TECHNICAL INFORMATION

MATERIAL

- Housing: High temperature thermoplastic, complies with UL 94V-0, black colour
- Shell: Stainless steel
- Contact: Copper alloy, selective gold plated on contact area, 50u" min. nickel under-plated gold flash overall or tin 100u"min. selective plated.

MECHANICAL PERFORMANCE

- Insertion Force: 35N (3.57 Kgf) max.
- Withdrawal Force: 10N (1.02 Kgf) min.
- Durability: 10,000 cycle unplug / plug 8N (0.81 Kgf) min.
- Vibration: No disturbance greater than 1µs
- Mechanical Shock: No disturbance greater than 1µs

ELECTRICAL PERFORMANCE

- Low Level Contact: Initial 30mΩ max. ; Final ΔR: 20mΩ max.
- Insulation: 100MΩ min.
- Current Rating/Temperature Rise: ΔT30°C max.
- Voltage: 30V DC.
- Current: Signal contacts 1.0A, Power contacts 1.8A

PACKAGING

- Tape & Reel

SPECIFICATION

- Amphenol Specification: PS-7655

ENVIRONMENTAL

- Operating Temperature: -40°C to +85°C
- Shipping Storage Temperature: -20°C to +60°C
- Thermal Shock: No physical damage, contact resistance ΔR=10mΩ max.
- Cyclic Temperature Humidity: No physical damage, contact resistance ΔR=10mΩ max.
- Temperature Life: No physical damage, contact resistance ΔR=10mΩ max.
- Salt Spray: No physical damage, contact resistance ΔR=10mΩ max.
- Solderability: 95% of immersed area, No voids pin holes

TARGET MARKETS/APPLICATIONS



Charger
Car Media Player/Hub



Connector Hub
Flash Disk
Mobile Phone/Tablet
VR Camera



Hard Disk Drives
Solid State Drives



Industrial Computer
POS System



Medical

PART NUMBERS

Description	Part Numbers
Waterproof Micro USB 2.0, Type B Receptacle, Right Angle SMT, IPX4 Rating	GMCBA058XX1230HHR

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[65-647-8-BK-BU](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#)
[KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#)
[KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [17-210051](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [MAB 8 SN V](#) [A-USB A-](#)
[2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SMT-AS1N-W30](#) [4689-1](#) [1-](#)
[1734084-2](#) [E8110-001-01](#) [MUSBA81130](#) [33UBARS1-04SW11](#) [33UBAR-04SW11](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [10135326-001LF](#)
[M9177/3-1](#) [925](#) [4198](#) [690-024-633-031](#) [KUSBEX-BSFS1N-W](#) [USBFTVC6MRG](#) [UA-20BMFA-SL8001](#)