

Micro SD and SD Card Sockets

SD COMPLIANT FOR UHS-I AND UHS-II INTERFACE

Amphenol is a leader in SD card sockets and has the capability to support customized designs. The push-push eject feature is designed for ease of card extraction. The user-friendly SD card socket is ideal for use in portable devices such as digital cameras and mobile phone, server applications as well as automotive devices.

- Compatible with second reflow process
- Extremely low camber after reflow process
- Shielding for superior EMI/ESD
- Can be used for PCB 2 sided SMT
- Space-saving design
- Superior solderability and SI performance



FEATURES

- 2.70mm ultra thin card socket
- Compatible with second reflow process
- Extremely low camber after reflow process
- Shielded design for superior Electromagnetic Interference (EMI) and Electromagnetic Discharge (ESD)
- Simple card lock mechanism

BENEFITS

- Saves space
- Can be used for Printed Circuit Board (PCB) 2 sided SMT
- Superior solderability performance
- Superior signal integrity (SI) performance
- Prevents card from ejecting and card scrape prevention

TECHNICAL INFORMATION

MATERIAL

- Housing: High Temperature Thermoplastic, complies with UL 94V-0
- Contact: Copper Alloy
- Shell: Stainless Steel

MECHANICAL PERFORMANCE

- Insertion Force: 14N max. (Lock force)
- Extraction Force: 14N max. (Lock force release)
- Standard Durability: 10,000 cycles

ELECTRICAL PERFORMANCE

- Current Rating: 0.5A
- Voltage Rating: 5V AC
- Contact Resistance: 100m Ω max.

PACKAGING

Tape and Reel

SPECIFICATION

 Amphenol Product Specification: PS-7330 (SD) & PS-7500 (Micro SD)

PART NUMBERS

Description	No. of Positions	Туре	Part Numbers
Micro SD Card Socket, LCP Black	8	Hinge	GTFH08131YHR
Micro SD Card Socket, Normal Open, 1.85mm Height, LCP Black	8	Push-Pull	GTFN08431B1HR
Micro SD Card Socket, LCP Black	8	Push-Push	GTFP08121YHR
Micro SD Card Socket, LCP Black	8	Push-Push	GTFP08131Y2HR
Micro SD Card Socket, LCP Black	8	Push-Push	GTFP08131YHR
Micro SD Card Socket, LCP Black	8	Push-Push	GTFP08431B1EU
Micro SD Card Socket, LCP Black	8	Push-Push	GTFP08431BEU
Micro SD Card Socket	8	Push-Push	GTFP08531Y6HR
Micro SD 4.0 Card Socket, 1.45 mm Height, Normal Open, LCP Black		Push-Push	GTF4P17131HR
SD Card Socket, 15U" GOLD	9	Push-Push	GSD09002SEU
SD Card Socket	9	Push-Push	GSD09002SHR
SD Card Socket	9	Push Pull	GSD090012SEU

ENVIRONMENTAL

- The card shall be mated and exposed to the following condition for 5 cycles:
- a) -55±3°C for 30 minutes
- b) +85±2°C for 30 minutes. Transit time shall be within 3 minutes, Recovery time 1~2 hours
- The card shall be mated and exposed to the condition of +85±2°C for 96 hours, less than 25% relative humidity
- Salt Spray Test: EIA-364-26 condition 5 ± 1% salt solutions, at 35 ± 2°C duration 48 hours

TARGET MARKETS/APPLICATIONS



Infotainment



Mobile Phone Tablet Virtual Reality Camera



Server Storage

Disclaimer Please note that the above information is subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Memory Card Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

M21-033321-005 6407-249V-25273P 6407-249V-25343P 6426-201-21343 69.920.0553.0 FCN-568P068-G/07-4V 80918041000000 N7E50-7516PG-20-WF 21920-5 2041353-2 33CFAE-DN 502431-1011 EN2997S61212BN EN2997SE61212BN 617230001 95622-003LF N7E50-U516RB-50-SIN0005 95079-00CALF 84648-056HLF 68-580163-21S 33DVIR-29S12R 125A-78C00 MI20A-50PD-SF-EJL(71) KP10S-SF-PEJ(812) 504536-0691 504580-0691 CCM03-3109 B LFT 2309923-1 61126-050CAHLF IC1GA-68PD-1.27DS-EJ(72) GTFP08432B1HR G85DT17001P1EU G85B21611142HHR GSD090144HR G85D1140022P1HR GMCB05801124EU 112K-TAA0-RA1 115S-ACA2 115S-ACA3 115S-BS00 115S-BT00 115V-AD00 MCSP-Q1-08-A-SG-T/R 503960-0695 101B-TAA0-R 101D-TAAA-R01 101D-TAAB-R01 104D-TCA0-R06 104B-TAA0-R 112C-TBAR-R02