


MILLIPACS® 2mm HARD METRIC SERIES – RIGHT ANGLE RECEPTACLE CONNECTORS

OVERVIEW

Millipacs® is a 2mm modular, Board-To-Board and Cable-To-Board Interconnection System in Hard Metric (HM) configuration designed in accordance with IEC 917, IEC 61076-4-101 and Telcordia GR-1217-CORE standards.

The 2mm HM connector is one of the most popular backplane connector system. Millipacs® series offers attractive propositions for all market segments due to the cost-effectiveness, user flexibility, standardization and availability of its broad range. Millipacs® connector system is extensively used for chassis-based packaging in the Communications, Data, Medical and Industrial & Instrumentation segments.

Millipacs® series HM right angle receptacles are offered in standard signal modules of 5 and 8 rows. 5 row modules are available up to maximum of 125 signal contacts and 8 row modules are available up to maximum 200 signal contacts per 50mm length. Besides signal module, hybrid modules are available with signal pins, power and coax contacts. Right angle headers receptacles mate with vertical headers and right angle headers.




FEATURES

- Hard Metric
 - 2mm pitch
-
- Modular and Scalable by 25mm to 50mm
-
- 2-beam tulip contact
 - Multipurpose center, Coding feature, Guiding feature and location peg
-
- Stamped contacts
 - Blank position feasibility
-
- Hybrid connectors with signal, power and coaxial contacts
-
- Two outer rows

BENEFITS

- Popular equipment practice standard. Millipacs® co-exists with all HM compatible connectors and accessories
 - Adequate spacing for routing PCB traces and thereby optimizing board layers, Reduces PCB real estate Vs 2.54mm
-
- Standard Modular length, without any loss of position
-
- Equalized signal path and contact reliability
 - Easy guiding and visual identification. Prevents wrong mating
-
- Accurate True Position
 - Improves creepage distance, Custom loading
-
- Enables versatile circuit design
-
- Optional shielding



MILLIPACS® 2mm HARD METRIC SERIES – RIGHT ANGLE RECEPTACLE CONNECTORS



TECHNICAL INFORMATION

MATERIALS

- Insulator material: High-Temperature polymer
- Contact material: Copper Alloy
- Contact plating: Gold/Palladium nickel on mating areas and Tin over Nickel on press-fit/terminal area

ELECTRICAL PERFORMANCES

- Operating current: 1.5 A at 20°C
: 1.0 A at 70°C
- Test voltage: 750 Vrms
- Contact resistance: 20 mΩ max
- Insulation resistance: 10⁴ MΩ min

MECHANICAL PERFORMANCE

- Mating force: 0.75 N max per contact pair
- Withdrawal force: 0.15 N min per contact pair
- Hertz stress: 200 Kpsi min
- Misalignment: Longitudinal ± 2.0mm
Transversal ± 2.5mm
- Inclination: ±2.0°

SPECIFICATIONS

- Product specification: GS-12-203
- Application specification: GS-20-022

ENVIRONMENTAL

- Operating temperature: -55°C to +125°C

APPROVALS AND CERTIFICATIONS

- Designed in accordance with IEC 917 and IEC 61076-4-101
- Fits DIN 43356 and IEEE 1301 Hard Metric Practice
- Telcordia GR-1217-CORE standards
- UL and CSA recognized

PACKAGING

- Tray Packaging

TARGET MARKETS/APPLICATIONS

- Communications
 - IP, Internet backbone driving high bandwidth requirements
 - LAN / WAN interfaces & data over public networks
 - Core Switches
 - Routers
 - Hubs
 - Base Station
 - Wireless Base Station
 - Transmission Access Systems
- Data
 - Servers
 - Storage units
- Industrial & Instrumentation
 - Data Acquisition systems for Test & Measurements
 - Railway Traffic Management & Control Systems
 - Control Systems for Process
 - Energy & Power Industries
 - In-flight Entertainment & Communication for Avionics
 - Digital Image Processing
 - Multimedia
 - Signage
 - Video Surveillance
 - Radar
 - Sonar System
 - UAV
- Medical
 - MRI Scanners
 - Diagnostic Equipment

Disclaimer

**MILLIPACS® 2mm HARD METRIC
SERIES – RIGHT ANGLE RECEPTACLE CONNECTORS**

PART NUMBERS

No. of signal rows	Type	Features	Right Angle Receptacle series	Max. No. of signal pins	Mounting style
5	A	22 column, 50mm + MPC	HM2R10P	110	Press-fit
	A	22 column, 50mm + MPC + location peg	HM2R01P	110	Press-fit
	A	12 column, 30mm + MPC	HM2R27P	60	Press-fit
	A	22 column, 50mm + MPC + recess for guide pin + location peg	HM2R29P	110	Press-fit
	B	25 column, 50mm	HM2R02P	125	Press-fit
	B22	22 column, 44mm	HM2R70P	110	Press-fit
	B19	19 column, 38mm	HM2R71P	95	Press-fit
	AB	25 column, 50mm + polarization	HM2R65P	125	Press-fit
	AB22	22 column, 44mm + polarization	HM2R66P	110	Press-fit
	AB19	19 column, 38mm + polarization	HM2R67P	95	Press-fit
	C	11 column, 25mm + end polarization	HM2R30P	55	Press-fit
	C	11 column, 25mm + end polarization + location peg	HM2R03P	55	Press-fit
	CR	11 column, 25mm + reversed + end polarization + location peg	HM2R20P	55	Press-fit
	L	50mm, 6 power/coax + MPC	HM2E30P	6 Spl.	Press-fit
	M	50 mm, 55 signal + 3 power/coax + MPC	HM2R05P	3 Spl.+ 55	Press-fit
	N	25mm, 3 power/coax + end polarization	HM2E32P	3 Spl.	Press-fit
8	D	22 column, 50mm + MPC	HM2R81P	176	Press-fit
	D	22 column, 50mm + MPC + location peg	HM2R87P	176	Press-fit
	DE	25 column, 50mm + polarization	HM2R95P	200	Press-fit
	E	25 column, 50mm	HM2R88P	200	Press-fit
	F	11 column, 25mm + end polarization	HM2R83P	88	Press-fit
	F	11 column, 25mm + end polarization + location peg	HM2R89P	88	Press-fit

* MPC – Multi purpose center for polarization and coding

* Application tooling are available on request

* Compact PCI Connectors are available for Types A, B22, B19, AB22, and AB19

* Performance levels: 3 – 50 mating cycles;
2 – 250 mating cycles;
1 – 500 mating cycles.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hard Metric Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[6345127-1](#) [646916-9](#) [6469658-1](#) [973108](#) [1-2000713-0](#) [1-2000713-2](#) [1-2000713-3](#) [120646-1](#) [1645343-1](#) [1645456-1](#) [1645594-1](#) [1645595-1](#)
[1645601-1](#) [1934822-1](#) [278071110010833](#) [1645179-1](#) [1645245-1](#) [1645457-1](#) [1645525-1](#) [1645570-1](#) [1645596-1](#) [17041102202](#) [17-8072-125-](#)
[000-863+](#) [1857470-1](#) [1934275-1](#) [1934289-1](#) [1934759-1](#) [2000673-1](#) [2170292-2](#) [2-536642-6](#) [3-106015-1](#) [352188-1](#) [352629-1](#) [3-646529-0](#)
[5120823-1](#) [5120899-1](#) [3-100145-0](#) [3-100147-0](#) [3-100669-1](#) [3-106081-0](#) [HM2DK2368PLF](#) [5646530-1](#) [3-352049-0](#) [3-352069-0](#) [3-352115-0](#)
[3-352638-0](#) [352189-1](#) [3-646357-0](#) [3-646487-0](#) [3-646513-0](#)