



SECTION A-A

N = Number of poles
 Dim L = $N \times 3.81 + 0.8$
 Dim P = $(N-1) \times 3.81$
 Dim T = $N \times 3.81 + 9.8$

	Dim L	Dim P	Dim T
2-6p	±0.15		±0.15
7-12p	±0.20		±0.20
13-18p	±0.30		±0.30
19-24p	±0.40		±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	6/23'06	Voltage/Current rating is changed from 160V/8A to 125V/4A	Marvin
△	6/23'06	Solid/Stranded wire is changed from AWG16-28 to AWG20-28	Marvin
△	6/23'06	Withstanding Voltage is changed from 1.3KV to 1.25KV	Marvin
△	12/02'08	Flange screw changed from "-" to "+/-"	Tony
△	11/21'09	The normal grey No. changed from RAL7004/P to RAL7035/D	Kind
△	02/22'11	Electrical is changed	Runner
△	05/10'11	The dimension is changed from 3.0 to 3.8	Runner
△	04/11'12	Contact is changed	Runner

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item ① Terminal body:Thermoplastic (UL94V-0)
- Item ② Terminal body:Thermoplastic (UL94V-0)
- Item ③ Terminal lever:Thermoplastic (UL94V-0)
- Item ④ Wire guard:Stainless Steel
- Item ⑤ Female contact:PhBz (CuSn) Tin plated
- Item ⑥ With flange screw:Steel M2.5 plated zinc "+/-"

△ Electrical

- Voltage rating: 300V △
- Current rating: 8A △
- Solid wire(AWG): 14-28 △
- Stranded wire(AWG): 14-28 △
- Wire strip length: 8-9mm
- Withstanding Voltage: 1.6KV △
- Operating temperature: -40°C to +115°C
- Safety Approval:
- Critical dimension: △

PART NO.

HW xx 30 x 2 xxxx G

RoHS compliant
(lead<4%)
In copper Alloy

Poles
07 7 CONTACTS
08 8 CONTACTS
... ..
24 24 CONTACTS

Color
0 Black
5 Green
(RAL 6018/T)
6 Blue
△ 8 Grey
(RAL 7035/D)

0000 Standard @ Logo
000A Standard ANY Logo
Any special item by
customer request,
please contact sales
department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE				HW3.81 SERIES (with flange) 2P ~ 24P			
PART NO.		DWG NO.		8HW0102			
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
		Runner 2012.04.11	Tony 2008.12.02			UNIT: mm	X. ±0.50
						SCALE: NONE	X.X ±0.30
SHEET: 01/01				REV.: H		X.XX ±0.10	X° ±1°

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [734-104](#) [734-302](#) [8-141-P](#) [8426620000](#) [860505](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#)
[PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFH16150](#) [ELFP03110](#) [ELFP10210](#) [ELFT06250](#)
[ELVP03100](#) [1700410](#) [1700425](#) [1702246](#) [1717806](#) [1719600](#) [1734692](#) [1734795](#) [1740291](#) [1752441](#) [1752865](#) [1754144](#) [1760051](#) [1760336](#)
[1777701](#) [1783410](#) [1800227](#) [1801080](#) [1836888](#) [1848818](#) [1849079](#) [1860870](#) [1876327](#) [1896417](#) [1903096](#) [19346](#) [1946309](#) [1970579](#) [1973592](#)