



N=NUMBER OF POLES

Dim L	(N-1)×5.0+6.0
Dim B	(N-1)×5.0

	TOL				
	1--4P	5--9P	10--14P	15--19P	20--24P
Dim L	±0.15	±0.20	±0.30	±0.40	±0.50
Dim B	±0.15	±0.20	±0.30	±0.40	±0.50

SIGN	DATE	DESCRIPTION	APPROVER
△	2/26'07	The Soldering temperature from 245° to 250°	Aaron
△	7/17'09	Oprating Tem.changed to -40°C ~ 115°C	Kind
△	7/17'09	Current rating changed from 7A to 6A	Kind
△	05/23'11	Current rating is changed from 6A to 8A	Steven

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item 1 Insulating body Thermoplastic (UL94V-0)
- Item 2 Insulating cover Thermoplastic (UL94V-0)
- Item 3 Insulating lever Thermoplastic (UL94V-0)
- Item 4 Contact pin Brass, Tin plated
- Item 5 Spring clamp Stainless steel

Electrical cULus

- Voltage rating:300V
- Current rating:8A
- Wire range:
 - Solid wire(AWG):16-26
 - Stranded wire(AWG):16-26
 - Wire strip length:6-7mm
- Withstanding Voltage:1.6KV
- △ ● Operating temperature:-40°C to +115°C
- △ ● Soldering temperature:250°C±10°C/5 Sec
- Safety Approval:
- Critical dimension:

PART NO.

HX xx 00 x 0 xxxx G

RoHS Pb<40,000ppm

Poles	0 Black	0000 Standard @ Logo
01 1Contacts	2 Red	000A Standard ANY Logo
02 2Contacts	3 Orange	Any special item by customer request,
... ..	5 Green(RAL6018/T)	please contact sales department.
24 24Contacts	8 Grey(RAL7004/P)	
	9 White	
	C Multiple colors	

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		HX 5.0 Series Vertical (90° Wire inlet)					
PART NO.		HXxx00x0xxxxG			DWG NO.		8HX0001
APPROVED		DESIGNED	DRAWN	CUST NO.		Tolerance	
		STEVEN 2011.05.23	STEVEN 2011.05.23			X. ±0.50	
				SHEET: 01/01		X.X ±0.30	
						X.XX ±0.10	
						X° ±1°	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Terminal Blocks](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[MBE-1512](#) [MBE-154](#) [MBE-156](#) [MBES-153](#) [MBES-156](#) [MH-2512](#) [MHE-132](#) [MHE-163](#) [MI-254 \(35\)](#) [MI-272](#) [880507](#) [MPT-275](#)
[15602-04-08-21](#) [BA311TU](#) [BA411SU](#) [MV-152](#) [MV-252-D](#) [MV-253/NCNOC](#) [MV-254-D](#) [MV-255](#) [MV-462](#) [MV-493](#) [MVE-252](#) [MVE-253](#)
[MVE-273](#) [MVEB-153](#) [1700096](#) [1705142](#) [1745195](#) [1760594](#) [1776118-2](#) [1-796689-8](#) [1-796692-6](#) [20020314-C121B01LF](#) [CB2-12](#)
[KP03215000J0G](#) [KP04215000J0G](#) [S451](#) [282802-2](#) [29.007](#) [29.116](#) [30.103](#) [30.106](#) [30.252](#) [30.503](#) [30.608](#) [30.753](#) [30.755](#) [30.756](#) [30.853](#)