


# 17H

D-Sub connectors - Stamped and Formed Contacts

## DUAL PORT D-SUB CONNECTORS



MAIN CHARACTERISTICS

### Specifications

- Connectors according to MIL C24308

Materials and platings	
Shells	Steel, tin plated
Insulator	Glass-filled thermoplastic, UL 94V-0
Pin contacts	Brass, selected gold in mating area; 2.54µm (100µ") min. tin on termination area over 1.27µm (50µ") min. nickel
Socket contact	Phosphor bronze, selected gold in mating area; 2.54µm (100µ") min. tin on termination area over 1.27µm (50µ") min. nickel
Rear insert	Brass, 2.54µm (100µ") min. nickel plated
Boardlock	Phosphor bronze, 2.54µm (100µ") min. tin plated
Screwlock	Brass, 2.54µm (100µ") min. nickel plated

Electrical Data	
Current rating	3A
Voltage rating	250V AC/rms 60Hz
Withstanding voltage	1000V AC/rms 60Hz for one minute
Insulation resistance	1000MΩ
Contact resistance	20mΩ max

Climatic Data	
Operating temperature	-55°C to +125°C
Salt spray	24 hours

Mechanical Data		
Single contact insertion force	0.54kg (1.19lb) max	
Single contact withdrawal force	0.06kg (0.13lb) min	
Mating and unmating force		
Unit: kg ( lb)		
No. of Cts	Mate (max)	Unmate (min)
9	3.05 (6.74)	0.36 (0.79)
15	5.09 (11.24)	0.46 (1.01)
25	8.44 (18.66)	0.81 (1.8)
15 (Hi-den)	3.81 (8.42)	0.52 (1.14)
Standard plating thicknesses		
<ul style="list-style-type: none"> <li>• gold flash</li> <li>• 0.4µm (15µ") gold</li> <li>• 0.76 µm (30µ") gold</li> </ul>		

DESCRIPTION

Amphenol's G17H dual port connectors are a state of the art design. The front metal shell helps reduce EMI / RFI emissions.


Designed to save PC board space, Amphenol's dual port provides two I / O connectors in a minimal amount of board space.

*Economical  
dual port  
connectors*

APPLICATIONS

- Industrial
- Telecom
- Any industry standard I / O connections




17H / E13



**Amphenol**




## Shell size dimensions- standard and high density



\* spacing between ports (see "how to order" for dimensions)  
 \*\* profile distance (see "how to order" for dimensions)  
 \*\*\* Footprint options (see "how to order" for dimensions)  
 H\*\*\* Standard Density (SD)  
 High Density (HD)  
 SD / SD = 8.08mm (.318")  
 SD / HD = 5.08mm (.200")  
 = 8.89mm (.350")  
 HD / HD = 8.89mm (.350")  
 = 5.08mm (.200")


### Recommended P.C.B. Layout




Shell Size	Nb OF CONTACTS	DIMENSIONS mm (inch)				
		A	B	C PLUG	D SOCKET	E
E	9/HD 15	30.84 (1.21)	24.99 (.984)	16.92 (.666)	16.24 (.639)	11.09 (.437)
A	15/HD 26	39.24 (1.54)	33.32 (1.31)	24.7 (.972)	24.56 (.967)	19.39 (.763)
B	25	53.04 (2.09)	47.04 (1.85)	38.96 (1.53)	38.38 (1.51)	33.24 (1.31)
E	15 (Hi-den)	30.84 (1.21)	24.99 (.984)	16.92 (.666)	16.24 (.639)	10.31 (.406)
C	37	69.32 (2.73)	63.50 (2.50)	55.42 (2.18)	54.76 (2.16)	49.86 (1.96)

## Panel mounting option


### Flange mounting options:



Threaded rear insert  
**0 / 4**




Fixed front female screwlock  
**7**




Removable female screwlock  
**1 / 5**


### Board mounting options:



Threaded hole  
**1**



Dual arrowhead boardlock  
**2**



Quad arrowhead boardlock  
**3**



## Dual Port Connectors

L17H X X X X X X X X

### Spacing Between Ports

- 1 - F = 15.88mm (.625")  
G = 28.42mm (1.12")
- 2 - F = 19.05mm (.750")  
G = 31.60mm (1.24")
- 3 - F = 22.86mm (.900")  
G = 35.41mm (1.39")
- 4 - **SCSI**  
G = 12.80mm (.504")
- 7 - F = 20.70mm (.815")  
G = 32.20mm (1.26")

### Top Connector

- 1 = 9 Pos. Male
- 2 = 9 Pos. Female
- 3 = 15 Pos. Male
- 4 = 15 Pos. Female
- 5 = 25 Pos. Male
- 6 = 25 Pos. Female
- 7 = 15 Pos. High Density Female
- 8 = 50 Pos. Female SCSI
- 9 = 26 Pos. High Density Female
- J = 15 Pos. High Density Male
- D = 37 Pos. Male
- E = 37 Pos. Female
- F = 44 Pos. High Density Male
- G = 44 Pos. High Density Female
- M = 62 Pos. High Density Male
- N = 62 Pos. High Density Female
- P = 78 Pos. High Density Male
- Q = 78 Pos. High Density Female

### Bottom Connector

- 1 = 9 Pos. Male
- 2 = 9 Pos. Female
- 3 = 15 Pos. Male
- 4 = 15 Pos. Female
- 5 = 25 Pos. Male
- 6 = 25 Pos. Female
- 7 = 15 Pos. High Density Female
- 8 = 50 Pos. Female SCSI
- 9 = 26 Pos. High Density Female
- K = 15 Pos. High Density Male
- D = 37 Pos. Male
- E = 37 Pos. Female
- F = 44 Pos. High Density Male
- G = 44 Pos. High Density Female
- M = 62 Pos. High Density Male
- N = 62 Pos. High Density Female
- P = 78 Pos. High Density Male
- Q = 78 Pos. High Density Female
- R = 9 Pos. Male + 9 Pos. Male
- S = 9 Pos. Female + 9 Pos. Female

### Footprint Options

- SD / SD**  
BLANK = 8.08mm (.318")
- SD / HD**  
BLANK = 5.08mm (.200")  
889 = 8.89mm (.350")
- HD / HD**  
BLANK = 8.89mm (.350")  
508 = 5.08mm (.200")

### Flange Mounting Options

- 0 = 4-40unc Rear Insert
- 1 = 4-40unc Removable Screwlock
- 3 = 3.05mm (.120") Clear Hole
- 4 = M3 Rear Insert
- 5 = M3 Removable Screwlock
- 7 = 4-40unc Fixed Front Screwlock

### Board Mounting Options

- 0 = Triple Arrowhead Boardlock
- 1 = 4 \* Threaded 4-40unc Inserts
- 2 = Dual Arrowhead Boardlocks
- 3 = Quad Arrowhead Boardlocks
- 4 = 3.18mm (.125") Clear Hole

### Shell Plating


- 1 = Bright Tin / Nickel
- 2 = Nickel

### Contact Plating

- 0 = Flash Fold
- 1 = 0.4µm (15µ") Gold
- 2 = 0.76µm (30µ") Gold
- 3 = Full Flash Gold
- 4 = 1.27µm (50µ") Gold

**For special request, please consult factory**

**Do not hesitate to contact us for further information**



# Amphenol

## Amphenol IT & Communication Products

Block A3/A4, The 4th Industrial District of  
Industrial Headquarters, Dong Keng Road  
Gong Ming Town, Shen Zhen China  
Fax: +86(0)755 2754 9955

### Technical Support

Tel: +86(0)755 2717 7945  
Info-dsub@amphenol.com.cn  
<http://www.dsubconnector.com>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub Dualport Connectors](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[787672-3](#) [164A15909X](#) [K42X-E15S/S-A4NJ](#) [K42X-E9SS-A4NJ](#) [242A14060X](#) [164A15819X](#) [DLS2SS5AN21X](#) [241A22450X](#) [242A14180X](#)  
[241A14190X](#) [DLS4SS5AN21X](#) [178-037-513R491](#) [178-037-613R491](#) [178-009-413R571](#) [178-009-513R571](#) [178-009-613R491](#) [178-009-613R691](#) [178-015-513R571](#) [178-015-613R571](#) [178-025-413R571](#) [178-025-513R571](#) [179-009-613R571](#) [179-025-513R571](#) [K42X-E15S/S-A4N](#) [L17H2220131](#) [178-015-513R491](#) [178-025-613R481](#) [178-025-613R571](#) [178-037-513R571](#) [178-037-513R671](#) [L17H2ED0130](#)  
[L17H1440130](#) [L17H1770231](#) [L17H2440120TM](#) [L17H1431134](#) [L17H1212130](#) [L17H2212120](#) [L17H1222134](#) [L17H2662120TM](#)  
[L17H2550120](#) [L17H2440120](#) [L17H2440121](#) [L17H1120134](#) [L17H2120120](#) [L17H2120230](#) [L17H1440134](#) [L17H2990130](#) [K42X-B25S/S-A4N](#) [K42X-E9P/E15S-A4NJ](#) [178-009-313R571](#)