



REV.

Bottom connector D=37pos. Male

Top connector D=37pos. Male

RoHS Compliant

PRODUCT CODE

ELECTRICAL : BOARDLOCK: BRACKET :

Voltage rating 250V AC(RMS)

Current rating 3A

Copper Alloy.Tin plated Zinc Alloy ,Nickel plated

Withstanding Voltage >1000 V AC(RMS) Contact resistance 25 m0hms max. Insulation resistance >1000 M Ohms

CONTACTS: BODY : SHELL:

Copper Alloy

PBT, UL 94V-0, Color:Black

Gold flash plated over 50u" nickel on mating area

SPCC, 100u" min tin over 50u" min nickel over 50u" copper

D-SUB TECHNICAL DATA

M

E C N

チーー

First Release Drawing

20/Aug/13

DATE

APPROVED ₽

DESCRIPTION REVISIONS

100u" tin plated over 50u" nickel on solder area

Spacing between ports 3-F=22.86 G=35.41

Board mounting options
3=Quad Arrowhead
boardlocks

Flange Mounting Options 0=4-40unc Rear Insert

Contact plating 0=Flash Gold

Shell plating 1=Tin

TOLERANCE:+/-0.05mm

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Dualport Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

787672-3 164A15909X K42X-E15S/S-A4NJ K42X-E9SS-A4NJ 242A14060X 164A15819X DLS2SS5AN21X 241A22450X 242A14180X 241A14190X DLS4SS5AN21X 178-037-513R491 178-037-613R491 178-009-413R571 178-009-513R571 178-009-613R491 178-009-613R691 178-015-513R571 178-015-613R571 178-025-413R571 178-025-513R571 179-009-613R571 179-025-513R571 K42X-E15S/S-A4N L17H2220131 178-015-513R491 178-025-613R481 178-025-613R571 178-037-513R571 178-037-513R671 L17H2ED0130 L17H1440130 L17H1770231 L17H2440120TM L17H1431134 L17H1212130 L17H2212120 L17H1222134 L17H2662120TM L17H2550120 L17H2440120 L17H2440121 L17H1120134 L17H2120120 L17H2120230 L17H1440134 L17H2990130 K42X-B25S/S-A4N K42X-E9P/E15S-A4NJ 178-009-313R571