



Boite boitier	A	B	B'	C	D	D'	E	F ±0,05	Pas	G	*
E	11,1	6,2	9,6	0,9	2,84	2,84	3,1	10,98	2,74	7,62	2x3
A	19,20	2,74	7,62	2,84	10,98	11,2	11,7	19,20	2,74	7,62	2x5
B	33,12	2,76	7,62	2,84	10,93	11,2	11,7	33,12	2,76	7,62	2x8
C	49,68	2,76	7,62	2,84	10,93	11,2	11,7	49,68	2,76	7,62	2x12
D	66,24	2,76	7,62	2,84	10,87	11,1	11,6	66,24	2,76	10,5	2x12

TECHNICAL DATA

'' D '' SUBMINIATURE CONNECTORS

SHELL: Steel .  
finish :tinned  
BODY: Glass filled thermoplastic.  
Flame retardant to UL 94 V-0 .  
Colour : black .

CONTACTS: Material for sockets : brass  
Material for pins : brass  
Finish of contact mating area :  
Gold over Ni

ELECTRICAL: Voltage proof >1000 V Rms to 50Hz .  
Nominal current 7,5 A (size20) 20 A (size8).  
Contact resistance <5m Ohms .  
Insulator resistance >5000 M Ohms .

CLIMATIC : Temperature range -55°C up to 85°C  
Damp heat 21 days ( + 40 - 95 % RH )  
Other climatic specifications in accordance  
with NF C 93-425, sheet HE501 and MIL C 24-308 .

MECHANICAL: Mating and unmating force size E 30 N max. 3.5 N mini.  
A 50 N max. 4.4 N mini.  
B 83 N max. 8.0 N mini.  
C 123 N max. 11.0 N mini.  
D 166 N max. 14.5 N mini.

L \*\*7D \* \*\* \* F179

L = RoHS

77D Shell steel tinned  
717D with Dimples plug only.

Shell size: E-A-B-C-D

Mounting type  
Without

Configuration:  
9- 15- 25- 37- 50

Contacts:  
Wire Wrap  
2 winding  
Option:  
Contact type : S - female  
                  : P - male

Amphenol Socapex  
Usine de Dole

IND. MODIFICATIONS EXEC. DATE Approb. N°SERIE 017F PLAN NOTICE NOTICE-17D IND.

DATE DU TRACÉ DESIGNATION L \*\* 7D \* \* \* \* F 179

COMMUNICATION ET UTILISATION INTERDITES SAUF AUTORISATION

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub Standard Connectors](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[56F706-005-LI](#) [56F711-015](#) [LV242999-142T12](#) [015-0341-000](#) [015-0372-005](#) [015-0372-008](#) [015-8755-001](#) [020419-0104](#) [012-0467-000](#)  
[012-9507-034](#) [012-9507-114](#) [020745-0008](#) [609-25P](#) [CT2-18-11PCAU](#) [CT6-10SL-3SC](#) [CT6-10SL-4SC](#) [CT6-14S-2SC](#) [CT6E14SA7SC](#)  
[CT6N10SL-4SSA34](#) [M83513/01-FC](#) [M83723/76W24619 L/C](#) [M85049/48-3-2F](#) [6STD09PCM99B70X](#) [6STD09SCM99B30X](#)  
[6STD09SCT99S40X](#) [6STD15PCT99S40X](#) [6STD15SCT99S40X](#) [6STF09PCM05B70X](#) [7-135760-9](#) [MC11E-10-6SN](#) [747552-3](#) [MD1-21PS](#)  
[MDM-15SCBRM7-F222](#) [MDM96517-699](#) [MDM96521-744](#) [MDVB1-21SL1](#) [MIK0-1-7SH003](#) [MIKQ6-7SH076](#) [MIKQ7-7PH077](#) [MIKQ7-](#)  
[7PH11](#) [MIKQ7-7PH32](#) [MJSV-28SL61](#) [MKJ4A1F14-55S](#) [8-135760-3](#) [8STD09PCM99B30X](#) [PG-KV/PV-16-GROM-SEALING](#) [GDA15P](#)  
[GDAY15PB](#) [980-0000-170](#) [980-0000-171](#)