

LMR®-195-UF FLEXIBLE LOW LOSS CABLE ASSEMBLIES

Times LMR cable assemblies are high performance broadband, flexible, low-loss RF coaxial cables that can be used virtually anywhere, either indoors or outdoors. As a completely Times manufactured solution, performance and reliability are assured.



- Excellent RF Shielding, better than 90 dB
- UV and weather resistant
- Flexible and easy to use

Mechanical Properties


	Units	
Diameter	in (mm)	0.195 (4.95)
Weight	lb/ft (kg/m)	0.021 (0.03)
Minimum Bend Radius	in(mm)	0.5 (12.7)
Operating Temperature	°F (°C)	-40° to 185°(-40 to 85)
Tensile Strength	lb (kg)	40 (18.2)
Bending Moment	ft lb (N-m)	0.1 (0.14)
Flat Plate Crush	lb/in (kg/mm)	10 (0.18)
Storage Temp	°F (°C)	-94 to 185 (-70 to 85)

KEY APPLICATIONS

- Antenna feeder runs
- Inter/intra cabinet jumpers
- Internal component equipment wiring
- GPS system wiring

Electrical Properties

• • • • • • • • • • • • • • • • • • •		
	Units	
Impedance	Ω	50 +/- 2
Maximum Frequency	GHz	6.0
Capacitance	pF/ft (pF/m)	25.4 (83.3)
Velocity of Propagation		74%
Delay	ns/ft (ns/m)	1.27 (4.17)
Shielding	· · · · · ·	>90dB minimum
Voltage Withstand	Volts DC	1000
Jacket Spark	Volts RMS	3000
Attenuation	dB/ft	dB/m
900 MHz	0.13	(0.43)
2.5 GHz	0.23	(0.74)
5.8 GHz	0.35	(1.17)
	_	



nner Conductor

Dielectric

3 Outer Conductor

4 Overall Braid

5 Jacket

Stranded BC

Foam PE

Aluminum Tape

Tinned Copper

TPR

LMR®-195-UF FLEXIBLE LOW LOSS CABLE ASSEMBLIES

Ordering Guide

LUF195- NMNM-3.0 F

Interface NM N Male SM SMA Male QM QMA Male TM TNC Male BM BNC Male Length

Units of Measure F Feet M Meters







WORLD HEADQUARTERS 358 Hall Avenue, Wallingford, CT 06492 1-800-867-2629



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Cable Assemblies category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

73-6352-10 73-6353-3 73-6364-6 R285001001 R288940004 R288940005 145111-05-12.00 1661-C-24 1801171170914KE 24P104C24J1-012 24P104C24P1-006 24P104C24P1-018 24P204C24J1-003 172-2150-EX 1800920920914PJ FCB-3030-ALT 21117-046 21117-050 PCX-24-50 24P103C24P2-003 25P203C25P2-003 PTWY-24-78 R284008001 R285001021 R285426000 R288940003 R288940008 RF179-74BJ3-77RP1-0305 4814-BB-24 5260-72 JT2N1-CL1-1F DLP-COAX1 4814-K-48 115101-09-06.00 CCNTN2-MM-LL335-26 73-6351-25 73-6352-3 73-6353-25 1800920920610PJ GD0BQ0BQ024.0 1-3636-600-5210 TL8A-11SMA-11SMA-01500-51 R284C0351060 R288940009 R288040009 R284C0351028 R288940002 9702-1SL-1 PT82NSMA 73-6353-10 R285020301W