

IMPEDANCE: 50 OHMS

FREQ. RANGE: DC TO 65.0 GHz DWV: **325 VRMS**

OPERATING TEMP.: -55°C TO +125°C

1.10:1 DC TO 26.5 GHz, 1.30:1 TYPICAL TO 50 GHz VSWR:

INSERTION LOSS: .12 X SQRT(F(F IN GHz)) **INSUL. RESISTANCE:** 5000 MEGOHMS MIN.

CONTACT RESISTANCE

OUTER CONDUCTOR: 2 MILLIOHMS MAX. INNER CONDUCTOR: 6 MILLIOHMS MAX. ENGAGEMENT/

DISENGAGEMENT: 2.5 LBS MAX. ENGAGEMENT

1.5 LBS MIN. DISENGAGEMENT

SOCKET CONTACT

MATERIAL: SEE NO		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X° ±1°0′ X°X′ ±15′	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING.		SV Microwave, Inc.		
FINISH: SEE NOTES		DECIMAL: .X ±.030 .XX ±.010	3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63MIL-STD-10. 6) DIA: SO N COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS		2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409		
SURFACE AREA: N/A		.XXX ±.005 INTERPRET DIMENSIONS AND TOLERANCES			SMPM, MALE TO T-FLEX 405 SMOOTH BORE INTERFACE FIT M38999 SIZE 12 INSERT		
PROPRIETARY		PER ASME Y14.5M - 1994					
THE INFORMATION CONTAINED IN THIS DRAY		THIRD ANGLE PROJECTION	DRAWN:	JMC 09/04/07	0175 0405 0005 0040		NOEKI
IS THE SOLE PROPERTY OF SV ANY REPRODUCTION IN PART OF WITHOUT THE WRITTEN PERMINANT	IN PART OR AS A WHOLE	+ +	CHECKED:	JM 09/04/07	SF3211-6		6004
SV MICROWAVE, INC IS PROHIB			APPROVED:	JM 09/04/07	SCALE: 4:1		SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connector Accessories category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

89674-0712 F702RX24 FERRULE-174 R125802000 R141802000 R141805000 R141842000 R161844000 R161862000 R161862000W R280752000 R280907000 R694261906 RFI21-13 RFI375-12-D3 RFI75-13-D2 RFI75-3 RFI75-4-D2 RFI97-13 AX102906 AX102907 R8997-0013 HP-375 HP-500 2098-0294-00 2098-3251-94 KA-81-05 89674-0805 RUBBER-CAP-BNC F1 FERRULE-223 202102-11 RFI25-5-D3 RFI75-12-D2 RFI75-2-D2 RFI75-4-D3 RFI75-4-D3 RFI97-14 360HS001M2508M6