

**ROHS COMPLIANT** 

# PRODUCT DATA DRAWING

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	DCN 38106	03/11	PJS





#### MATERIAL:

BODY,

PRESS CAP &

STAINLESS STEEL PER AMS-5640, ALLOY UNS S30300, TYPE 1 **COUPLING NUT:** 

**LOCK RING &** 

CONTACT: BERYLLIUM COPPER PER ASTM B196,

ALLOY No. UNS C17300, TD04

PTFE PER ASTM D1710, TYPE I, GRADE 1, CLASS B **INSULATOR:** 

GASKET: SILICONE RUBBER PER A-A-59588,

CLASS 2B, GRADE 50/60

FINISH:

**COUPLING NUT:** PASSIVATED PER AMS-2700

BODY,

PRESS CAP &

CONTACT: GOLD PER ASTM B488, TYPE II,

CODE C, CLASS 1.27; OVER NICKEL

PER AMS-QQ-N-290, CLASS 1, .00010" MIN.

#### PERFORMANCE:

IMPEDANCE: 50 OHMS

FREQ. RANGE: DC TO 18.0 GHz

VSWR:

1.01+.01F (GHz) DC TO 18.0 GHz OR APPROXIMATELY 80% OF THE UPPER **CUTOFF FREQUENCY OF THE CABLE** 

WHICHEVER IS LOWER.

1000 VRMS. DWV:

**INSUL. RESISTANCE:** 5000 MEGOHMS

MATERIAL:	SEE NOTES		
FINISH:	SEE NOTES		
SURFACE AR	rea: <b>N/A</b>		
PROPRIETARY			
IS THE SOLE F ANY REPRODI WITHOUT THE	TION CONTAINED IN THIS DRAWII PROPERTY OF SV MICROWAVE, IN JUCTION IN PART OR AS A WHOLE WRITTEN PERMISSION OF /E, INC IS PROHIBITED.		

DIMENSIONS ARE IN INCHES TOLERANCES:
FRACTIONAL: ±1/64 ANGULAR: X° ±1°0' X°X' +15'
DECIMAL: .X ±.030 .XX ±.010 .XXX ±.005
INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994

THIRD ANGLE PROJECTION

1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES. 005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SUFFACE ROUGHNESS 63.MIL-STD-10. 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN 2005 T.I.R. 7) REMOVE ALL BURRS.				
DRAWN:	PJS	03/29/11		
CHECKED:	PJS	03/29/11		

PJS 03/29/11

APPROVED:

UNLESS OTHERWISE SPECIFIED

### SV Microwave, Inc.

2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409

TITLE: SMA R/A PLUG SOLDER-ON FOR .141 SR CABLE

	SIZE <b>B</b>	95077	DWG. NO.	M39012/8	0-3108
Ī	SCALE: 4:1				SHEET 1 OF 1

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Mil Spec Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

M55339/38-00001 M39012/69-0004 M39012/95-0001 M39012/56B3112 M3933/25-88N M39012/55-3125 UG-23D/U(40) UG-306/U(40) UG-492/U SMA6251A1-3GT50G-50B SMA1111A1-3GT50G-1-50 M39012/28-0010 M39012/55B3022 M39012/26-0018 M39012/26-0022 M39012/26-0101 M39012/26-0225 SMA1111A2-3GT50G-5-50 SMA1112A5-3GT50G-5-50 SMA1112A6-3GT50G-1-50 M39012/79-3108 M39012/79B3001 M39012/80-3107 M39012/55-3030 M39012/56-3126 M55339/02-30001 M55339/28-30001 M55339/28-30002 M55339/29-30001 M55339/31-30001 SMA2071A1-3GT50G-50 1102-0003 M39012/26-0011 M39012/26-0012 M39012/26B0006 M39012/26B0015 M39012/28-0022 M39012/30-0101 M39012/31-0002 M39012/33-0001 M39012/39-0501 M39012/55-3006 M39012/55-3008 M39012/55-3008 M39012/55-3008 M39012/55-3008 M39012/55-3008