






		REVISIONS			
REV	ECO	DESCRIPTION	ESCRIPTION DATE		APPR
B1	-	RELEASE NEW DWG FORMAT	Feb.06,2014	Tod	Tommy
B2	-	UPDATE THE DURABILITY	Jun.27,2015	Drack	Tommy
В3	-	UPDATED	04DEC15	MRF	Tommy
B4	-	UPDATED LOGO	20APR16	MRF	Tommy






































MA1CAF1700	
=1 ²⁰ °,	





















- MA1CAS1900		M23, PLUG, ST, 19POS, P TYPE, KEYED "S"	27	M23,
-	MA1CAR1900	M23, PLUG, ST, 19POS, P TYPE, KEYED "R"	26	PLUG,
-	MA1CAP1900	M23, PLUG, ST, 19POS, P TYPE	25	3, S1
-	MA1CAG1900	M23, PLUG, ST, 19POS, E TYPE, KEYED "G"	24	RAIC
-	MA1CAF1900	M23, PLUG, ST, 19POS, E TYPE, KEYED "F"	23	<u>,</u> 当
-	MA1CAE1900	M23, PLUG, ST, 19POS, E TYPE	22	, STRAIGHT, THREADED
			21	EAD
-	MA1CAS1700	M23, PLUG, ST, 17POS, P TYPE, KEYED "S"	20	Ü
-	MA1CAR1700	M23, PLUG, ST, 17POS, P TYPE, KEYED "R"	19	
-	MA1CAP1700	M23, PLUG, ST, 17POS, P TYPE	18	
-	MA1CAG1700	M23, PLUG, ST, 17POS, E TYPE, KEYED "G"	17	
-	MA1CAF1700	M23, PLUG, ST, 17POS, E TYPE, KEYED "F"	16	DV
-	MA1CAE1700	M23, PLUG, ST, 17POS, E TYPE	15	DWG NO
			14	Ö
-	MA1CAS1600	M23, PLUG, ST, 16POS, P TYPE, KEYED "S"	13	
-	MA1CAR1600 M23, PLUG, ST, 16POS, P TYPE, KEYED "R"		12	ĭ.
-	MA1CAP1600	M23, PLUG, ST, 16POS, P TYPE	11	MA1CAxxx00
- MA1CAG1600		M23, PLUG, ST, 16POS, E TYPE, KEYED "G"		
-	MA1CAF1600	M23, PLUG, ST, 16POS, E TYPE, KEYED "F"	9	ê
-	MA1CAE1600	M23, PLUG, ST, 16POS, E TYPE	8	
			7	77
-	MA1CAS1200	M23, PLUG, ST, 12POS, P TYPE, KEYED "S"	6	REV:
-	MA1CAR1200	M23, PLUG, ST, 12POS, P TYPE, KEYED "R"	5	翌
-	MA1CAP1200	M23, PLUG, ST, 12POS, P TYPE	4	완
-	MA1CAG1200	M23, PLUG, ST, 12POS, E TYPE, KEYED "G"	3	
-	MA1CAF1200	M23, PLUG, ST, 12POS, E TYPE, KEYED "F"		
-	MA1CAE1200	M23, PLUG, ST, 12POS, E TYPE	1	유
QUANTITY	PART NUMBER	DESCRIPTION	ITEM	_
				1

MATERIALS LIST UNLESS OTHERWISE SPECIFIED SIGNATURES DATE 1) All dimensions are in metric(mm) Drack Jun.27,2015 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 3) Note reference = XMATERIAL SPECIFICATIONS: CUSTOMER: THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, PROCESS SPECIFICATIONS: SPECIFICATIONS AND PERFORMANCE DATA SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. NEXT ASS'Y:

Amphenol

Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036

M23, PLUG, STRAIGHT, THREADED

١	SIZE	TYPE	DWG NO:				REVISION
3	В	C-	MA1CAxxx00				B4
	SCALE: N	ONE	C-MA1CAxxx00	SHEET	1	OF	1

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

INSULATION INSERT: PA66,UL94 V0

HOUSING BODY: ZINC DIE CAST, NICKEL PLATED COUPLING NUT: COPPER ALLOY, NICKEL PLATED

2. SPECIFICATIONS:

2.1 CURRENT RATING: 10 AMPS - 12 POSITION

9 AMPS - 16 POSITION 9 AMPS - 17 POSITION 7 AMPS - 19 POSITION

2.2 VOLTAGE RATING: 160V AC/DC - 12 POSITION 125V AC/DC - 16 POSITION

125V AC/DC - 17 POSITION 63V AC/DC - 19 POSITION

2.3 OPERATING TEMPERATURE: -20°C TO +130°C 2.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2

MILLIAMPS CURRENT LEAKAGE @ 2500 VOLTS AC. 2.5 DEGREE OF PROTECTION: IP67 (MATED CONDITION)

2.6 DEGREE OF POLLUTION: 3 PER UL840 2.7 OVERVOLTAGE CATEGORY: III PER UL840

2.8 MATING CYCLE DURABILITY: >500 CYCLES 2.9 RoHS COMPLIANT

3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 1-3637-600-5205 1612618 21036836414 8R4006A16M010 1R3006A20M005 41-40011 42-00006 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01203 41-40013 42-00008 43-00343 43-01026 43-01162 43-01173 43-10000 XS3P-M421-2 600X518050X 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-16213 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004 860RD04-113R004 860RD04-213R004 1-213245-2