Item

Part number

Cable OD Range


7.5~11.0 mm 11.0~15.0 mm


4.5~7.5 mm


ယ N

MA5CAP1200-S3 MA5CAP1200-S2 MA5CAP1200-S1









	Ø28.0						
69.50 REF.	To Composition of the control of the						

2	REV	
-	ECO	
FIRST RELEASE	DESCRIPTION	REVISIONS
Sep.07,2015	DATE	
Drack	ВҮ	
Tommy	APPR	

## NOTES: UNLESS OTHERWISE SPECIFIED

ymphenol X

MA5CAP1200-Sx XXXX

1. MATERIAL:
INSULATION INSERT: PA66,UL94 V0
SEAL: VITON, EPDM
HOUSING BODY: ZINC DIE CAST, NICKEL PLATED
COUPLING NUT: ZINC DIE CAST, NICKEL PLATED

Ņ

2. SPECIFICATIONS:
2.1 CURRENT RATING: 10 AMPS
2.2 VOLTAGE RATING: 180 V AC/DC
2.3 OPERATING TEMPERATURE: -20°C TO +130°C
2.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2
MILLIAMPS CURRENT LEAKAGE @ 2500 VOLTS AC.
2.5 DEGREE OF PROTECTION: IP87 (MATED CONDITION)
2.6 DEGREE OF POLLUTION: 3 PER UL840
2.7 OVERVOLTAGE CATEGORY: III PER UL840
2.8 MATING CYCLE DURABILITY: >500 CYCLES 2.9 RoHS COMPLIANT

3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

NEXT ASSY:	TRACESS STEATHER INVESTIGATION	Volence asserting		MATERIAL SPECIFICATIONS:		3) Note reference = X	2 PL DEC ±0.16	2) Tolerances are as follows:	UNLESS OTHER		QUANTITY	
THOMS:						atric(mm). s: lone ±1/64 s ±1*		UNLESS OTHERWISE SPECIFIED		PART NUMBER	SEE TAX NOMBEX CHAX	
MANUFACTURING VARIATIONS	SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLED. ALL DIMENSIONS ARE SUBJECT TO NORMAL	THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES	CUSTOMER:		APPROVAL:	ENGINEER:	CHECKED:	DRAWN: Drack	SIGNATURES	Σ	UMBER	
MUATIONS.	D PERFORMAN E THE PROPER PORATION, NO ARE IMPLED, A BJECT TO NOR	PPLIED FOR DESIGN FEAT								MATERIALS LIST		_
		THE S						Sep.07,2015	DATE	핃		
<b>BNON</b> E	B		<u>N</u>							ア [な		
ONE	ا ا		3A,PL		S.		$\triangleright$		<u>.</u>	묘		
HEET 1 OF	MA5CAP1200-Sx		M23A,PLUG,STR,12P,P TYPE, CHECKMATE		Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036		Amphenol		IST	DESCRIPTION		
-	AS A SAN		Ħ								Ð	

I :HS IA:VER WYECAP1200-Sx l :so DMG NO: M23A,PLUG,STR,12P,P TYPE, CHECKINATE элт

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 1-3637-600-5205 1612618 21036836414 8R4006A16M010 1R3006A20M005 41-40011 42-00006 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01203 41-40013 42-00008 43-00343 43-01026 43-01162 43-01173 43-10000 XS3P-M421-2 600X518050X 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-16213 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004 860RD04-113R004 860RD04-213R004 1-213245-2