

ltem

Part number


Cable OD Range


11.0~14.5 mm 7.5~11.0 mm


14 5~17 0 mm

ယ N

MB5CKN0800-S3 MB5CKN0800-S2 MB5CKN0800-S1







-	
_	
9	
TES.	
S	
_	
∍	
=	
m	
LESS	
0,	
Q	
쿠	
市	
70	
≤	
7	
ĸ	
m	
SPE	
ΞĎ.	
<u></u>	
⊐	
⊞	

REV <u>2</u> 2

ECO

UPDATED COUPLING NUT FIRST RELEASE DESCRIPTION REVISIONS

Sep.07,2015 Drack Oct.26,2015 Drack DATE

Tommy Tommy APPR

ВΥ

MATERIAL: INSULATION INSERT:PA66,UL94 V0 SEAL: VITON, EPDM HOUSING BODY: ZINC DIE CAST, NICKEL PLATED COUPLING NUT: ZINC DIE CAST, NICKEL PLATED

2. SPECIFICATIONS:
2.1 CURRENT RATING: SIGNAL: 10 AMPS
POWER: 30AMPS

2.2 VOLTAGE RATING: SIGNAL: 250V AC/DC POWER: 630V AC/DC

2.3 OPERATING TEMPERATURE: -20°C TO +130°C
2.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2
MILLIAMPS CURRENT LEAKAGE @ SIGNAL: 2500VOLTS AC.
POWER: 6000 VOLTS AC.

2.5 DEGREE OF PROTECTION: IP67 (MATED CONDITION)
2.6 DEGREE OF POLLUTION: 3 PER UL840
2.7 OVERVOLTAGE CATEGORY: III PER UL840
2.8 MATING CYCLE DURABILITY: >500 CYCLES
2.9 ROHS COMPLIANT

ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

PROCESS SPECIFICATIONS: NEXT ASS'Y:		MATERIAL SPECIFICATIONS:		3) Note reference = X		UNILESS OTHERWISE SPECIFIED 1) All dimensions are in metrc(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/84 3 PL DEC ±0.08 Angles ±1*			QUANTITY			
-			CUSTOMER	SNO			_	ns +1/64	VISE SPECIFIED		PART NUMBER	SEE PART NUMBER CHART
MANUFACTURING VARIATION	THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SIZE SHOWN HEREON ARE THE PROJECTY OF THE MARCHAND LOCK ORD CANTON, NO RIGHTS TO THE MARCHAND LOCK ORD CANTON, NO RIGHTS TO THE MARCHAND LOCK ORD CANTON				APPROVAL:	ENGINEER:	CHECKED:	Drawn: Drack	SIGNATURES	MA.	JMBER	MBER CHART
	FORMANCE DATA PROPERTY OF VITON, NO RIGHTS MPLIED, ALL T TO NORMAL	D FOR GN FEATURES,						Oct.26,2015	S DATE	TERI		
SCALE: NONE	B C-		M23B,PL				Sir	1	>	MATERIALS LIST	묘	
	MB5CKN0800-Sx	- _			CIIII CONTAIND, INI 40000	44724 Morley Drive	Sine Systems - www.amphenol-sine.com			ST	DESCRIPTION	
SHEET 1 OF)800-Sx		+4),CHECKMA		10000	95036	enol-sine.com))			
1	A2		Ħ								TEM	

OF ке∨: А2 sн: 1 WB2CKM0800-2X M23B,PLUG,STR,8POS(4+4),CHECKMATE DMG NO: :BJTIT

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 1-3637-600-5205 1612618 21036836414 8R4006A16M010 1R3006A20M005 41-40011 42-00006 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01203 41-40013 42-00008 43-00343 43-01026 43-01162 43-01173 43-10000 XS3P-M421-2 600X518050X 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-16213 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004 860RD04-113R004 860RD04-213R004 1-213245-2