

PCIe® M.2 Gen 5 Card Edge Connectors

HIGH DENSITY HIGH PERFORMANCE CONNECTOR

Amphenol's PCIe® M.2 Gen 5 Connectors provide 67 contacts on 0.50mm pitch. It occupies less board space, offers more connector height options and supports higher data rates compared to PCIe® Mini Card connector. It is designed for PCIe® Gen 5, making it suitable for tablets, laptops and low profile storage and server applications. PCIe® M.2 connectors also support higher data rate transmission with both single and double-sided modules.

- Various connector height and keying options
- Accepts angled insertion of add-in module cards
- The product support angled insertion
- Provides both right angle and vertical orientation for M.2 Connectors. Right angle option is available, the design of vertical option is ongoing



TARGET MARKETS



FEATURES

- Card edge connector with 67 contacts on a 0.50mm pitch
- 75 positions with 8 connector key options
- Available in various connector heights
- Supports both single and double-sided modules
- Upgradable to Gen 5 (32Gb/s)
- Provides both right-angle and vertical orientations

BENEFITS

- Fully compliant with PCI-SIG PCIe® M.2 specification
- Design flexibility
- Options to reduce overall height
- Enables higher data rates
- Supports higher speeds with backward compatibility to Gen 3 and Gen 4
- Allows for application flexibility

TECHNICAL INFORMATION

MATERIAL

- Contact: Copper Alloy with Gold plating sufficient to meet all mechanical and environmental requirements
- Contact Finish: Must be compatible with Lead-free soldering process
- Housing: Complies with UL 94 V-0. Must be compatible with Lead-free soldering process

ELECTRICAL PERFORMANCE

- Low Level Contact Resistance: EIA-364-23, 55mΩ max. (initial) per contact, *20mΩ max. change allowed
- Insulation Resistance: EIA-364-21, * $>5 \times 108\Omega$ at 500V DC
- Dielectric Withstanding Voltage: EIA-364-20, * $>300\text{VAC}$ (RMS) at sea level
- Current Rating: *0.75A/Power contact (continuous), * The temperature rise above ambient shall not exceed 30°C, * The ambient condition is still air at 25°C, * EIA-364-70 Method 2
- Voltage Rating: 50VAC per contact

MECHANICAL PERFORMANCE

- Durability:
 - Normal M.2: 25-60 mating cycles

ENVIRONMENTAL

- Durability: EIA-364-9; *Option 1 – 25 Cycles, *Option 2 – 60 Cycles, Upon completion of cycles the sample must meet all visual and electrical performance requirements
- Insertion Force: 20N (2.04KgF, 1 Newton = 1Kg* m/s²) max., EIA-364-13, Method A
- Shock: * 250G (notebook) and 285G (tablet), *at 2ms half sine, *on all six (6) axis
- Vibration: EIA-364-1000 Test group 3, EIA-364-28
- Operating Temperature Range: -40°C to +80°C
- Environmental Test Methodology: EIA-364-1000 Test group 1, 2, 3, 4
- Useful Field Life: Three (3) years

SPECIFICATIONS

- Amphenol Product Specification:
 - GS-12-1142
 - GS-12-1195
 - GS-12-1248

PACKAGING

- Tape & Reel

TOOLING INFORMATION

- Tooled Up

TARGET MARKETS/APPLICATIONS



Wireless



Laptop
Tablet



Storage



Industrial PC

PART NUMBERS

Description	Height (mm)	Data rate	Orientation	Key Options	Part Numbers
M.2 Gen 5	4.2	32Gb/s	Right Angle	M	MDT420M0X501
M.2 Gen 5	6.7	32Gb/s	Right Angle	M	MDT670M0X501
M.2 Gen 5	8.5	32Gb/s	Right Angle	M	MDT850M0X501
M.2 Gen 5	3.2	32Gb/s	Right Angle	M	MDT320M01501

SS10PC1EM2G50923EA4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [PCI Express/PCI Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[PCIEEXT16HOT](#) [UEX220-6U](#) [10025026-10003PLF](#) [10125756-980000LF](#) [GPCP442628110HR](#) [GPCP245400111HR](#) [10082378-10000TLF](#)
[MDT580M03001](#) [MPE-D-52-R-SMT-9.2-TR](#) [2041216-1](#) [MDT580M01001](#) [10141523-111T0LF](#) [10146070-112Y0LF](#) [10150657-052R0LF](#)
[1759513-1](#) [10082378-10213TLF](#) [10123920-A20LF](#) [10124928-001LF](#) [10125101-A15RLF](#) [10125101-A30RLF](#) [10125756-642010LF](#)
[10125756-A42010LF](#) [1612257-7](#) [1-1612257-2](#) [10125756-A40010LF](#) [10151114-001TLF](#) [SM3ZS067U215AMR1500](#) [10146070-113X0LF](#)
[MDT320M01004](#) [MDT580M01003](#) [10146070-123X0LF](#) [MDT420STD001](#) [10146070-113B0LF](#) [10146069112X0LF](#) [1-1734774-2](#) [63010](#)
[74540-0201](#) [74540-0501](#) [7-1734774-7](#) [3-1761465-1](#) [10039755-10111TLF](#) [10039755-10112TLF](#) [10018783-10211TLF](#) [10018784-10212TLF](#)
[1761465-2](#) [87715-9202](#) [87715-9208](#) [1871058-1](#) [5-1761465-4](#) [10018783-10200MLF](#)