


Circuito	Dimension		Circuito	Dimension	
Circuits	Α	В	Circuits	Α	В
2	6.7		14	24.7	18.0
4	9.7	3.0	16	27.7	21.0
6	12.7	6.0	18	30.7	24.0
8	15.7	9.0	20	33.7	27.0
10	18.7	12.0	22	36.7	30.0
12	21.7	15.0	24	39.7	33.0



Specifications:

Current Rating:5.0A AC/DC Voltage Rating:250V AC/DC


Contact Resistance:10m ohm. Max. Insulation Resistance:1,000M ohm. Min.


Withstanding Voltage:1,500V AC For One Minute Operating Temperature Range:−25°C ~ +105°C

Material and Finish

Insulator:High Temp. Plastic (Nylon 46 UL94V-0)

Insulator Color:Black Contact:Copper Alloy Plated:Tin Plated







TOLERANCE (mm)		NCE (mm)	APPROVALS	DATE	TITLE	
	X.	±0.3	Stephane	08/Oct/2007		3.0 Power Connector
	x.x	±0.2	Rob	08/Oct/2007		R/A SMT w/Ear
	x.xx	±0.15	APPROVED Rob	08/Oct/2007]	

A4

AMPHENOL
Amphenol European
Design Center

Scale N.A. Sheet 1 of 1

MF30-SHE1-XX

HE1-XX

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

571763P 58098-0628 61-168618-12P D38999/20FJ29SB L/C 72.250.1628.2 72.250.2428.2 74720-0505 747680210 76.350.0729.0 768711403 FCN-244F080-G/1 FCN-260A9920 FCN-268D024-G/2F#10X-R10 MP-5T180MUNNA-005 MP-5XRJ45UNNB-003 PCS-E50FA
PCS-XE26LKA PCS-XE26MA+ PCS-XES68MS+ G38A71314B 91-569719-35R 9776-18-6 DX40-50P(55) 1571250010 157-22500-3
MS3471L14-19P L/C 171224-6031 1888020-8 91-569786-35H 91-569786-35M 91-644626-35P 172501-4002 172501-6002 FCN-260C008A/L0 FCN-260C024-AL0 FCN-261Z008 FCN-268D008-G/1K 2000314-1 200331-1 2007498-2 PCR-E28LMDAG1+ PCR-E36FC+ PCSE28FS+ PCS-XE26SLFD+ PCS-XE26SLFDT+ G38A71214B HDRA-E68W1LFDTC-SL+ HDR-E14MSG1+ R88A-CNK81S CRT1ATT02