



RECOMMENDED PCB LAYOUT

DIMENSION

A	(N-1)×3.5+4.90	⚠
B	(N-1)×3.5	

N= NUMBER OF CONCATS

Poles	Tolerance
2P-6P	±0.15
7P-12P	±0.20
13P-18P	±0.25
19P-24P	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
⚠	10/20'05	Dim changed from 3.8 to 3.5	Marvin
⚠	04/20'06	Added feature	Marvin
⚠	8/16'06	Added VDE standard	Steady
⚠	1/11'07	Soldering temperature changed from 245° to 250°	Tony
⚠	5/27'08	Operating temperature is changed	Marvin
⚠	3/17'09	The dimensions is changed from 2.3mm to 2.5mm	Jacke
⚠	2009.08.18	The material is changed	Jacke
⚠	2011.03.16	The dimensions is changed from 2.5mm to 2.45mm	Aaron
⚠	2012.05.14	Voltage rating is changed	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- ⚠ Item ⓐ Male contact pin: Copper Tin plated
- Item ⓑ Terminalhousing: Thermoplastic (UL94V-0)

- ⚠ Electrical: cULus /VDE
- ⚠ ● Voltage rating: 300V/300V
- Current rating: 10A/10.5A
- Withstanding Voltage: 1.6 KV/2.5KV
- ⚠ ● Operating temperature: -40°C to +115°C
- ⚠ ● Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval: cULus VDE
- Critical dimension: ⚠

OQ xx 1 2 x 1 xxxx G

- No. OF POLES: 02: 2 POLES; 24: 24 POLES
- Color: 0 Black (RAL9005); 2 Red (RAL3001/D); 3 Orange(RAL2011/P); 4 Yellow(RAL1018/A); 5 Green(RAL6018/T); 6 Blue (RAL5015/A); 8 Grey(RAL7035/D)
- G: RoHS compliant (lead<4%) In copper Alloy
- 0000: "@ " Logo
- 000A: "ANYTEK" Logo
- Any special item by customer request. please contact sales department.

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE	OQ 3.5mm Series 90° (2P-24P) Triangle Key Lock						
PART NO.	OQxx12x1xxxxG			DWG NO.	80Q.04.02		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Chen Bo 05/14'12	Chen Bo 05/14'12		X. ±0.50		
					UNIT: mm		X.X ±0.30
					SCALE: NONE		X.XX ±0.10
				SHEET: 01/01	REV.: L		X° ±1°

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [721-104/026-047](#) [721-204/026-045](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [860505](#) [860516](#) [860810](#) [GBPACX-12](#)
[93.731.4953.0](#) [PVP03-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFP03110](#) [ELFP10210](#) [ELFT07250](#)
[ELVD12100](#) [ELVF09400](#) [ELXH071G0E](#) [1725220000](#) [1760336](#) [1855000000](#) [19346](#) [1946309](#) [1973592](#) [19892](#) [25.320.4053.1](#) [25.320.4553.9](#)
[25.320.4753.1](#) [25.320.5453.1](#) [25.340.0353.1](#) [25.340.1053.1](#) [25.345.3553.0M001](#) [25.640.3553.1](#) [SH02-5,08](#) [SH06-3,81](#) [SH08-5,08](#) [SH08-](#)
[5,08-K](#) [SH12-5,08](#) [SHS04-5,00](#) [30.303](#) [30.305](#) [30.306](#) [PHP09-5,08](#) [25.193.0453.0](#) [25.320.4653.1](#) [25.332.2453.1](#)