



DIMENSION

| | |
|---|----------------|
| A | (N-1)×3.81+5.0 |
| B | (N-1)×3.81 |

N= number of poles

| Poles | Tolerance |
|---------|-----------|
| 2P-6P | ±0.15 |
| 7P-12P | ±0.20 |
| 13P-18P | ±0.25 |
| 19P-24P | ±0.30 |

| SIGN | DATE | DESCRIPTION | APPROVER |
|------|------------|---|----------|
| △ | 04/20'06 | Added feature | Marvin |
| △ | 8/16'06 | Added VDE standard | Steady |
| △ | 1/12'07 | Soldering temperature changed from 245° to 250° | Tony |
| △ | 5/27'08 | Operating temperature is changed | Marvin |
| △ | 2009.08.18 | The material is changed | Jacke |
| △ | 2010.07.07 | Remove the CSA mark | Chen Bo |
| △ | 2010.12.21 | Dim changed from 2.6 to 2.5 | Runner |
| △ | 2012.05.22 | Voltage rating is changed | Chen Bo |

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item ⑤ Male contact pin: Copper Tin plated
- Item ⑥ Terminalhousing): Thermoplastic (UL94 V-0)

- Electrical: cULus /VDE
- Voltage rating: 300V/300V
 - Current rating: 10A/10.5A
 - Withstanding Voltage: 1.6 KV/2.5KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 250°C±10°C/5 Sec
 - Safety Approval:
 - Critical dimension: ▽

OQ xx 3 2 x 0 xxxx G

- No. OF POLES: 02: 2 POLES; 24: 24 POLES
- Color: 0 Black (RAL9005); 2 Red (RAL3001/D); 3 Orange(RAL2011/P); 4 Yellow(RAL1018/A); 5 Green(RAL6018/T); 6 Blue (RAL5015/A); 8 Grey(RAL7035/D)
- G RoHS compliant (lead<4%) In copper Alloy
- 0000: "@ " Logo
- 000A: "ANYTEK" Logo
- Any special item by customer request. please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

| | | | | | | | |
|--------------|--|---------------------|---------------------|-----------|-------------|---------|-------|
| TITLE | OQ 3.81mm Series 180° (2P-24P) Triangle Key Lock | | | | DWG NO. | 80Q0601 | |
| PART NO. | OQxx32x0xxxxG | | | CUST NO. | | | |
| APPROVED | CHECKED | DESIGNED | DRAWN | Tolerance | | | |
| | | Chen Bo 05/22'12 | Chen Bo 05/14'12 | | UNIT: mm | X. | ±0.50 |
| | | | | | SCALE: NONE | X.X | ±0.30 |
| SHEET: 01/01 | | | | | REV.: M | X.XX | ±0.10 |
| | | | | | | X° | ±1° |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[57.404.7553](#) [57.504.0053.7](#) [57.510.0053](#) [57.910.6153](#) [01.112.1453](#) [CTB932VE/6](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [734-304](#) [8-141-P](#) [FKCT 2.5/ 3-ST KMGY](#) [860505](#) [860508](#) [860516](#) [860810](#) [861908](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP02-5,00](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [H-10](#) [1546228-5](#) [ELFP03110](#) [ELVP03100](#) [ELXH03100](#) [ELXP041G0](#) [ELXT046G0](#) [1700101](#) [1700410](#) [1703243](#) [1703634](#) [1705229](#) [1710175](#) [1714537](#) [1717806](#) [1719600](#) [1728941](#) [1729386](#) [1734692](#) [1734795](#) [1736036](#) [1740194](#) [1740291](#) [1740628](#) [1740990](#)