



RECOMMENDED PCB LAYOUT

N = Number of poles
 Dim A = (N x 5.08) + 2.0
 Dim B = (N - 1) x 5.08 (A)

	Dim A	Dim B
2-6p	±0.15	±0.15
7-12p	±0.25	±0.25
13-18p	±0.30	±0.30
19-24p	±0.40	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
(A)	8/16'06	Added VDE and TUV standard	Steady
(A)	8/16'06	Current rating (cULus) changed from 10A to 20A	Steady
(A)	1/20'07	Dimension changed from 4.0 to 3.5	Tony
(A)	1/20'07	Soldering temperature changed from 245° to 250°	Tony
(A)	2009.10.21	The material is changed from Brass to Copper	Jacke
(A)	2009.10.21	The operating temperature is changed	Jacke
(A)	2009.10.21	Remove the CSA certification	Jacke
(A)	2010.03.23	The design is changed	Jacke

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- (A) (B) Item (C) Male contact pin: Copper Tin plated
- (B) Item (D) Terminal(housing): Thermoplastic (UL94V-0)

- (A) (A) Electrical: cULus /VDE /TUV
- (B) Voltage rating: 300V/300V/300V
- (A) Current rating: 20A/20A/20A
- (B) Withstanding Voltage: 1.6 KV/2.5KV/2.5KV
- (A) Operating temperature: -40°C to +115°C
- (A) Soldering temperature: 250°C ± 10°C / 5 Sec
- (B) Safety Approval:

OQ xx 5 4 x 1 xxxx G

No. OF POLES
 02: 2 POLES
 :
 24: 24 POLES

COLOR
 0 Black (RAL9005)
 2 Red (RAL3001/D)
 3 Orange(RAL2011/P)
 4 Yellow(RAL1018/A)
 5 Green(RAL6018/T)
 6 Blue (RAL5015/A)
 8 Grey(RAL7035/D)

G: Pb<40000ppm
 0000: "@" Logo (Standard)
 000A: "ANYTEK" Mark
 Any special item by customer request. please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		QO 5.08mm 90° /Close Series 2p-24p		DWG NO.		80Q0704		
PART NO.		OQxx54x1xxxxG		DWG NO.		80Q0704		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance		
		Jacke	Jacke			UNIT: mm		
		2010.03.23	2009.10.21			SCALE: NONE		X.
SHEET: 01/01				REV: I		X.X		±0.30
						X.XX		±0.10
						X°		±1°

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[57.404.7553](#) [57.504.0053.7](#) [57.510.0053](#) [57.910.6153](#) [01.112.1453](#) [CTB932VE/6](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [734-304](#) [8-141-P](#) [FKCT 2.5/ 3-ST KMGY](#) [860505](#) [860508](#) [860516](#) [860810](#) [861908](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP02-5,00](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [H-10](#) [1546228-5](#) [ELFP03110](#) [ELVP03100](#) [ELXH03100](#) [ELXP041G0](#) [ELXT046G0](#) [1700101](#) [1700410](#) [1700425](#) [1703176](#) [1703243](#) [1705229](#) [1710175](#) [1714537](#) [1717806](#) [1719600](#) [1728941](#) [1729386](#) [1734692](#) [1734795](#) [1736036](#) [1740194](#) [1740291](#) [1740628](#)