

Power Series 50A / 50A+2A

For Your High Power and Data Transmission



Key Features

- ✓ Robust, High Density Terminal Design (Crown Spring Terminal)
- ✓ Current Rating Up To 50A
- ✓ Hybrid Type
- ✓ AC / DC Applications
- ✓ UL 94V-0 Rated Material
- ✓ UV Resistant
- ✓ 3 Points Lock Bayonet Mating Style



Harsh Environment



UV Resistant



IP67 Mated



UL 94V-0

Male Conn. Female Pin			Female Conn. Male Pin		
2 Pin	4 Pin (2+2)	6 Pin (2+4)	2 Pin	4 Pin (2+2)	6 Pin (2+4)

Application



Electric Bikes



Lighting Systems



Industrial Automation







Broadband Wireless Access





Specification

General Characteristics

Current Rating	Power: 50A Signal: 2A	Plastic Material	UL94V-0, UL746C f1 UL Recognized
Voltage Rating	Power: 600V AC/DC Signal: 30V AC/DC	Operation Temperature	-40°C ~ 105°C
Waterproof Rating	Receptacle: IP67 (Mated) Field Installable: IP67 (Mated)	Contact Resistant	Less than 10mΩ.
Recommended Gauge	Power: 8 AWG Signal: 20 ~ 22 AWG	Locking Mechanism	3 Points Lock Bayonet
Durability	1,000 Cycles		

Ordering Information

Connector Type	Receptacle (Solder Type)		
Product Image			
Contacts	Power Pin	Power + Signal Pin	
	02	04 (2+2)	06 (2+4)
			
Part Number	PWM-02RMFS-TS7001	PWMU-04RMFS-TS7001 PWMU-06RMFS-TS7001	

Connector Type	Field Installable (Screw-in Type)		
Product Image			
Contacts	Power Pin	Power + Signal Pin	
	02	04 (2+2)	06 (2+4)
			
Part Number	PWM-02BFMB-TL7001	PWMU-04BFMB-TL7001 PWMU-06BFMB-TL7001	

Luc Kan | Sales & Marketing | Email: luc@ltw-tech.com

Follow Us On

Find out more
new product here



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Standard Circular Connector](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[5M2530B10P](#) [600259N006](#) [600273N007](#) [6134-336-13149](#) [6134-337-11149](#) [6134-337-2390](#) [6134-341-17149](#) [6280-4SG-516](#) [6280-7SG-3DC](#)
[6290](#) [6291A](#) [66200A-10](#) [680-SMG](#) [681-PMG](#) [CXS3102A14S2P](#) [CXS3102A181S](#) [7251-6SG-300](#) [7271-6SG-300](#) [7282-3PG-300-CH3](#) [75-](#)
[474014-05S](#) [75-474618-01S](#) [75-474618-04S](#) [799539-000](#) [MI8-SE](#) [805-005-07NF11-19PC](#) [805-005-07NF15-7PA](#) [8280-4PG-516](#) [8280-7PG-](#)
[519](#) [8282-5PG-519](#) [836783-1](#) [MP-4102-25P-C](#) [862256-1](#) [864019-2](#) [866857-1](#) [867865-1](#) [PT01SP-14-18P](#) [PT08P-14-5S](#) [PTSF06SE-14-12S](#)
[120-1833-000](#) [QCM019PC2DC012B](#) [1-2069279-1](#) [121583-0217](#) [121667-0020](#) [129591AU](#) [1000B BULK](#) [RD10A16-19-P6CS051/1](#)
[RD10A20-31-P8CS051/1](#) [RD16A14-12-S6CS051/2](#) [1301240290](#) [1301240347](#) [1301860202](#)