

## RJ Connectors

1 - 2 3 4 5 6 - 7 8 9

### Specification

**(RCP)** RJ45 C Size (Plastic)  
**(RCM)** RJ45 C Size (Metal)  
**(RDP)** RJ45 D Size (Plastic)  
**(RDM)** RJ45 D Size (Metal)  
**(ROP)** RJ45 ODVA (Plastic)

### Cat Type & Shielded

**(00)** None **(5S)** Cat.5e shielded  
**(5U)** Cat.5e Unshielded

### Connector Body (Style)

> For Receptacle > For Overmolded with Cable  
**(P)** Front Fastened **(A)** With Strain Relief  
**(R)** Rear Fastened **(B)** Without Strain Relief  
**(D)** Dual Fastened  
  
 > For Field Installable  
**(A)** With Strain Relief  
**(B)** Without Strain Relief

### Connector (Housing) Gender

**(MM)** Plug **(FF)** Jack

### Assemble Style

> For Receptacle > For Overmolded with Cable  
**(H)** Jack 180 (Horizontal) **(M)** Overmolded with Cable  
**(V)** Jack 90 (Vertical)  
  
 > For Field Installable  
**(A)** Field installable (Compled)  
**(S)** Field installable (Feed-Thru)

### Mating Style

**(T)** 3 Points Lock Bayonet **(S)** Screw Thread

### Backshell

> For Receptacle > For Overmolded with Cable > For Field Installable  
**(C)** Circular **(L)** Straight **(L)** Straight  
**(S)** Square **(R)** Right Angle

### Waterproof Types

**(U)** Unmated Waterproof **(M)** Mated Waterproof

### Waterproof Rating

**(7)** IP 67 \*IP 68 upon request.

### More information

> For Receptacle > For Overmolded with Cable  
**(001), (002).....** (□)+(■) : Cable Type + Cable Length  
  
 (□) : Cable Type (■) : Cable Length  
**(A)** C5e UTP Solid Cable From 1M to 99M  
**(B)** C5e FTP Solid Cable EX. **(01)** = 1M

**RJ Connector:** Overmolded with Cable (Double-ended)  
Waterproof to Waterproof / Non-Waterproof

**Specification (1st End)**

- (RCP) RJ45 C Size (Plastic)
- (RCM) RJ45 C Size (Metal)
- (RDP) RJ45 D Size (Plastic)
- (RDM) RJ45 D Size (Metal)
- (ROP) RJ45 ODVA (Plastic)

**Cat Type & Shielded (1st End)**

- (5U) Cat.5e Unshielded
- (5S) Cat.5e Shielded

**Connector (Housing) Gender (1st End)**

- (M) Plug
- (F) Jack

**Specification (2nd End)**

> For Waterproof Connectors

- (RCP) RJ45 C Size (Plastic)
- (RCM) RJ45 C Size (Metal)
- (RDP) RJ45 D Size (Plastic)
- (RDM) RJ45 D Size (Metal)
- (ROP) RJ45 ODVA (Plastic)

> For Non-Waterproof Plug

- (UPG) Unshielded Plug
- (SPG) Shielded Plug

**Cat Type & Shielded (2nd End)**

> For Waterproof Connectors

- (5U) Cat.5e Unshielded
- (5S) Cat.5e Unshielded

> For Non-Waterproof Plug

- (06) Gold Plating 6u"

**Connector (Housing) Gender (2nd End)**

- (M) Plug

**Mating Style**

- (T) 3 Points Lock Bayonet
- (S) Screw Thread

**Backshell**

> For Overmolded with Cable

- (L) Straight
- (R) Right Angle

**More information**

> For Overmolded with Cable

(□)+(■) : Cable Type + Cable Length

(□) : Cable Type      (■) : Cable Length

(A) C5e UTP Solid Cable      From 1M to 99M

(B) C5e FTP Solid Cable      EX. (01) = 1M

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GAX-8-62](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#) [GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [RJ11FTVC2G](#) [RJ11FTVC2N](#) [RJFTVX2SA1G](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#) [AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102288](#) [AX102651](#) [AX102660](#) [AX104024](#) [J0012D21NL](#) [J0026D01ENL](#) [PC4D0018P](#) [8949-B88/6](#) [2-6609208-5](#) [303066VFL](#) [303068V](#) [303088LFLSA](#) [303088SBL](#) [30-8603](#)