




| REVISIONS | | | | | |
|-----------|-----|------------------|-------------|-------|-------|
| REV | ECO | DESCRIPTION | DATE | BY | APPR |
| A1 | - | RELEASED DRAWING | Oct-25-2018 | Blink | Tommy |
| A2 | - | UPDATE DRAWING | Feb-19-2019 | Blink | Tommy |



SEALING PLUGS CAN BE PURCHASED SEPARATELY

NOTES : (UNLESS OTHERWISE SPECIFIED)

- MATERIAL :
 SHELL : THERMOPLASTIC , UL94 V-0.
 INSERT : THERMOPLASTIC , UL94 V-0.
 COUPLING NUT : THERMOPLASTIC , UL94 V-0.
 O-RING : NBR OR SILICONE RUBBER.
 WASHER : SILICONE RUBBER.
 END CAP : THERMOPLASTIC , UL94 V-0.
 PLASTIC RING : THERMOPLASTIC , UL94 V-0.
 WIRE SEAL: SILICONE RUBBER.
- SPECIFICATIONS :
 2.1 RATED CURRENT : 45A (MAX).
 2.2 RATED VOLTAGE : 600V(AC/DC).
 2.3 OPERATING TEMPERATURE : SEE TABLE.
 2.4 DIELECTRIC WITHSTANDING VOLTAGE : LESS THAN 2 MILLIAMPS CURRENT LEAKAGE@2500 VOLTS AC.
 2.5 INSULATION RESISTANCE : 5000 MEGOHMS MIN.
 2.6 IP CLASS : IP67 AND IP69K IN THE MATED CONDITION, WIRE SEALS FULLY POPULATED.
 2.7 MATING CYCLES DURABILITY : 500 CYCLES MIN.
 2.8 RoHS COMPLIANT.

3. SUITABLE CONTACTS : 8# CONTACT.

| CONTACT SIZE | CONTACT PN | WIRE RANGE | Insulation Overall Diameter(min-max) |
|--------------|------------|------------|--------------------------------------|
| 8# | MS10A23x | 12-10AWG | Ø2.8mm - Ø4.1mm |

- IN THE CONTACT PN, "x" DENOTE DIFFERENT PLATING.**
4. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

| KEY | PART NUMBER | |
|-----|----------------|------------------|
| | -40°C ~ 105°C | -40°C ~ 125°C |
| N | RTS6BS14N3SHEC | RTS6BS14N3SHEC03 |

(A2)

| QUANTITY | PART NUMBER | DESCRIPTION | ITEM |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| MATERIALS LIST | | | |
| UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64 2 PL DEC ±0.15 Angles ±1° 3 PL DEC ±0.08 3) Note reference = | | SIGNATURES DATE DRAWN: Blink Feb-19-2019 CHECKED: Tod Feb-19-2019 ENGINEER: APPROVAL: Tommy Feb-19-2019 | |
| MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS: NEXT ASSY: | | CUSTOMER: THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. | |
| | | Amphenol Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036 | |
| | | ECO-MATE, PLUG, END CAP SIZE 14, 3 POS, SOCKET | |
| | | SIZE TYPE DWG NO: B C- RTS6BS14*3SHECxx | REVISION A2 |
| | | SCALE: NONE | SHEET 1 of 1 |

TITLE: ECO-MATE PLUG/END CAP, SIZE 14, 3 POS, SOCKET
 DWG NO.: RTS6BS14*3SHECxx
 REV: A2
 SH: 1
 OF: 1

ecomate® RM/RSSM/Aquarius™ - Contact Size 3.6mm (1403 Insert Arrangement) Options

| Crimp Contacts, 1403 Insert Arrangement, Machined | | | | | |
|---------------------------------------------------|---------------|-------|-------------------------------|------------------|------------|
| Part Number | | AWG | Wire Range (mm ²) | For Use w Endcap | Plating |
| Male | Female | | | | |
| MP10A23T-10 | MS10A23T-10 | 8 | 10.0 | No | Tin |
| MP10A23S-10 | MS10A23S-10 | 8 | 10.0 | No | Silver |
| MP10A23F-10 | MS10A23F-10 | 8 | 10.0 | No | Gold Flash |
| MP10A23G5-10 | MS10A23G5-10 | 8 | 10.0 | No | Gold 5μ" |
| MP10A23G10-10 | MS10A23G10-10 | 8 | 10.0 | No | Gold 10μ" |
| MP10A23G15-10 | MS10A23G15-10 | 8 | 10.0 | No | Gold 15μ" |
| MP10A23G30-10 | MS10A23G30-10 | 8 | 10.0 | No | Gold 30μ" |
| MP10A23S-63 | MS10A23S-63 | 12-10 | 4.0 - 6.0 | No | Silver |
| MP10A23F-63 | MS10A23F-63 | 12-10 | 4.0 - 6.0 | No | Gold Flash |
| MP10A23TL | MS10A23T | 12-10 | 3.0 - 6.0 | Yes | Tin |
| MP10A23SL | MS10A23S | 12-10 | 3.0 - 6.0 | Yes | Silver |
| MP10A23FL | MS10A23F | 12-10 | 3.0 - 6.0 | Yes | Gold Flash |
| MP10A23G5L | MS10A23G5 | 12-10 | 3.0 - 6.0 | Yes | Gold 5μ" |
| MP10A23G10L | MS10A23G10 | 12-10 | 3.0 - 6.0 | Yes | Gold 10μ" |
| MP10A23G15L | MS10A23G15 | 12-10 | 3.0 - 6.0 | Yes | Gold 15μ" |
| MP10A23G30L | MS10A23G30 | 12-10 | 3.0 - 6.0 | Yes | Gold 30μ" |
| MP10A23S-25 | MS10A23S-25 | 16-14 | 1.5 - 2.5 | No | Silver |
| MP10A23F-25 | MS10A23F-25 | 16-14 | 1.5 - 2.5 | No | Gold Flash |

| Tooling, Machined | |
|-------------------|------------------------------------------------|
| Part Number | Description |
| QXRT08 | Contact Extraction Tool, # 8 (Ø 3.6mm) Contact |
| M300BT | Hand Crimper |
| WA27-300BT-EP | Pneumatic Crimper |
| TP968 | Locator M3200BT and WA27-300BT-EP |

| Plating Options | |
|-----------------|------------------------------|
| Symbol | Plating |
| T | Tin Plating Over Nickel |
| S | Silver Plating Over Nickel |
| F | Gold Plated |
| G5 | Gold Plated (Thickness 5μ") |
| G10 | Gold Plated (Thickness 10μ") |
| G15 | Gold Plated (Thickness 15μ") |
| G30 | Gold Plated (Thickness 30μ") |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Standard Circular Connector](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[5M2530B10P](#) [600259N006](#) [600273N007](#) [6134-336-13149](#) [6134-337-11149](#) [6134-337-2390](#) [6134-341-17149](#) [6280-4SG-516](#) [6280-7SG-3DC](#)
[6290](#) [6291A](#) [66200A-10](#) [680-SMG](#) [681-PMG](#) [CXS3102A14S2P](#) [CXS3102A181S](#) [7251-6SG-300](#) [7271-6SG-300](#) [7282-3PG-300-CH3](#) [75-](#)
[474014-05S](#) [75-474618-01S](#) [75-474618-04P](#) [75-474618-04S](#) [799539-000](#) [MI8-SE](#) [805-005-07NF11-19PC](#) [805-005-07NF15-7PA](#) [8280-4PG-](#)
[516](#) [8280-7PG-519](#) [8282-5PG-519](#) [836783-1](#) [MP-4102-25P-C](#) [862256-1](#) [864019-2](#) [866857-1](#) [867865-1](#) [PT01SP-14-18P](#) [PT08P-14-5S](#)
[PTSF06SE-14-12S](#) [120-1833-000](#) [QCM019PC2DC012B](#) [1-2069279-1](#) [121583-0217](#) [121667-0020](#) [129591AU](#) [1000B BULK](#) [RD10A16-19-](#)
[P6CS051/1](#) [RD10A20-31-P8CS051/1](#) [RD16A14-12-S6CS051/2](#) [1301240290](#) [1301240347](#)