NOTES: I. MATERIALS AND FINISHES: 3. MECHANICAL: BODY & CONTACT - BeCu, GOLD PLATING INSULATORS - PTFE, NATURAL

THIRD ANGLE PROJ. 🕀 🖯

REVISIONS DESCRIPTION REV DATE ECN APPR RELEASE TO MFG. 06-Nov-19 Α 13541

EΗ

SCALE 3.500

A. DURABILITY: 100 CYCLES MIN. WHEN MATED FULL DETENT JACK 500 CYCLES MIN. WHEN MATED LIMITED DETENT JACK 1000 CYCLES MIN. WHEN MATED A SMOOTH BORE JACK

B. TEMPERATURE RANGE: -65°C TO +165°C

4. PACKAGING:

A. QUANTITY: SINGLE PACK MARKING: BAG TO BE MARKED

"AMPHENOL RF, SMP-FS2A-1950 AND DATE CODE". ROHS DIRECTIVE 2011/65/EU COMPLIANT

2.95 REF ---[0.116] TYP(2)

I.43 MAX. (-15 dB MIN) @ 18 - 26.5 GHz

I.50 MAX. (-14 dB MIN) @ 26.5 - 40 GHz

2. ELECTRICAL:

A. IMPEDANCE: 50 OHM

B. FREQUENCY RANGE: DC - 40 GHz

C. VSWR (RETURN LOSS) : 1.07 MAX. (-30 dB MIN) @ DC - 4 GHz | 1.22 MAX. (-20 dB MIN) @ 4 - 18 GHz

D.DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS, MIN.

-∅3.56 REF [0.140] INTERFACE PER-MIL-STD-348 SERIES: SMP PLUG TYP(2)

> $\begin{bmatrix} 0.542^{+0.010}_{-0.000} \end{bmatrix}$ REQUIRED JACK TO JACK SPACING FOR BLIND MATE APPLICATIONS

- 19.50 REF [0.768]

## **CUSTOMER OUTLINE DRAWING**

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

<0.5mm 0.5 - 6mm ± 0.05mm ±0.1mm 6 - 30mm 30 - 120mm ±0.2mm ± 0.3mm ANGLES ±1° NOTICE - These drawings, specifications, or other data (I) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

	MATERIAL	DRAWN	DATE
<pre>&lt;0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES <math>\pm 0.05</math>mm <math>\pm 0.1</math>mm <math>\pm 0.2</math>mm <math>\pm 0.3</math>mm <math>\pm 1</math>°</pre>		KRISHNA S	20-Nov-18
NOTICE - These drawings, specifications, or other data (1) are, and remain the	SEE NOTES	ENGINEER	DATE
property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they	REFERENCE	KRISHNA S	20-Nov-18
are given by Amphenol Corp. the furnishing of these drawings, specifications, or	EAR# 8528	APPROVED	DATE
The state of the s	REF: SMP-FSBA-1716	K. CAPOZZI	06-Nov-19
rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be	CONFIGURATION LEVEL: In Work	CAD FILE	
related to or disclosed by said drawings, specifications, or other data.	FINISH		

SMP STR ASSEMBLY			ММ	
	1			DR
SCALE: 18.0:1.0	SHEET 2 0	F 2		ı T
DWG SIZE			REV	

TITIF

Ar	mphenol RF
W	ww.amphenolrf.com
ORAWING NO.	SMP-FS2A-1950
ITEM NO.	SMP-FS2A-1950
PART NO.	SMP-FS2A-1950

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

5916-1103-603 5918-1103-000 5919-1503-000 651A505 82-5552 9030-9523-502 A0407000 R114703000W R125704000 R125771001

R141710000W R141723161 R141730000 R143730700 R143770000 R161703000W R161730000 R161753000W R161791530W

R201705000 R222705200 R222M40010W R223703180 R316754000 R405006000 R443162000 AD78TL HRM-513S 1996352-2

2157155-1 252169-75 AD158 2101130-1 252186 R114704000W R114720000W R125705001 R125705701 R125771000 R125771001W

R125791501W R127704001 R127.870.001 R127872001 R141717000 R142710000 R142723000 R143703000 R143704000 R143705700