



Dim.L = N x 3.81
 Dim.B = (N-1) x 3.81
 N= number of poles

poles Dim.	2P-6P	7P-12P	13P-18P	19P-24P
Dim.L	±0.15	±0.20	±0.25	±0.30
Dim.B	±0.10	±0.15	±0.20	±0.25

SIGN	DATE	DESCRIPTION	APPROVER
△	11/01'05	Electrical standard changed.	Marvin
△	04/20'06	2p to 6p with wedge is changed.	Marvin
△	06/06'06	2p to 6p with wedge is removed	Marvin
△	8/13'06	Added VDE standard	梁仁松
△	12/15'08	Flange screw changed from "-"solt type to "+/-"solt type	Kind
△	2010.07.12	The solid and Stranded wire is changed from16-26 to16-28	Chen Bo
△	2010.07.12	Rremove the CSA mark	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item a Clamp: Brass(CuZn) Ni plated
- Item b Terminal screw: Steel Zinc plating "-" slot type
- Item c Female contact: PhBz ,Tin plated
- Item d Terminal (housing): Thermoplastic (UL94V-0)
- Item e Terminal (cover): Thermoplastic (UL94V-0)
- △● Item f With flange screw:steel M2.5 Zinc plating "+/-" slot type

- △△ Electrical cULus/VDE
 - Voltage rating: 300VAC/300VAC
 - Current rating: 10A/10.5A
 - Wire range: 1.5mm²
 - △● Solid wire(AWG): 16-28/16-28
 - Stranded wire(AWG): 16-28/16-28
 - Torque: 3Lb-In/0.2Nm
 - Screw: M2
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV/2.5KV
 - Operating temperature: -40°C to +115°C
 - △● Safety Approval:

TJ xx 31x 2 xxxx G

- | | | | | |
|-----|-------------|---|-------------------|---------------------------------------|
| 02 | 2 CONTACTS | 0 | Black (RAL9005) | RoHS |
| 03 | 3 CONTACTS | 2 | Red (RAL3001/D) | Pb<40,000ppm |
| ... | ... | 3 | Orange(RAL2011/P) | 0000: "@" Logo |
| 24 | 24 CONTACTS | 4 | Yellow(RAL1018/A) | 000A: "ANYTEK" Mark |
| | | 5 | Green(RAL6018/T) | 0091: "ANYTEK" Mark |
| | | 6 | Blue (RAL5015/A) | Any special item by customer request. |
| | | 8 | Grey(RAL7035/D) | please contact sales department. |

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		TJ-3.81mm Series With flange				
PART NO.		TJxx31x2xxxxG		DWG NO.	8TJ0602	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
			Chen Bo 2010.07.12		X. ±0.50	
					UNIT: mm	X.X ±0.30
					SCALE: NONE	X.XX ±0.10
				SHEET: 01/01	REV: I	
					X° ±1°	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [734-104](#) [734-302](#) [8-141-P](#) [8426620000](#) [860505](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#)
[PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFH16150](#) [ELFP03110](#) [ELFP10210](#) [ELFT06250](#)
[ELVP03100](#) [1700410](#) [1700425](#) [1702246](#) [1717806](#) [1719600](#) [1734692](#) [1734795](#) [1740291](#) [1752441](#) [1752865](#) [1754144](#) [1760051](#) [1760336](#)
[1777701](#) [1783410](#) [1800227](#) [1801080](#) [1836888](#) [1848818](#) [1849079](#) [1860870](#) [1876327](#) [1896417](#) [1903096](#) [19346](#) [1946309](#) [1970579](#) [1973592](#)