



Dim.L = N x 5.08
 Dim.B = (N-1) x 5.08
 N= number of poles

| poles Dim. | 2P-6P | 7P-12P | 13P-18P | 19P-24P |
|---------------|-------|--------|---------|---------|
| Dim.L | ±0.10 | ±0.20 | ±0.30 | ±0.40 |
| Dim.B | ±0.10 | ±0.20 | ±0.25 | ±0.30 |

| SIGN | DATE | DESCRIPTION | APPROVER |
|------|------------|-----------------------------------------------------------|----------|
| △ | 01/25'05 | Part No. changed. | Marvin |
| △ | 06/26'06 | Current rating(cULus) is changed from 10A to 20A | Marvin |
| △ | 06/26'06 | Solid/Stranded wire(AWG) is changed from 12-22 to 12-24 | Marvin |
| △ | 8/10'06 | Added VDE and TUV standard. | 羅仁松 |
| △ | 12/15'08 | Flange screw changed from "-"solt type to "+/-"solt type | Kind |
| △ | 12/15'08 | Operating Temp. changed from -30°C +105°C to -40°C +115°C | Kind |
| △ | 2010.03.09 | Add the 2P mark | Jacke |

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material**
- Item ① Clamp: Brass(CuZn) Ni plated
 - Item ② Terminal screw: Steel Zinc plating "-" slot type
 - Item ③ Female contact: PhBz ,Tin plated
 - Item ④ Terminal Cover: Thermoplastic (UL94V-0)
 - Item ⑤ Terminal housing: Thermoplastic (UL94V-0)
 - △ Item ⑥ With flange screw: Steel Zinc plating M2.5"+/-" slot type
- △ Electrical cULus/VDE/TUV
- Voltage rating: 300VAC/300VAC/300VAC
 - △ Current rating: 20A/20A/20A
 - Wire range: 2.5mm²/0.34-2.5mm²
 - Solid wire(AWG): 12-24/14-22
 - △ Stranded wire(AWG): 12-24/14-22
 - Torque: 5Lb-In/0.5Nm/0.56Nm
 - Screw: M3
 - Wire strip length: 7-8mm
 - Withstanding Voltage: 1.6KV/2.5KV/2.5KV
 - △ Operating temperature: -40°C to +115°C
 - Safety Approval: cULus VDE TUV
 - Use with 0Q1.0x1.0mm square pin, Withdrawal force:200 - 500gf /pole



TJ xx 51x 2 xxxx G △

- | | | | |
|----------------|----------|---------------------------------------|--------------|
| 02 2 CONTACTS | 0 Black | 0000: "@" Logo | RoHS |
| 03 3 CONTACTS | 2 Red | 000A: "ANYTEK" Mark | Pb<40,000ppm |
| ... | 3 Orange | Any special item by customer request. | |
| 24 24 CONTACTS | 5 Green | please contact sales department. | |
| | 6 Blue | | |
| | 8 Grey | | |

| | | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|----------------------|---------------------|
| ANYTEK | | CUSTOMER COPY | |
| ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD | | | |
| TITLE | TJ-5.08mm Series With flange | | |
| PART NO. | TJxx51x2xxxxG | DWG NO. | 8TJ0009 |
| APPROVED | CHECKED | DESIGNED | DRAWN |
| | | Jacke 2010.03.09 | Jacke 2010.03.09 |
| SHEET: 01/01 | | UNIT: mm | Tolerance |
| | | SCALE: NONE | X. ±0.50 |
| | | REV: G | X.X ±0.30 |
| | | | X.XX ±0.10 |
| | | | X* ±1* |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [734-104](#) [734-302](#) [8-141-P](#) [8426620000](#) [860505](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#)
[PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFH16150](#) [ELFP03110](#) [ELFP10210](#) [ELFT06250](#)
[ELVP03100](#) [1700410](#) [1700425](#) [1702246](#) [1717806](#) [1719600](#) [1734692](#) [1734795](#) [1740291](#) [1752441](#) [1752865](#) [1754144](#) [1760051](#) [1760336](#)
[1777701](#) [1783410](#) [1800227](#) [1801080](#) [1836888](#) [1848818](#) [1849079](#) [1860870](#) [1876327](#) [1896417](#) [1903096](#) [19346](#) [1946309](#) [1970579](#) [1973592](#)