

QDC-2 QUICK DISCONNECT CORD



- UL listed
- Heavy duty cables
- Non-ferros metal blades
- Stainless steel sash chains
- Corrosion resistant contacts
- Overall length approx. 21”
- Mounting block - epoxy potted for low resistance

Application

The QDC-2 Quick Disconnect Cord is designed for use on overhead doors, gates, and any other opening that cannot be protected by other methods. The QDC-2 is designed to provide years of reliable service. It incorporates a proven design with heavy duty corrosion resistant contacts. The rugged connector system and heavy duty cables will withstand the harshest treatment and environments. It is suitable for both indoor and outdoor applications. The heavy duty cables have successfully withstood bending cycle test of over 2000 cycles.

Specifications

Model	Stock Number	Contact Rating	Wire Size
QDC-2	4300020	1 Amp @ 24VDC	18 AWG 2 conductor PVC Insulated/jacketed

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Switch Actuators](#) category:

Click to view products by [Amseco](#) manufacturer:

Other Similar products are found below :

[LW1B-A0L](#) [LW1B-M0](#) [680-4000-00](#) [704.012.618](#) [704.411.018I](#) [704.412.0](#) [704.633.1](#) [704.730.1](#) [704.733.0](#) [84-1221.7](#) [862.8102](#) [G6083](#)
[9PA24](#) [A0107X](#) [A019307](#) [ADC-418G](#) [12MA7](#) [ASDHYY-B](#) [HW1F-3G](#) [HW1M-L2222](#) [HW4S-31L](#) [200-.704-00](#) [JS-10008](#) [JS-10083](#) [JS-10118](#) [JS-10133](#) [JS-10277](#) [JS-10389](#) [JS-150](#) [JS-552](#) [JS-555](#) [JS-68](#) [JS-6-B](#) [JS-91](#) [JS-94](#) [22-211.011](#) [9001KXSDC](#) [92-458.500](#) [SAPT654133](#)
[2PA3](#) [SW53AA2](#) [302561](#) [LW2L-A0](#) [3E-12.0](#) [468-10243-001](#) [51-030.005](#) [JM-13](#) [JS-10120](#) [JS-138-B](#) [JS-143-B](#)