

## DEMO MANUAL DC1767

LTC2997 Remote/Internal Temperature Sensor

### DESCRIPTION

Demonstration circuit 1767 features the LTC<sup>®</sup>2997, a high accuracy, analog output, temperature sensor.

DC1767 is designed to allow easy evaluation of the LTC2997.

# Design files for this circuit board are available at http://www.linear.com/demo

𝕶, LT, LTC, LTM, Linear Technology and the Linear logo are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

### **QUICK START PROCEDURE**

#### **Jumper Settings**

D+/D-: These jumpers select which temperature input connects to the LTC2997. INT uses the internal temperature sensor, EXT uses an off-board sensor connected to the D+/D- analog inputs, and Q1 uses the transistor stuffed in Q1 (the MMBT3904 by default).

### **Analog Connections**

Analog signal connections are made via the row of turret posts along the edges of the board.

GND: (2 turrets) These turrets connect directly to the internal ground planes.

VCC: Connect a 2.25V to 5.5V power supply to this turret.

D+/D-: Should be set to EXT. This is where the external diode should be connected.

VREF: Output Only. 1.8V ouput that can drive up to  $\pm 200 \mu A$  of load.

VPTAT: The voltage on this turret is proportional to the sensor's absolute temperature, with a slope of 4mV/K. VPTAT can drive up to a  $\pm 200\mu$ A load and up to 1000pF capacitive load.



Figure 1. Proper Measurement Equipment Setup



### **PARTS LIST**

ITEM	QTY	REFERENCE	PART DESCRIPTION	MANUFACTURER/PART NUMBER
1	1	C1	CAP., X7R, 0.1µF, 10V 20% 0603	AVX, 0603ZC104MAT
2	1	C2	CAP., X7R, 470pF, 10V 10% 0603	AVX, 0603ZC471KAT2A
3	7	E1, E2, E3, E4, E5, E6, E7	TESTPOINT, TURRET, 0.094, PBF	MILL- MAX, 2501-2-00-80-00-00-07-0
4	2	JP1, JP2	HEADER, 3 PIN 0.079 DUAL ROW	SAMTEC, TMM-103-02-L-D
5	1	Q1	XISTOR MMBT3904 SOT-23	ON SEMI., MMBT3904LT1G
6	1	R1	RES., CHIP, 1k, 1/10W, 5% 0603	YAGEO, RC0603JR-071KL
7	1	U1	IC, LTC2997IDCB	LINEAR TECH., LTC2997IDCB#TRPBF
8	2	XJ1, XJ2	SHUNT, 0.079" CENTER	DEMO CIRCUIT 1767A
9	1		FAB, PRINTED CIRCUIT BD	
10	2		STENCIL (TOP & BOTTOM)	STENCIL DC1767A





### **SCHEMATIC DIAGRAM**



TECHNOLOGY

Information furnished by Linear Technology Corporation is believed to be accurate and reliable. However, no responsibility is assumed for its use. Linear Technology Corporation makes no representation that the interconnection of its circuits as described herein will not infringe on existing patent rights. dc1767f

3

DEMO MANUAL DC1767

#### DEMONSTRATION BOARD IMPORTANT NOTICE

Linear Technology Corporation (LTC) provides the enclosed product(s) under the following AS IS conditions:

This demonstration board (DEMO BOARD) kit being sold or provided by Linear Technology is intended for use for **ENGINEERING DEVELOPMENT OR EVALUATION PURPOSES ONLY** and is not provided by LTC for commercial use. As such, the DEMO BOARD herein may not be complete in terms of required design-, marketing-, and/or manufacturing-related protective considerations, including but not limited to product safety measures typically found in finished commercial goods. As a prototype, this product does not fall within the scope of the European Union directive on electromagnetic compatibility and therefore may or may not meet the technical requirements of the directive, or other regulations.

If this evaluation kit does not meet the specifications recited in the DEMO BOARD manual the kit may be returned within 30 days from the date of delivery for a full refund. THE FOREGOING WARRANTY IS THE EXCLUSIVE WARRANTY MADE BY THE SELLER TO BUYER AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. EXCEPT TO THE EXTENT OF THIS INDEMNITY, NEITHER PARTY SHALL BE LIABLE TO THE OTHER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

The user assumes all responsibility and liability for proper and safe handling of the goods. Further, the user releases LTC from all claims arising from the handling or use of the goods. Due to the open construction of the product, it is the user's responsibility to take any and all appropriate precautions with regard to electrostatic discharge. Also be aware that the products herein may not be regulatory compliant or agency certified (FCC, UL, CE, etc.).

No License is granted under any patent right or other intellectual property whatsoever. LTC assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or any other intellectual property rights of any kind.

LTC currently services a variety of customers for products around the world, and therefore this transaction is not exclusive.

**Please read the DEMO BOARD manual prior to handling the product**. Persons handling this product must have electronics training and observe good laboratory practice standards. **Common sense is encouraged**.

This notice contains important safety information about temperatures and voltages. For further safety concerns, please contact a LTC application engineer.

Mailing Address:

Linear Technology 1630 McCarthy Blvd. Milpitas, CA 95035

Copyright © 2004, Linear Technology Corporation

dc17671

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Temperature Sensor Development Tools category:

Click to view products by Analog Devices manufacturer:

Other Similar products are found below :

 EVAL-ADT7516EBZ
 EVAL-ADT75EBZ
 T20321SS2B
 T2016P2CRRXC4S2
 MAX1455EVKIT-NS
 DC2507A
 DS18B20EVKIT#

 MAX6654EVKIT
 EV-TEMPSENSE-ARDZ
 MAX1617AEVKIT
 BB-WSK-REF-2
 MCP9800DM-TS1
 TMPSNSRD-RTD2
 MIKROE-2273

 MIKROE-2501
 MIKROE-2539
 MIKROE-2554
 DPP201Z000
 DPP901Z000
 1899
 EV-BUNCH-WSN-2Z
 DPP904R000
 KIT0021
 SEN0206

 SEN0227
 MIKROE-2769
 3251
 SEN-13314
 3263
 SEN0137
 LM20XEVM
 3328
 TMP708EVM
 BOOSTXL-TMP107
 DC1785B
 MHUM-01

 3538
 DPP201G000
 DFR0066
 WPP100B009
 SDT310LTC100A3850
 SI7005EVB-UDP-M3L1
 2857
 1782
 2652
 269
 3245
 3622
 3648

 3721