

NUMBER


TDS-3533/B

PRODUCT DESCRIPTION

FCCN convoluted metal core conduit without cover

PRODUCT RANGE

Multiflex product range



Square locked

Galwin 5 - 1046 AW Amsterdam
P.O. Box 8155 - 1005 AD Amsterdam
The Netherlands

Tel.: +31 (0)20 586 3586

Fax: +31 (0)20 688 1126

Email: sales@anamet.nl

Website: www.anameteurope.com

Vat Reg NL001442429B01

Trade register Amsterdam 330 60 401

FCCN	DIAMETRE		BENDING RADIUS (CL)		SMALL COIL		STANDARD COIL		LARGE COIL		WEIGHT (kg/m)
	Size (dn)	Inside (mm)	Outside (mm)	Static (mm)	Dynamic (mm)	Metre	Article No.	Metre	Article No.	Metre	
10	7,0	9,0	20	30	-	-	-	-	50	302.610.5	0,08
12	10,0	13,0	30	45	-	-	-	-	50	302.612.5	0,13
16	13,0	16,0	45	60	-	-	-	-	50	302.616.5	0,15
20	17,0	20,5	50	70	10	302.620.1	30	302.620.3	50	302.620.5	0,20
25	21,2	25,0	60	80	10	302.625.1	30	302.625.3	50	302.625.5	0,26
32	28,1	32,0	70	90	10	302.632.1	30	302.632.3	50	302.632.5	0,33
40	37,7	43,0	90	120	10	302.640.1	30	302.640.3	-	-	0,52
50	48,4	54,0	110	140	10	302.650.1	30	302.650.3	-	-	0,64

APPLICATION AREA

FCCN is a galvanised steel square locked conduit. This general purpose conduit is very flexible and has many applications in industrial applications, construction, underfloor wiring systems and industrial machines.

MATERIAL & CONSTRUCTION:

Construction: Galvanised steel core, square-locked.

Cover specifications: None.

Temperature: -55 °C till +300 °C.

Colour: Metal.

CLASSIFICATION ACCORDING TO NEN-EN-IEC 61386:

Compression resistance: Class 3, Medium (750N).

Impact resistance: Class 3, Medium (2J).

Tensile strength: Class 3, Medium (500N).

Protection class: IP 40.

Issued by:

Seyda Simsek

Marketing Communications Manager

Approved by:

Rob Guichelaar

Technical Manager

Date:

August 1, 2019

Page:

1 of 1



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Non-Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [ANAMET EUROPE](#) manufacturer:

Other Similar products are found below :

[601203-000](#) [CTA-0053](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-123-06](#) [120-123-10](#) [120-125-12BL](#) [120-125-12R](#) [120-125-20R](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-105-1-1-06BE](#) [120-105-1-1-06CE](#) [120-108-10B](#) [120-116-1-1-06BP](#) [120-116-1-1-10BP](#) [120-116-1-1-12BF](#) [120-123-12](#) [120-125-09](#) [120-125-12](#) [120-125-12Y](#) [120-125-52BL](#) [120-S002-12](#) [HC1B-7008-0375-0](#) [120-S001-09](#) [120-S002-09](#) [121-101-1-1-56BFC](#) [121-101-1-1-64BFC](#) [121-103-1-1-12BFTTH](#) [RAY-90-3.0\(100\)](#) [20675-2](#) [8S42-100FR-CS8184](#) [SAS-115-1-1048-1X](#) [SAS-160-1-1048-1X](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [3-1991136-0](#) [561-SL1000PP](#)