

Surface Mount Termination 45 Watts



Features:

- RoHS Compliant
- 45 Watts
- DC 6.0 GHz
- AIN Ceramic
- Non-Nichrome Resistive
 Element
- Low Return Loss
- 100% Tested
- Small Size

Description

The C45N50Z4 is a high performance AIN surface mount termination. The termination is well suited to all cellular frequency bands such as; AMPS, GSM, DCS, PCS, PHS and UMTS. The high power handling makes the part ideal for terminating high power 90 degree couplers and for use in microstrip circuits. The termination is also RoHS compliant!


General Specifications

Desisting Flammant	This is films
Resistive Element	Thick film
Substrate	AIN Ceramic
Terminal Finish	Matte Tin over Nickel Barrier
Operating Temperature	-50 to +150°C (see de rating chart)
Tolerance is ± 0.010 ", unless otherwise specified. Designed to meet or exceed	

applicable portions of MIL-E-5400. All dimensions in inches.


Electrical Specifications

Power:	45 Watts
Frequency Range:	DC – 6.0 GHz
Return Loss:	>20 dB DC – 5.0 GHz >15 dB 5.0 – 6.0 GHz







Typical Performance:




Power De-rating:



Mounting Footprint and Procedure:



Tape and Reel



USA/Canada: Toll Free: Europe:

(315) 432-8909 (800) 544-2414 +44 2392-232392

Available on Tape and Reel For Pick and Place Manufacturing.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Frequency/RF Resistors category:

Click to view products by Anaren manufacturer:

Other Similar products are found below :

800-50T-S 10-100RV-S E250N50X4 250-100RM-S 250-50RM-S 150-100RL-S A4B50X1A 10-50TV G150N50W4B FC1206E8450FGW0 R1A06031000G5AR 060120A25X50-2 C45N50Z4 A5B50X1A 100200-4Z50-2 C150N50Z4 30-100R 60-50TP-S 100N50TW E200N50X4 250375-4Z50-2 60-50TPR MIC1000AFLMGNHWS FT10301N0050J CS12010T0100GTR C8A50Z4B CW12010T0100GTR FR10515N0050JBK FR10515N0100JBK FR10800N0100JBK FT10517N0050J01 FT10517N0050JBK FT10800N0050J02 LT11020T0050JBK LT12010T0050JBK 250375-4X50-2 30-100R-S 400-50T 40-50TPP 60-50TP C10A50Z4 C16A50Z4 C1A50Z4 C50A50Z4 G250N50W4 G450N50W4 J100N50X4B K100N50X4B R2B130850R0J4J0 R3A100550R0J5G0